A Professional Press Publication

# Professional

#### APRIL 1988


- Connectivity And Communication
- PC Compatibility Standards
- TurboIMAGE Logging



#### **WORKSTATIONS**

HD'e Now

oSRX



# What lucky numbers are the perfect match for your HP 3000?



#### Zentec's 8392. Available now at \$849!

The Zentec 8392 is <u>everything</u> the HP user needs and more—for less. Immediate delivery brings you a 14-inch diagonal screen, HP-compatible keyboard layout, ergonomic design, and complete compatibility with HP application software.

With features that outperform all others, the Zentec 8392 also provides ANSI X3.64

compatibility for operation with your DEC\* computer as well. It's so flexible, reliable, and efficient, your cost-per-seat is noticeably lower in the multiuser environment.

Your Zentec 8392 is key selectable for both 80 and 132 columns with


standard memory of 8 pages. We back our promise with a full one-year warranty and cost-effective maintenance contracts available throughout North America and Canada through Dow Jones Service Company.


Install the Zentec 8392 and your search for the perfect match is complete.

Call 800-332-5631 (outside Calif.) or 408-727-7662 for information and the name of your nearest authorized distributor.

THE CUSTOM TERMINALS COMPANY

European inquiries, call our International Headquarters in the U.K. at 44-4867-80666. DEC is a registered trademark of Digital Equipment Corporation.





# ONTENTS

**APRIL 1988** 

VOL. 2, NO. 4

28 FOCUS: Learning LAN Bridges by Tad Witkowicz

The key to true LAN connectivity.

34 FOCUS: Compatibility by Don Person

PC compatibility standards: the best and the worst of the microcomputer compatibility sideshow.

38 FOCUS: Connectivity and Communication by Michael M. Dediu
Improving research and development.

46 The New 350/835 TurboSRX by Andy Barlow
HP's latest 3-D graphics workstation.

52 IPRINT
by Ashley Grayson and Dafydd ab Hugh
Forms follow function keys.

62 Multitasking Performance by Joe Bormel

Monitoring performance when running more than one program on the Integral.

66 XDS, Long Pointers and C by Tim Chase
Solving portability problems with extended data addressing.


# DEVELOPMENT: TurboIMAGE Logging Editorial 8 by Lisa Burns Hartman Industry Watch 10 Data insurance 74 News & Trends 14 New Products 22 Spectrum News 73 Product Showcase 93 Advertisers Index 96 Calendar 96



INDUSTRY WATCH: HP battles for the lead in education's CMI market . . . 10


#### On The Cover:

This month's cover illustration is the work of Michael Schroeder, Reading, PA.



**ENTER 147 ON READER CARD** 

#### **NEED AN EXTRA COMPUTER WORKSTATION?**



- Expandable 256K to 2 MegaBytes
- Multiple Copy and Plot Queuing
- · Bidirectional Buffering
- Fast Installation/Easy Operation
- Automatic Self-Test
- 30 Day Money-Back Guarantee
- 1 Year Warranty 24 Hour Service

#### MicroPlot 80 HPIB Buffer

256K - \$895

512K - \$1095

MicroPlot 80A HPIB Buffer MicroPlot 55 Serial Buffer

256K - \$995 1 MB - \$1645 512K - \$1245 2 MB - \$2245 Chances are you're sitting in front of it - waiting for a slow printout or plot to finish. The MicroPlot series of buffers eliminate the waiting. You keep working while the plotter or printer is running. The result? System availability is increased by a factor of 5 to 20.

Three models save you money while you're saving time. The MicroPlot 80 HPIB buffer offers intelligent performance at below dumb buffer prices. Copy, Pause, Multiple Plot Queuing, and Purge features are standard. Expandable to 512k, the MicroPlot 80 is ideal for large printing or small plotting applications. The MicroPlot 80A includes all MicroPlot 80 features plus full buffer and I/O status indicators, custom firmware support, and Pen-Up pause mode. Memory expansion to 2MBytes and compatibility with major software packages make the MicroPlot 80A the logical choice for CAD/CAM/CAE applications. The MicroPlot 55 Serial buffer gives RS-232 interface users all the operational features of the MicroPlot 80A PLUS automatic "learn endof-plot" and manual "mark end of plot" features.

#### INTELLIGENT INTERFACES, INC.

P.O. Box 1486, Stone Mountain, GA 30086-1486 1-800-842-0888 In Georgia Call (404) 381-9891

Telex: 910 2502628 INTELLIGENT UD ENTER 118 ON READER CARD

Dealer and Value Added Reseller Inquiries Welcome



Publisher: Carl B. Marbach Editorial Director: R.D. Mallery

#### Editorial

MANAGING EDITOR Lonni Wright
COPY EDITOR Karen Detwiler
EDITORIAL ASSISTANT Randi Koenig
CONTRIBUTING EDITORS Lisa Burns Hartman,
Don Person

CONTRIBUTORS Andy Barlow, Joe Bormel, Tim Chase, Dr. Michael M. Dediu, Ashley Grayson, Dafydd ab Hugh, Larry McClain, Tad Witkowicz

#### Design

#### DESIGN/PRODUCTION DIRECTOR

Leslie A. Caruso

DESIGN/PRODUCTION ASSOC. Ruth Ann Leiby
ART/PRODUCTION ASSOC. Timothy M. Kraft
ART ASSISTANT Sue Ann Rainey
PRODUCTION ARTIST Richard Kortz
TRAFFIC/PRODUCTION ASST. Joann Corvino
TYPESETTING MaryEllen Springer, Diana Pohl

#### Circulation & Administration

VICE PRESIDENT Peg Leiby
MARKETING DIRECTOR Mary Wardlow
CIRCULATION MANAGER Betsy Ellis
CIRCULATION FULFILLMENT MANAGER
Margie Pitrone
CONTROLLER Andrea Beneke
MIS MANAGER John F. McGlinchey

#### PROFESSIONAL PRESS, INC.

For information on how to contact your sales representative, see page 96. Editorial, advertising sales and executive offices at 921 Bethlehem Pike, Spring House, PA 19477 **(215)** 542–7008 TWX 910 333 9522 **Easylink** 62805174 FAX (215) 628–2845

HP PROFESSIONAL ISSN 0986145X is published monthly by Professional Press, Inc., 921 Bethlehem Pike, Spring House PA 19477. Subscriptions are complimentary for qualified U.S. and Canadian sites. Single copy price, including postage, \$4. One year subscription rate \$30 U.S. and Canada; \$60 foreign. All orders must be prepaid. Second Class postage paid at North Wales, PA, and additional mailing offices. POSTMASTER: Send all correspondence and address changes to HP PROFESSIONAL, PO. Box 445, Spring House, PA 19477. COPYRIGHT © 1988 by Professional Press, Inc. All rights reserved. No part of this publication may be reproduced in any form without written permission from the publisher. All submitted manuscripts, photographs and/or art work are sent to Professional Press, Inc. at the sole risk of the sender. Neither Professional Press, Inc. nor HP PROFESSIONAL magazine are responsible for any loss or damage. HP PROFESSIONAL is an independent journal not affiliated with Hewlett-Packard Company. HP and Hewlett-Packard are registered trademarks and HP PROFESSIONAL is a trademark of Hewlett-Packard Company.





#### ON-LINE HELP, 24 HOURS A DAY



You know that sinking feeling you get when it's 3:00 am and you realize that your main database has been corrupted? And you don't know where? Or how to fix it? And you have fifty users coming in at sunrise?

We sure do, and that's why we implemented round-the-clock, round-theworld support for you DBGENERAL users, to assist you in diagnosing and repairing, restructuring, and managing your IMAGE and TurboIMAGE databases.

We put our expertise and experience to work for you 24 hours a day because problems do not always occur while the sun is shining: databases die in the dead of night and chains break at the break of dawn. And night time is the right time for database maintenance and repair.

Our technical support has meant the difference between up and down for hundreds of you. As you know, we do not charge a premium for this service it's included in your regular product maintenance.

We hope you never need to call our support line, but know you rest assured that you've got the best database product—and the support to match.



Buffalo Cincinnati Houston Los Angeles New York

(716) 689-6882 (513) 891-7867 (713) 621-2808 (213) 432-7713 (718) 398-1352

Australia Belgium Canada France

61 (2) 868-1877 32 (56) 41-83-99 (613) 448-2333 33 (1) 4588-8830 Germany 49 (89) 6088-3077 Holland Israel Mexico Scandinavia

31 (30) 52-1114 972 (3) 413-762 52 (5) 254-3274 46 (9) 910-364-80 44 (22) 346-0881

# What if there were more powerful forces at work?

Introducing the full range of Vectra PCs from Hewlett-Packard.

Exceptional power.

That's the defining characteristic of our new, comprehensive line of industry-standard PCs.

From the 20-megahertz 80386-based system, through the 12-megahertz 80286, to our entry-level and portable models.

And this line not only has the speed to get the job done, but the expandability, too.

For instance, the memory of our 12 MHz 80286-based model can be expanded up to 8 megabytes. And, im-

portantly, all 8 can be accessed at the same 12 MHz for faster performance.

With eight expansion slots and up to 620 megabytes of mass storage, the 80386 models' built-in expandability will handle your most demanding applications.

But there's more than just power. There's the compatibility to meet

SuperVisor



Mid-level, 80286 based

today's standards while anticipating tomorrow's.

Both desk-top and floor-mount models support 5.25" and 3.5" internal flexible drives, while the 80286 and 80386 machines will run OS/2.

And every single HP Vectra PC offers something no other PC can: HP's



HP Vectra RS/16 and RS/20 Personal Computers High-level, 80386 based

Choice of 16 or 20 MHz, 80386-

we never stop

asking

based microprocessors
• Up to 620 Mbytes hard disc storage supported—17 millisecond average seek time for 100 through 620 Mbytes

• Up to 16 Mbytes of 32-bit mem-y using interleaved page-mode DRAM

8 accessory slots for expansion, 330-watt peak power supply, and six half-height mass storage shelves

 Both 5.25 and 3.5 inch flexible disc drives supported internally Separate mouse/graphics tablet

port included • 80387 and Weitek 1167 coprocessor support

HP Vectra ES and ES/12 Personal Computers Mid-level, 80286 based

Choice of 8 or 12 MHz, 80286-based microprocessors

based microprocessors

• Up to 8 Mbytes of expanded memory, accessed at 12 MHz in the Vectra ES/12 PC, supporting LIM 4.0 expanded memory specification without using I/O slots

• 7 accessory slots for expansion
• 20 and 40 Mbyte hard disc

Both 5.25 and 3.5 inch flexible disc drives supported internally
 Separate mouse/graphics tablet

long established reputation for quality and reliability.

Advanced surface-mount technology and VLSI are just two examples of how this reputation is being upheld.



Portable, 8086 compatible

PCs like this are the product of a philosophy that never stops asking "What if ...?" to create a better computing tool for your business.

Just call for the location of your nearest HP sales office or dealer

at: 1800 752-0900, Dept. 2340. More power to you.

HP Vectra CS Personal Computer Entry-level, 8086 compatible • 7.16 MHz, 8086-compatible microprocessor with zero wait states

 Up to 8 Mbytes of expanded memory, addressable via LIM 3.2 expanded memory specification

 7 accessory slots for expansion 20 Mbyte hard disc modelBoth 5.25 and 3.5 inch flexible

disc drives supported internally HP Portable Vectra CS Personal Computer

8086 compatible • 7.16 MHz, 8086-compatible

microprocessor with zero wait states

• Up to 2 Mbytes expanded memory, addressable by LIM 3.2

• Four I/O slots

• Supports two 3.5 inch flexible disc drives

 20 Mbyte internal hard disc model available

• Up to 10 hour battery life

IBM style keyboard

AutoCad is a U.S. trademark of Autodesk Inc. PageMaker is a U.S. trademark of Aldus Corp

**ENTER 117 ON READER CARD** 



## It's How You Make It

You're a giant company by many a measure. Your sales are right up there on the Fortune list. But you have an identity crisis. You're fragmented: instruments, peripherals, computers, calculators . . . Even the individual product lines are fragmented: commercial vs. technical. Worse, the customers are fragmented. Just ask a commercial user if he's ever heard of a workstation, or what he might do with one. There are many instrument customers who don't even know HP makes computers!

Nothing in the preceding paragraph is news to anyone. The news is that change is in the wind and the wind is blowing.

The challenge to be met is clear. Catch Digital while Digital catches IBM. That will never be done by selling to the installed base. Legions of new customers must be found while losing none of the existing ones.

There are only three or four classes of new customers: truly new, those who never had a computer before (or only a PC); DEC customers; IBM customers; everyone else.

Truly new customers are best served by computer stores. The cost of sales to these is prohibitive. OEMs and VARs can pick these off as they graduate from their ATs. Wisely, HP is still promoting its relationship with the VAR community, unlike Digital. Winning customers away from IBM's midrange is easier than it seems. DEC has been doing it for years with awesome success. Just wait until the customer has more than one machine and needs to communicate!

Winning customers away from DEC is another matter. DEC has been charging hard at a single goal with a single plan for about 10 years now, spending dozens of billions on the way. Its VAXclusters are an ironclad lead. Until HP can field a response to clustering with real file sharing, it's gonna be tough indeed. Getting the rest of the world is just a matter of providing a good UNIX and HP's superior platforms and service, service, service.

Healing the rifts between commercial and technical, between instrument and computer, etc., is another big job. If you are one company, your employees have to see it when they look around. Only after you heal the rift in the minds of your employees can you begin to do the same in the minds of your customers. UNIX will help, but existing commercial customers must see a seamless networking between MPE and UNIX. They must find things to do with workstations that can benefit their MPE operations. Workstations are a natural for DEC users because they're just another VAX.

HP recently was hailed as the only company capable of catching DEC. We knew that when we started this magazine. It's nice to see the financial community agreeing with us as we approach our first anniversary.

HP PROFESSIONAL

# Don't let another fast Falcon Disk Subsystem pass you by.



If poor performance and insufficient disk capacity have got your HP 3000 bogged down, try a bird of a different feather — EMC's Falcon Disk Subsystems. High speed Falcon subsystems make HP 3000 systems fly while saving you more than just chicken feed!

With state-of-the-art Winchester technology and EMC's proprietary caching algorithm, Falcon disk subsystems really get your system performance off the ground. Featuring four megabytes of controller cache, the Falcon soars through even the worst I/O bottlenecks.

Every situation is different. No one has the same storage requirements, so now there is a whole family of Falcons to choose from. Pick the capacity to fit your needs. You can even configure up to 5.34 gigabytes in a single cabinet.

#### The Falcon Family

Falcon 400 ~ 406 megabytes Falcon 600 ~ 625 megabytes Falcon 800 ~ 890 megabytes Falcon 1200 ~ 1.25 gigabytes

Sealed Winchester technology makes high maintenance costs a thing of the past. In some cases, you can even buy or lease a Falcon for what you are now spending just to maintain and operate your older drives. And a 50,000 hour Mean Time Between Failure rating

makes the Falcon the most reliable subsystem in its field.

To further assure reliability, every Falcon is fully compatible with HP's sophisticated fault isolation diagnostics. EMC's network of Sales and Service locations worldwide provides on-the-spot service.

Falcon Series disk subsystems are available today. Don't let another one pass *you* by, join the thousands of satisfied HP 3000 users who already have a Falcon up and flying.

For more information, contact your local EMC sales representative or call:

**1-800-222-EMC2 Ext. 2290** (In Mass., 617-435-1000)



**The System Enhancement Company.**HP is a registered trademark of Hewlett-Packard, Inc. Falcon is a trademark of EMC Corporation.

ENTER 136 ON READER CARD

#### INDUSTRY WATCH

Larry McClain

# Education's CMI Market

HP has long been an aggressive player in the multibil-

lion-dollar education market. The company currently has more than 400 educational accounts — about 60 percent of which are in the college and university ranks, the rest in public school districts (kindergarten through 12th grades). In recent months, HP has shown heightened interest in the latter group. Significant growth in computer spending is projected for America's 80,000 public schools, especially for systems that provide Computer Managed Instruction (CMI). Hewlett-Packard already is the number one CMI vendor in California and it's vying with IBM and DEC for that distinction nationwide.

Minicomputer-based CMI lets teachers and administrators determine how students throughout the district are faring when their skills are measured against specific learning objectives. CMI often gets mistakenly lumped with another acronym popular among educators — Computer Assisted Instruction (CAI). With CAI, a computer or terminal is used to present instructional material directly to the student. While this has proven beneficial in some respects, it hasn't done much to reduce teachers' paperwork or help them shape curriculum to district objectives. CMI, on the other hand, is an information management system designed to assist the educator in the ongoing process of managing instruction.

"Comparing CMI to CAI is a bit like comparing today's physicians to turn-of-the-century doctors," says Tim Hughes of Abacus Educational Systems (Denver, CO), which offers a CMI



Dr. Larry Lawrence uses a Vectra PC and HP LaserJet printer with an HP 3000 minicomputer. He's working to integrate computer-managed instruction at the laboratory elementary school of the UCLA Graduate School of Education.

package for the HP 3000 family. "Doctors back then could take your temperature and do a few basic things, but they didn't have a CAT scan."

CMI's bread-and-butter applications include organization of curriculum, test generation, exam scoring and diagnostic data on student achievement.


Curriculum objectives usually are set at the district level, often by a committee.

For example, students in thirdgrade math should know how to add, subtract, multiply and divide competently. To ascertain whether they've mastered those skills, administrators first enter test items into the district's HP 3000. Terminals (or Vectra PCs) then are installed at the various school sites. At each terminal, there's also an optical mark reader. Teachers access the 3000, generate the test they want and print it on a LaserJet. Students record their multiple-choice answers on a form the mark reader will accept. Teachers then take the answer sheets back to the terminal and feed them to the card reader. The CMI test databases enable both teachers and administrators to generate a variety of sophisticated reports to see whether district goals are being met.

SEVERAL RECENT TRENDS have made school administrative computing — and especially CMI — a very hot market.

Continued.

# Downloading as easy as 1-2-3.





## Introducing DataExpressJr., the start of something big.

1. FOUNDATION: DataExpressJr. is the ideal foundation for your information center solution. IMACS provides a sophisticated yet inexpensive way for the end user to extract HP 3000 data, to compute, reformat and download to Lotus 1-2-3.®

2. STRUCTURE: DataExpressJr. is structured to increase productivity in your company immediately. Its use of Lotus-like terminology and processes provides familiarity for the end user. DataExpressJr.

has a controlled interface to an IMAGE™ database and, with the use of Reflection™, it can completely automate the PC download.



3. BUILDING: This extract-only program anticipates your changing system requirements. DataExpressJr. is completely compatible with other members of the highly successful DataExpress product family. This compatibility provides over

twenty different product feature levels and options to build with as your needs grow.

In short, it's as easy as 1-2-3. You can use function keys to select data from the menus and DataExpressJr. reformats and

downloads it to your PC, automatically when you are using  $Reflection^{\mathsf{TM}}$ . You can even generate a report from the data.

It's all you need in your HP 3000. Talk to IMACS about using DataExpressJr. as the foundation of your information center.

You've been asking for it ... now you can get it ... from IMACS.



ENTER 134 ON READER CARD



IMACS SYSTEMS CORPORATION 4676 Admiralty Way, Suite 516 Marina Del Rey, CA 90292 (213) 823-4577

#### IMX SYSTEMS CORPORATION

London, England (010) 541-0242 Telex 51-944017 Calgary, Canada (403) 259-2478 Telex 03-827973

IMX International Rotterdam The Netherlands (010) 412-3642

DataExpress and DataExpress.Jr. are trademarks of © IMACS SYSTEMS CORPORATION. LOTUS 1-2-3 is a registered trademark of Lotus Development Corporation. Reflection is a trademark of Walker, Richer & Quinn, Inc IMAGE is a trademark of Hewlett-Packard Co.

Foremost is the near panic over the quality of the nation's schools, a fever that began with the 1983 report, A Nation At Risk. After reading it, legislators in several states passed bills mandating greater accountability from public schools. This coincides with rising enrollments from the '80s "Baby Boomlet" that are already putting increasing pressure on public school resources.

According to Joseph Moriarty of the Kerry Consulting Group (Claremont, CA), a firm specializing in educational computing, "CMI is increasingly required just to stay even with the requirements for accountability."

Many lawmakers see computerization as crucial to achieving the necessary improvement in public schools. Several states have earmarked sizable sums for computer acquisition in the schools. There's even one Federal bill — the Computer Education Assistance Act of 1985 — that provides computer funding through 1990.

Another reason for the CMI surge is the decreasing cost of hardware capable of running sophisticated CMI applications. Although spending for computer equipment is only running between one percent and 1.5 percent of public education's total purse, that's still nearly three billion for the 1987-88 academic year — an amount that could rise even higher as more CMI solutions become available.

"Everybody seems to be wanting to get into the CMI market," says Moriarty. "The opportunity for dominance is attractive because of the large number of schools."

HEWLETT-PACKARD'S STRATEGY in CMI is to offer the most comprehensive systems on the market. "We offer complete solutions because of the relationships with our suppliers," says Lynn Gardner, HP's manager of education marketing for the K-12 segment. There are three software companies that figure prominently in

HP's plans. Two of them — Carter-Schaefer & Co. (Houston, TX) and Pertaine Systems, Inc. (Redwood City, CA) — offer HP 3000 packages that address schools' general administrative needs including budgeting, payroll, scheduling, inventory and some student information functions. The third company is Abacus Educational Systems.

Abacus has huddled with both Pertaine and Carter-Schaefer to develop ready-made software interfaces, enabling Abacus' CMI package to work smoothly with the other companies' products. HP customers currently running either Pertaine or Carter-Schaefer software easily can add full-fledged CMI. New HP customers can order the total package right off the bat: general administrative functions wed to CMI.

The relationship between Hewlett-Packard and Abacus dates back to the product's development, which was funded by a quarter-million-dollar grant from HP. One of Abacus' distinctions — quickly becoming a must for CMI packages — is its ability to be customized to a district's own objectives. Some CMI products force schools to use the software publisher's objectives.

Abacus is being used in more than 50 school districts and community colleges in the U.S. and Canada. The program fully supports curriculum development, and users can link curricular areas, teaching objectives and test items. Abacus generates more than 20 instructional management reports, ranging from the performance of one student on one objective to the performance of all district students on all objectives.

EDUCATORS ARE NOTORIOUS tire-kickers when it comes to computer purchases. To get the sale, a vendor must offer more than a comprehensive software solution — that's why HP plays up its other assets when wooing CMI customers: discounts, special service agreements, expandability and reliability.

Because schools have come to expect deep discounts from computer vendors, notes HP's Gardner, "We've increased our discounts in order to be very Abacus Educational Systems 7401 N. Broadway, Suite 200 Denver, CO 80221 (301) 430-1642 ENTER 297 ON READER CARD

Carter-Schaefer & Co. 1500 S. Dairy Ashford, Suite 400 Houston, TX 77077 (713) 558-1270

ENTER 298 ON READER CARD

Kerry Consulting Group 976 West Fourhill Blvd., Suite 392 Claremont, CA 91711 (714) 621-6469 ENTER 299 ON READER CARD

Pertaine Systems, Inc. 805 Veterans Blvd., Suite 110 Redwood City, CA 94063 (415) 367-9827 ENTER 300 ON READER CARD

aggressive in this market." Schools get a 25 percent discount on all HP 3000 hardware, a 38 percent discount on system peripherals and a 50 percent discount on software not bundled with the hardware. HP personal computers can be purchased for 38 percent off if there's a \$400,000 minimum commitment per year.

Adds Gardner, "To distance us from the competition, we're offering one year of free servicing to CMI customers." Moreover, expandability never will be a problem because HP has a long history of providing timely upgrades.

Finally, HP offers its CMI customers something that's in short supply in the computer industry — GUTS. In this case, GUTS means "Guaranteed Up-Time Service," HP's guarantee of 90 percent up-time on all of its systems.

CMI innovation, deep discounts and GUTS — that's HP's answer to to-day's crisis in education. —Larry McClain is a freelance writer based in Southern CA.

# Welcome to the next generation of HP terminal emulation software for Macintosh.



ymlabs is pleased to introduce **Session**, a family of emulators which links the Apple Macintosh to the HP3000, 9000 and 1000. Building on four years of experience with Mac2624, our original block mode product for the Mac, we have evolved a set of connectivity solutions which take advantage of the revolutionary developments in Macintosh hardware and software, offering unprecedented power and user friendliness.

Business Session™ (formerly Mac2624) is the foundation of the family, emulating an HP 2392 block mode terminal. Business Session runs under Apple's MultiFinder, so you can flip between HP and Mac applications, performing terminal operations and file transfers in background mode. Graphic Session™ adds support for the graphics capabilities of the HP 2393, and lets you ''plot'' output on an Apple LaserWriter or ImageWriter, either directly or from another Mac application. Color Session™ gives you the color text and graphics capabilities of the HP 2397.

If you've got a Mac, get Session. There is no better HP terminal emulator. If you haven't got a Mac, get one. There is no better personal computer.

#### Session. From Tymlabs.





#### HP, Cognos Sign Corporate Agreement

Canon OA System Uses PowerHouse

ognos Incorporated and Hewlett-Packard signed a two-year agreement in mid-February granting HP a corporate license for Cognos' advanced application development software.

This agreement allows HP to distribute internally Cognos' PowerHouse application development language for use by any of its divisions. Other Cognos software products — Graphics, Architect, The Expert and PowerPlan — also are included in the agreement.

In addition, Cognos will provide technical services to HP, enabling HP staff to develop their own internal support and education programs. Cognos products already are used within HP.

According to Lloyd B. Taylor, HP corporate director of information systems, "PowerHouse now offers HP users the option of operating under MPE-V on the HP 3000 business computers, under MS-DOS or OS/2 on the Vectra microcomputers, and later this year it will be available running under HP-UX on the HP 9000 Series 800

technical workstations."

Earlier in the month, Cognos announced that its advanced fourth-generation software is at the heart of a new office automation system launched in Japan by Canon Sales Co. Inc. of Tokyo.

Canon's System 3000 is the result of a unique cooperative project involving Cognos, Canon Sales Co. Inc. and Yokogawa HewlettPackard (YHP), also of Tokyo. The system includes hardware components from both Canon and YHP, and incorporates a specially modified version of PowerHouse as a key software component. YHP is a principal distributor of PowerHouse in Japan.

William G. Breen, Cognos senior vice president, operations, said, "This agreement opens a very important door for Cognos. A joint venture with one of Japan's leading manufacturers of office automation equipment provides an unparalleled opportunity for Cognos to gain recognition in the business applications software market in Japan."

#### McDonnell Douglas Chooses HP

Represents Entry Into UNIX Marketplace

Manufacturing and Engineering Systems Company recently chose HP as a UNIX-system workstation vendor, representing its entrance into the UNIX-system marketplace.

McDonnell Douglas will combine its Unigraphics software with HP 9000 workstations and servers as an HP value-added reseller (VAR) to provide a complete mechanical engineering CAD/CAM offering. The corporate agreement, which includes the workstations, has a first-year estimated sales

value of up to \$20 million.

Thirty HP 9000/Unigraphics systems have been installed at the McDonnell Douglas Helicopter Division, though the focus of the expected sales will be to customers external to McDonnell Douglas and HP.

The agreement will include workstations and servers from the HP 9000 Series 300 and 800 product lines, as well as associated peripherals. Series 300 is based on the Motorola 68000 processor. Series 800 is based on HP Precision Architecture.

#### **IEM Offers Lifetime Warranty**

1-, 2-, 4-MB Boards Purchased After 1/1/88

EM Inc. (Ft. Collins, CO) has announced its new lifetime warranty on 1-, 2-, and 4-MB memory boards for HP's Series 200/300 computers. Any IEM memory board purchased after January 1, 1988, that is used on a single machine (identified by serial number) is eligible for lifetime warranty coverage.

To begin lifetime coverage, the customer simply

needs to fill out and return a Lifetime Warranty Registration form, which is shipped with the product. Boards that aren't registered within 30 days will be covered by a two-year warranty.

While under warranty, any board that malfunctions will be replaced free of charge, provided the malfunction wasn't due to improper care or unauthorized servicing.

# Ford Aerospace Orders 767 UNIX-Based Engineering Workstations

Totals \$16 Million

ewlett-Packard recently received a \$16 million order for 767 HP-UX engineering workstations from Ford Aerospace and Communications Corporation. This is part of a larger contract awarded Ford Aerospace by the U.S. Army.

HP will ship the HP 9000 Model 330 workstations for the Ford Aerospace maneuver control system-nondevelopment item (MCS-NDI) under this contract, one of HP's largest workstation contracts in the past year.

The HP Model 330 workstations are based on the Motorola MC68000 microprocessor and run on the HP-UX operating system.

Ford Aerospace holds a \$50 million, one-year contract with options to provide the U.S. Army with components for MCS-NDI.

The MCS-NDI system comprises off-the-shelf equipment supplied by HP and other vendors, and software developed by Ford Aerospace. The MCS-NDI is a new automated control and communications system that can be used by the U.S. Army in the field.

Ford Aerospace is evaluating its third generation of HP processors, and compatibility among the models of a product line is critical to Ford's corporate strategy.


# Intermetrics Develops Software Tools For HP 64700 Series

Signs Agreement With HP

he Software Products Division of Intermetrics, Inc., has entered into a joint marketing agreement with Hewlett-Packard to provide software for the new HP 64700 emulator series. The software to be provided includes C cross compilers, cross assemblers, XDB source level cross debuggers and utilities specifically designed for programming embedded microprocessors.

The initial software offering is targeted to program the 68000 and 8086 microprocessor families, and the Z80. It is available on the following host platforms with special user interfaces: HP Vectra PC, IBM PC and compatibles, Sun, Apollo and VAX workstations.

The HP 64700 emulator series is an entry-level emulator designed for small design teams using the PC workstation with a migration path to a high-performance development environment. This will allow users to continue using the same emulator and development software as they grow to larger development host environments.



The HP 48050A measurement and control unit.

# HP Offers Measurement, Control Unit For Industrial Environments

48050A Extends 48000 RTU Family

ewlett-Packard recently introduced its new HP 48050A measurement and control unit designed specifically for harsh industrial environments.


The unit extends the scalability of the HP 48000 remote-terminal unit (RTU) product family by addressing applications that require small point counts, providing end users, systems integrators and OEMs with more tools to build their data-acquisition and control solutions. The HP 48050A has 23 I/O points, which can be increased to 45 I/O points with an expansion board.

Target markets for the data-acquisition and control unit include petrochemical, telecommunications, transportation, rubber and plastics, food and beverage, and electrical utilities.

Applications range from supervisory control and data-acquisition (SCADA) systems and energy management to the measurement, monitoring and control of remote facilities and equipment.

Customers will refer to the HP 48050A as an RTU, a distributed-control unit, a front-end processor, or an industrial data-acquisition and control unit depending on the particular application. It has a user-configurable database library incorporating more than 50 signal-processing functions ranging from simple scaling for engineering-unit conversions to more complex algorithms such as PID loop control or AGA flow calculations.

The HP 48050A contains a multitasking BASIC programming language. Userdefined tasks easily can be written in BASIC. Using a PC running MS-DOS, custom tasks and functions also can be written in Microsoft C or 8086 assembler and then downloaded to the HP 48050A.



The HP 4062C is shown here with the HP 4089A 96-pin test head installed on a commercial wafer prober.

# **HP Introduces High-Pin-Count Switching Matrix**

Extends Semiconductor Parametric Test

P recently introduced the HP 4089A, a new high-pin-count switching matrix.

Designed primarily for use with the HP 4062C high-performance semiconductor parametric test system, the 96-pin switching matrix doubles the number of test pins, while still maintaining high-resolution measurement capabilities.

The HP 4089A allows the HP 4062C to test the complex structures of advanced semiconductor processes. Customer parametric-test requirements are rapidly

changing, as new process technologies such as Bi-CMOS, GaAs and power MOS grow more important.

The HP 4089A's high pin count makes the HP 4062C suited to high-volume process-monitoring applications.

Extending HP's line of low-leakage switching matrices, the HP 4089A offers a full range of test-pin configuration options. HP's semiconductor parametric test system thus can be configured with 12 to 96 pins, depending on test needs.

The HP 4089A is fully compatible with existing HP systems. Owners of HP

systems can upgrade their systems to the larger switching matrix without rewriting the test code. Test programs written for R&D or processdevelopment needs on a lowpin-count system quickly can be transferred to a highpin-count system for process-control applications.

# Microsoft, HP Port MS OS/2 LAN Technology

For UNIX System V Environment


icrosoft Corporation and Hewlett-Packard have announced a new networking product, Microsoft LAN Manager/X (LM/X), which brings the functionality of the MS OS/2 LAN Manager to the UNIX System V operating environment. The new product, being jointly developed by Microsoft and Hewlett-

Packard, will allow a UNIX System V-based server running LM/X to service requests from workstations running Microsoft Networks, Microsoft Networks for XENIX and MS OS/2 LAN Manager ("LAN Manager") networking software.

LM/X initially will be developed to run on Intel 80386-based systems under the new merged XENIX/ UNIX System V product,

16 HP PROFESSIONAL

# Introducing, the 4GL Environment



The fourth generation language (4GL) was a revolution. It allowed programmers to code 10-20 times faster than COBOL! That's a benefit that is difficult to live without. However, when developing and running application systems, there is more to life than coding. Much more.

Enter the 4GL Environment. The next revolution.

If you also want to improve the speed and quality of systems analysis and design, produce user manuals automatically, integrate PC's into your applications and still squeeze the most performance out of your hardware.

Then you need to find out about the SPEEDWARE ENVIRONMENT.

Call us ..... Right now ..... Or else!

Marketing Dept. Telephone (416) 678-1841

Infocentre Corporation



For more information contact:

Infocentre Corporation 7420 Airport Road Suite 210 Mississauga, Ontario L4T 4E5

In Europe call: London (01) 828-1897

Only one product does it all,



Offices throughout the world including: New York, Los Angeles, Montreal, Toronto, London, Paris, Sydney.

**ENTER 115 ON READER CARD** 

Microsoft UNIX System V/386, Release 3.2. It can be ported to servers running other implementations of the UNIX operating system. LM/X will be licensed to OEMs by Microsoft and is scheduled to be released in early 1989. A software developer's kit will be available from Microsoft by the end of 1988.

HP is working closely with Microsoft to develop LM/X technology, applying its expertise in the UNIX System V environment to the port of Microsoft OS/2 LAN Manager technology. HP also is the first major OEM to announce support for LM/X and will be using the new product on the HP 9000 systems running under the HP-UX operating system.

An LM/X-based server will be able to service requests from workstations running any of Microsoft's other networking products, as well as related IBM products such as PC-LAN and OS/2 Extended Edition. All of these products, like LM/X, are based on the Server Message Block (SMB) communications protocol, a standard jointly defined by IBM, Microsoft and Intel.

In addition, because LM/X is a port of the OS/2 LAN Manager, DOS, OS/2 and XENIX systems running their corresponding LAN workstation software can communicate with both OS/2 LAN Manager servers and LM/X servers without requiring any new or different LAN workstation software.

Further communications breadth is achieved through LM/X's ability to coexist on the same server with other networking subsys-

tems, such as Sun's NFS or AT&T's RFS. This capability allows workstations running other networking products to exist in the same network as those running SMB-based software.

LM/X will be able to run on various networking hardware, including Token-Ring, IEEE 802.3/Ethernet and 5BASE1 StarLAN. The product also will be ported to different low-level transports (communication protocols), including Netbui (PC-LAN), TCP/IP and ISO. In addition. it will be ported to various transport-level interfaces, including Berkeley Sockets and AT&T System V Transport-Level Interface (TLI).

# HP 9000 Provides CADAM/CATIA Access With IBM 5080 Emulation

Combined Systems Solve Complex Tasks

P has announced that now its engineering workstations can access IBM mainframe-based applications with the HP 98855A, a new IBM 5080 emulation product.

Users of HP workstations and IBM mainframes can work together using the computational and graphics strengths of their respective systems to solve complex tasks. Engineers in a variety of industries, and designers who use HP 9000 workstations primarily for design and analysis, now can access

designs and data stored in IBM mainframe-based applications such as CADAM and CATIA.

The 5080 emulator is the result of a team effort between HP and Spectragraphics Corporation (San Diego, CA).

The HP 9000 Model 350SRX or 350CH workstations, which run the emulation, can communicate with an IBM mainframe in singleuser or multiuser configurations.

The HP/Spectragraphics design-set channel controller can support a maximum of 64 simultaneous users and up to eight LAN gateways. Alternatively, communications adapters and modems may be inserted on each end of the coax path to convert the communications to T1. V.35 and fiber-optic modes. This allows workstations to be remotely located from the host mainframe, while communicating via leased lines, microwave or fiber-optic links.

HP workstations with 5080 emulators can be added to existing IBM mainframes using Spectragraphics channel controllers and Spectragraphics IBM-compatible 5080 terminals.

The HP 98855A can be enhanced with an IBM 3278 emulator and a high-speed, file-transfer product. The 3278 emulator allows users of HP 9000 workstations to emulate an IBM 3278 terminal to perform data entryinquiry applications.

#### **HP Joins X Consortium**


Continues To Support X Window System

ewlett-Packard is among the first companies to join the X Consortium, a multivendor group chaired by the Massachusetts Institute of Technology. HP is committed to the X Window System to provide the foundation for distributed computing in a multivendor environment.

Through membership in the consortium, HP will continue to contribute to the future development and direction of the X Window System. Future releases of the X Window System from HP will be based on X version 11, release 2.

Other X news: At the X Conference held at MIT in January, HP announced its plans to develop for public use a set of "widgets" based on the X user interface toolkit.

"Widgets" are interactive graphical components of an applications user interface, such as menus, forms and scroll bars. The HP widget set will enhance software developers' productivity in writing portable, easy-touse applications for the X Window System. These widgets will be available from HP this summer and will be contributed to MIT for public distribution on the MIT X11 tape.



#### Inference Ports ART to HP

Connects To HP 9000 Workstations

nference Corporation recently announced it will port ART (the Automated Reasoning Tool) to the HP 9000 Series 300 and 800 workstations. The porting agreement is significant, since it will provide engineers with the capabilities of the industry's powerful expert system development tool on a high-performance engineering workstation.

Chuck Williams, Inference Corporation's executive vice president, views this business agreement as an important opportunity to bring the benefits of ART to the large installed base of HP 9000 workstations.

William G. Parzybok, Jr., vice president and general manager of HP's Engineering and Manufacturing Systems Group, said, "The agreement brings a significant new ability to workstation users. Expert system development is assuming even greater importance as it becomes more broadly commercialized."

The Series 300 family of technical computers provides users with a variety of workstations, instrument controllers and modular components. The high-end Series 800 workstations are based on an enhanced version of RISC architecture and offer 32-bit addressability as well as 48-bit and 64-bit virtual addressing.

ART is a primarily rule-based development and deployment environment used for building commercial expert systems. It has been used to develop and deploy wide-ranging expert system applications such as credit analysis, factory and office automation, medical claims monitoring, software emulation and process control.

# Standard And Poor's Trading Systems Licensed For HP Systems

StockMate Runs On HP 9000s

new licensing agreement recently announced makes Hewlett-Packard the first major computer vendor to support Standard and Poor's Trading Systems' real-time broker application on the UNIX operating system.

The Standard and Poor's computer software, S&P StockMate, is a quotation and information system designed for the securities-

brokerage industry. It operates on HP 9000 individual workstations and multiuser computers, including those systems based on Precision Architecture.

S&P StockMate is built around Standard and Poor's Ticker III, a professional, real-time, consolidated market-data broadcast of all North American securities including stocks, bonds, futures, indices and options.

#### **HP And TSSI Sign Agreement**

Links HP 16500A, CAE Simulators

ewlett-Packard has reached an agreement with Test Systems Strategies Inc. (TSSI, Beaverton, OR) under which TSSI will develop software links between the HP 16500A logic-analysis system and CAE simulation workstations.

With these links, users of CAE simulators are able to transfer test vectors to an HP 16500A logic-analysis system to permit real-world, stimulus-response analysis of simulated designs. The links represent an expansion of TSSI's current family of products for linking design to test systems.

Known as the Test Development Series (TDS), TSSI software products will link the HP 16500A to all CAE simulators presently supported by the TDS product family. The software runs on Apollo Aegis, Sun UNIX or DEC VAX/VMS operating systems.

HP will continue to provide support for the HP 74240A and 74240B CAE link between the HP Electronic Design System and the HP logic-analysis system.

# HP Provides Upgrade For Model 825S, SRX Workstations

2.0 MFLOPS Performance

ewlett-Packard has announced a CPU upgrade for the HP 9000 Model 825S and 825SRX workstations.

Previous workstations have had floating-point performance rated at around 1.0 MFLOPS. This is the first time that a workstation has performed at more than 2.0 MFLOPS.

The upgrade is a field-installable CPU board set upgrade for Model 825S multiuser/servers and 825SRX superworkstations that don't require an I/O expander. A new board set can be installed in minutes to replace the current CPU-board set. Model 825 systems with the new CPU upgrade are object-code compatible with all Series 800 systems, and no

software changes are required.

With 2.02 doubleprecision MFLOPS, the upgrade (\$10,000) boosts the floating-point performance to more than three times that of its predecessor. The upgraded Model 825 now is more than 75 percent faster than the Sun 4/260 and Silicon Graphics 4D/70, and four times faster than the DEC MicroVAX 3600 in floating-point performance. The integer performance of Model 825 is increased from eight to 14 times that of a VAX 11/780.

The Model 825SRX (\$69,500), a superworkstation, and the Model 825S (\$42,500), a multiuser computer and server, both are based on HP Precision Architecture.



# History's greatest collection systems don't work on the shop floor.

#### But CAPTURE does.

If Noah thought he had a tough collection job, he should try gathering data in a factory. He'd find all kinds of unmated devices generating or collecting data for limited uses.

CAPTURE removes the limitations. It's the ultimate software tool for real-time collection and distribution of data in a factory environment.

CAPTURE works with the devices you already have. Such as bar code readers, RF terminals, laser scanners, scale concentrators, and employee badges. Or the engineering department's home-grown gadget:

Use the collected data for any purpose you desire. You can modify the data, produce bar code labels, display full-color charts and graphs, or share data with existing computer sytems.

So CAPTURE can be your first step to a total CIM solution. In fact, the system works in any manufacturing environment for virtually any application: Process control. Quality control. Machine control. MRP. Job costing. Warehousing. Or you name it.

But even with all that power and versatility, CAPTURE is easy to install and use. No programmer assistance is required for shop personnel to gather, maintain and display data.

For more information on how CAPTURE can make history of your data collection problems, write or call ICC. We're the people who leave you to your own devices.





Manufacturing
National Account Program

Industrial Computer Corporation 6065 Barfield Road/Suite 114 • Atlanta, Georgia 30328 Telephone: 404/255-8336 ENTER 114 ON READER CARD

### NEW PRODUCTS

# SAS System Runs Under UNIX

SAS Institute Inc. announced the SAS System under UNIX to more than 3,000 SAS software users attending the 13th annual SAS Users Group International (SUGI) conference in Orlando, FL. The first UNIX implementation of the software will support Hewlett-Packard's HP 9000 Series 300 under HP-UX, with support for the 800 Series later this year.

In addition to opening a new market for the Institute, the SAS System for UNIX is an important step forward for the Institute's multivendor architecture. The multivendor architecture allows SAS to develop a software system that will run across most future hardware platforms that it might encounter. As SAS implements the system in each new environment, the host layer, which comprises about 10 percent of the code, is written specifically for that host platform. The remaining code, comprising the core and applications layer of the SAS System, is written in C and can be moved across hardware platforms.

The UNIX implementation is a validation of the multivendor architecture concept, which the Institute adopted in 1984. The core and applications layers are the same for both the HP release and the Institute's recent release for the SAS System for PCs (release 6.03).

The SAS System is an integrated software system providing complete control over data management, analysis and presentation. It includes modular components for data entry, retrieval and management; report writing and graphics; statistical and mathematical analysis; decision support; and applications development. To use any module in the SAS System, sites first need base SAS software for data management, analysis and report writing.

Available immediately, the SAS System

under HP/UX is licensed annually, with fees based on machine size.

Contact the Software Sales Department, SAS Institute, Inc., SAS Circle, Box 8000, Cary, NC 27512-8000; (919) 467-8000.

Enter 372 on reader card

# HP Expands 700 Series Terminals

HP has added two new terminals to the HP 700 terminal family — the HP 700/44, HP's first terminal for PC-based multiuser environments, and the HP 700/43, a general-purpose ASCII terminal.

When connected to a PC running Santa Cruz Operation's XENIX operating system, the HP 700/44 can use the same programs as the PC, including MS-DOS applications.

Like the recently introduced line of HP Vectra PCs, the HP 700/44 (\$575) has the IBM PC character set and enhanced PC keyboard layout, giving the terminal the look and feel of a PC. The 14-inch display screen, which has both 80- and 132-column modes, is available in amber, green or soft-white

phosphor. The latter shows black letters on a white screen similar to a printed page.

Up to 32 terminals can be connected to the HP Vectra RS/20, which is based on the Intel 80386 microprocessor, and up to 16 terminals can be connected to the HP Vectra ES/12 PC. These multiuser PC systems provide a cost-effective solution for small businesses, medical practices, financial institutions and companies with offices in many locations.

Designed for business, technical and manufacturing applications, the HP 700/43 display terminal (\$475) is an enhanced version of the HP 700/41 introduced in August 1987

HP also enhanced its HP 700/71 IBM 3191-compatible terminal (\$695) by increasing the refresh rate from 64Hz to 72Hz and by adding the soft-white screen option at no additional cost.

Contact Hewlett-Packard, 3000 Hanover St., Palo Alto, CA 94304.

Enter 396 on reader card



The HP 700/43 (left) is HP's newest general-purpose ASCII terminal. The 700/44 (right) is HP's first terminal for PC-based multiuser environments.

## IOtech Enhances IEEE-488 Interface

IOtech, Inc. has updated its IEEE interface for PC compatibles to provide added hardware compatibility and easier-to-use software features.

Personal488 (\$395) is a unique device driver-based interface that's easier and simpler to operate than standard subroutinebased interface products. Product enhancements include wider compatibility with other NEC 7210-based interfaces currently available; hardware improvements that allow multiple boards to share the same DMA and interrupt channel and built-in selectable waitstate generator so it can operate with the new high-speed PCs; and enhancements to the device driver software that make software code more readable and shorter by allowing the user to predefine an instrument's parameters such as its device name, IEEE address and terminators once.

Also included are several additional utilities that redirect IEEE data to the serial or parallel port so the user can command an IEEE plotter or printer from application-specific software such as Lotus 1-2-3 or AutoCAD.

The Personal488 is compatible with all popular DOS-based languages with no drivers or extra add-ons needed.

Contact IOtech Inc., 23400 Aurora Rd., Cleveland, OH 44146; (216) 439-4091.

Enter 384 on reader card

# VOCOM Provides Integrated Software

VOCOM, a division of Dean-Michaels Corporation, recently announced the VOCOM Application Software solutions system that can be independently run or integrated in any fashion.

A global database is used and can be structured around user-defined accounts, units, projects or any combination thereof. This user-defined structure provides for reporting flexibility normally not found in standard accounting systems. The user can view the profitability of any entity such as company, division, department, profit/cost center, project, product line and more. The user can easily define whatever units and projects are appropriate for his business and report any combination of the units and



Personal488 is IOtech's updated IEEE interface for PC compatibles.

projects desired. Reporting can be made for any date range and can be consolidated to any level.

The VOCOM system features modular structure to adapt to organization needs, complete integration and online editing for maximum accuracy, comprehensive security to limit access to vital information, online documentation for ease of operation, organizational structure by account, unit or project and extensive report writing capabilities.

The VOCOM system consists of nine modules:

- General Ledger Order Management
- Accounts Payable Fixed Assets/Depreciation
- Accounts Receivable Payroll/Personnel
- Purchasing/Receiving Prospect Tracking
- Inventory Management

Contact VOCOM, The Dewitt Bldg., P.O. Box 847, Ithaca, NY 14851; (607) 272-8464.

Enter 400 on reader card

## Cognos Launches PowerHouse PC

Cognos Incorporated recently entered the PC workstation market with the release of PowerHouse PC, a full-function version of Cognos' fourth-generation application development language that runs under DOS or OS/2 on 80286- and 80386-based PCs.

PowerHouse PC turns an AT-class PC into a workstation for serious application development. The product has built-in com-

munications facilities that enable PowerHouse programmers to develop applications on a PC to run on a minicomputer, or vice versa.

PowerHouse PC will let you use the PC to run time-consuming jobs like large data entry and verification operations so that companies can free up the more expensive CPU cycles on mid-range machines and increase their staff productivity simultaneously.

PowerHouse PC includes all standard PowerHouse modules — a data dictionary, dictionary reporter, screen-design and data-input program, volume transaction processor and a report writer. In addition, there's a microcomputer file-format utility and a host connection program to provide terminal emulation and to transfer data files or complete applications. An import/export utility allows users to transfer data between PowerHouse PC applications and PC-based programs.

The product runs on IBM PC ATs or compatible 286/386 machines, including HP Vectras, DEC VAXmates and DG Dasher/286s, as well as IBM PS/2 Model 50 and up.

The minimum configuration DOS version requires 640 KB of RAM, and its OS/2 counterpart requires 2.5 MB of RAM. Contact Cognos Inc., P.O. Box 9707, 3755 Riverside Dr., Ottawa, Ontario K1G 3Z4; (613) 738-1440.

Enter 399 on reader card
Continued on page 24.

# CDMS Expands Typesetting Options

Syntactics Corporation has expanded the capabilities of the Crystal Document Management System (CDMS) (starting at \$595), a software package that fully integrates word processing with a powerful document-format database and optional integrated typesetting.

With the introduction of LaserPak, an add-on product for CDMS, users can generate typeset-quality documents on HP's LaserJet printer family and on laser printers

supporting PostScript.

LaserPak takes advantage of CDMS's automatic typesetting features such as defining parameters for fonts, point sizes and vertical spacing so that typesetting becomes a one-button operation. A document is laid out, fully typeset and directed to the printer with the press of a single function key.

With LaserPak, graphic images also can be incorporated into CDMS documents. Bitmapped images from sources such as Mac-Paint can be integrated with text files with a simple command.

LaserPak is available in two versions — LaserPak/HP and LaserPak/PS. LaserPak/HP supports typesetting on the HP LaserJet printer family. It's available for PCs and Altos systems running XENIX, and for AT&T, NCR and Unisys UNIX-based systems.

LaserPak/PS supports typesetting on Apple, QMS and other PostScript laser printers. It currently is available for AT&T UNIX-based computers.

LaserPak is based on the technology of Syntactics' CrystalTypeset, introduced in November 1986 to provide HP LaserJet Plus support for CrystalWriter, a Syntactics word processing package.

Contact Syntactics Corp., 4655 Old Ironsides Dr., Suite 400, Santa Clara, CA 95054; (408) 727-6400.

Enter 376 on reader card

# AMS Automates Porting From Series 80

Advanced MicroSolutions has announced a new release of its HP Series 80 to Rocky Mountain BASIC Translator and Porting Guide that automates moving from the obsoleted HP Series 80 computers. By using the AMS package, Series 80 programs and data can be moved to the HP 9000, Vectra PC or the IBM PC/AT running RMB with little or no programming required.

With the AMS Translator, the porting to the newer desktop computers can be accomplished in hours or days rather than the



LaserPak allows CDMS users to generate typesetquality documents on the HP LaserJet printer family and PostScript laser printers.

weeks, months or years required to manually translate the code.

This package automatically translates over 90 percent of all Series 80 keywords including ROMs and binaries. Documentation includes complete keyword cross-reference, porting instructions and an in-depth language comparison. While using the AMS Translator, users also will be learning the new language and system.

Contact Advanced MicroSolutions, 2510 Middlefield Rd., Redwood City, CA 94063; (415) 365-9880.

Enter 395 on reader card

# CIA Exposes HP 3000 Secrets

FACER INFORMATION DESIGN has released its Australian product, CIA, into the North American and European markets.

CIA (CPU I/O Analyser) allows the performance of the HP 3000 to be monitored both online and in batch mode.

The online monitor has simple-to-use screen structures that allow the display of total or "filtered" process, CPU, memory and disc activity. It allows the queues of processes to be dynamically altered as well as give file equations, files being accessed and segmentation for each process.

The batch mode function allows CIA (\$3,000) to collect performance statistics in background over a user-defined period and at user-defined intervals. At the end of the statistics collection period, a set of reports is produced that show the global, disc and process activity of the system over the statistics collection period. Both CPU and disc activity is also shown in graph form. Contact FACER INFORMATION DESIGN, P.O. Box 270, Epping NSW 2121, Australia; FAX + 61 2 484 5709.

Enter 398 on reader card

## **On HP PA 3000s**

Proactive Systems recently announced the availability of its BACKCHAT distributed database software on HP Precision Architecture. BACKCHAT replicates databases in real time and provides distributed database solutions for users of multiple HP 3000s.

Following work under HP's FAST START program, BACKCHAT now is available for MPE/XL systems using NS as a communication link. In addition, it supports

Continued on page 84.

#### There's one error even our software won't flag.



When it comes to computer operations, you'll find NSD's JobRescue<sup>™</sup> is perfectly matched to your needs.

The reason? It's integrated. Which means you can have one program that answers all your production requirements. That's because JobRescue now has expanded capabilities. So we handle everything from reports to production scheduling to batch job management.

But make no mistake! We are still the standard in error management for HP. During operation, JobRescue works online and in the background. Examining your \$STDLISTs for errors continuously. And alerting you when they occur.

Still, eliminating hidden production errors is just the beginning. Our new report and scheduling modules will help you greatly improve the overall quality of your work as well. So you can now manage virtually every facet of your computer operations.

That's why you should give us a call. We'll answer any questions you have and send you our JobRescue demo.

JobRescue. You need it for a very basic reason. Nobody's perfect.



NSD, Inc. 1670 South Amphlett Blvd. Suite 103, San Mateo, California 94402 800.538.3818, (In CA) 800.538.9058 Canada 800.445.3818, Local 415.573.5923

# **UNIX** Applications You Need Most

ne software package brings more to UNIX environments than empty promises. The SAS System.

The SAS System is the #1 choice for data analysis. The SAS System is the all-purpose answer for researchers, statisticians, students. business analysts, and applications developers. The SAS System is backed by an industry leader.

Now we've teamed with Hewlett-Packard to bring you the SAS System under HP-UX. That means you'll get software that's powerful. productive, and proven for the applications you need most. On everything from singleuser workstations to multi-user systems.

#### **Superior Data Analysis**

Reliable statistics are a hallmark of the SAS System, from simple descriptive statistics to complex multivariate techniques.

Monitor experimental data on a day-today basis. Compute analysis of variance for both balanced and unbalanced data. Perform regression analysis and build linear models. The SAS System's ready-to-run programs handle any data analysis task... in record time.

For your advanced mathematical and engineering applications, the SAS System offers an interactive matrix language. You can transcribe almost directly from statistical formulas to SAS statements, and operate on entire matrices of numbers instead of one number at a time.

#### **Efficient Data Management**

The SAS System reads data from any kind of file, in any kind of format. Then you can sort, merge, and concatenate data using common-sense statements.

File updates are easy, too. You can create customized panels that look exactly like your business forms, surveys, or laboratory logbooks...screens that speed up data entry and reduce errors.

#### **Powerful Reports and Graphs**

When it comes to communicating your findings, nothing succeeds like the SAS System. Create anything from simple lists to full-color graphics, often with just a few keystrokes.

Produce tables, charts, calendars, and other formatted reports. Or display your data in attention-getting graphs—from pie charts to 3D plots to prism maps.

Combine these SAS System applications any way you choose. Tailor them with customized front-end menus for individuals or groups. And port them easily between workstations or operating systems.

#### Try the SAS System Free for 30 Days


The SAS System delivers on its promise. See for yourself with a free 30-day software evaluation. For all the details, clip and mail

the coupon. Or call your Software Sales Representative at (919) 467-8000.

We'll tell you more about the #1 data analysis software, backed by SAS Institute's total commitment to support you all the way.




SAS Institute Inc.
SAS Circle ☐ Box 8000
Cary, NC 27512-8000 Phone (919) 467-8000 Fax (919) 469-3737



and compatible mainframes under OS. CMS, and VSE; Digital Equipment Corp.'s VAX™ series minicomputers and work-stations under VMS™, Prime Computer, Inc.'s Prime 50 series under PRIMOS®: Data General Corp.'s ECLIPSE® MV series under AOS/VS; and IBM Corp.'s PS/2, PC AT, and compatibles under MS-DOS® and PC DOS.


SAS is a registered trademark of SAS Institute Inc. UNIX is a registered trademark of AT&T.

Copyright © 1988 by SAS Institute Inc. Printed in the U.S.A.




# Now on HP.

Introducing the SAS' System









Tell me more about the SAS® System, including details about a free

Name

Title

Company/Organization

Mailing Address

City

State

ZIP

Network Address (identify network)

Mail to: SAS Institute Inc.
Attn: CC
SAS Circle □ Box 8000
Cary, NC 27512-8000

# Learning LAN Bridges

The Key To True LAN Connectivity

LAN Bridge is an intelligent packet switch that spans two or more local area networks providing the path for internetwork data traffic as shown in Figure 1. The Bridge monitors data packet activity on each connected LAN and decides which data packets should be transferred from one LAN to the other. As a result, the Bridge functions as a data packet filter allowing only specific packets to travel from one LAN to the other: Packets that match a certain destination criteria (those destinations determined not to be located on the sending LAN) are transferred while others (those located on the sending LAN) are blocked.

With a LAN Bridge in place, any device connected to LAN-A in *Figure 1* can send data packets to any device located on LAN-B, just as if the sending device were directly connected to LAN-A. In a properly designed bridge, the LAN user doesn't even realize that the destination device is on another LAN.

A LAN Bridge takes advantage of the LAN packet format shown in *Figure 2*. Local area networks that obey one of the IEEE LAN standards such as IEEE-802.3 (Ethernet, STARLAN), IEEE-802.4 (MAP) or IEEE-02.5 (Token Ring) implement data packets having

the format shown in Figure 2. Each

[By Tad Witkowicz]

packet contains a Destination Address followed by a Source Address and Data Field.

The Destination Address identifies the address of the device to which the packet is being sent, while the Source Address identifies the address of the sending device. All data information, including the LAN protocol, are contained inside the Data Field of each packet. Each of the popular LAN protocols such as TCP/IP, XNS, DECNET, MAP, TOP, LAT, as well as numerous vendor modifications of these, utilize the packet format shown in *Figure 2*.

Because it is connected as a node on each of the two interconnected networks, the LAN Bridge receives all data packets on each connected LAN and compares packet Destination Addresses with an Address Directory it maintains for each LAN. Using this Address Directory, the Bridge determines which packets should be forwarded (bridged) to attached LANs.

Since the LAN Bridge examines only the Address Fields and not the Data Fields contained in each packet, the bridg-

ing process is protocol-independent (Figure 3).

A well-designed LAN Bridge has

the ability to build its own Address Directory by listening to data traffic and memorizing the different Source Addresses it encounters on each of the connected LANs. It stores all Source Addresses in local memory which is used as a directory. This type of Bridge is known as a Learning Bridge. Its key advantage is ease of use since it is a "plug and play" device requiring no user programming or setup.


Important Bridge features include:


Protocol Independence. LAN software protocols exist in many standards such as DECNET, TCP/IP, XNS, TOP, MAP, OSI and LAT. Many LAN vendors have taken pieces of LAN protocol standards and adapted them to their own products resulting in incompatible standards. For example, a wellknown personal computer LAN offers Novell and 3Com protocols, each using XNS, yet the LANs are incompatible because the protocols have been modified.


It's essential that a LAN Bridge be insensitive to the LAN protocol or its usefulness becomes extremely limited. An XNS-dependent bridge can pass only XNS packets from one LAN to another. This becomes a problem if a user wants to install TCP/IP or DECNET devices on each LAN. Those devices would be unable to communicate with their peers located on the other LAN because the XNS-de-

pendent Bridge can pass only XNS packets.

Fast Filter/Transfer Rate. A key performance parameter for a LAN Bridge is its ability to filter (examine) a large number of packets in a short period of time. A LAN Bridge must be







able to examine all the packets that appear on each LAN. This requirement exists because the Bridge has no way of knowing whether or not a given packet needs to be transferred until it receives the packet and compares its Destination Address with its Address Directory.

Consequently, if the Bridge is unable to keep up with the traffic on the connected LANs, it will miss data packets that may have been destined for the other LAN. When this occurs, the sending device must retransmit the packet, thereby incurring a delay in its ability to communicate with its peer on the other LAN and unnecessarily increasing local traffic.

Once the Bridge determines that a packet must be transferred to the other LAN, it must perform the actual transfer from its memory. This transfer must be done quickly so that additional packets can follow.

If the Bridge is unable to keep up with the trafficgenerating capability of the two connected LANs, packets will be lost, causing a communications bottleneck as well as creating unnecessary and excessive LAN traffic.

Connecting Dissimilar LANs. The ability to bridge dissimilar LANs such as Ethernet and Token Ring or Ethernet and STARLAN is becoming an important requirement in the implementation of LANs. Because different LAN standards operate

at different data transmission speeds with different cables using different priority schemes, a Bridge that connects dissimilar LANs must be able to perform the bridging function described earlier and convert the standards (speeds, topology consideration, etc.) as well (see Figure 4).

This important capability allows a LAN user to select the type of wiring scheme, transmission speed and LAN standard that's most effective for his specific situation. As LAN protocols (LAN software) become available for the different standards, the user will be able to maintain full functionality regardless of the LAN standard employed.

#### Key To Internetworking

NTERNETWORKED LANs or ILANs represent an important development in the ability to implement local area networks. The ILAN concept solves the connectivity problem created when large LAN users have installed multiple LANs, using multiple LAN standards, purchased from different vendors and located at multiple sites within a corporation. Here are several examples of ILAN in use:

Backbone LANs. An example of a Backbone LAN is

The ILAN concept solves the connectivity problem created when large LAN users have installed multiple LANs...

shown in *Figure 5*. In the figure, a coaxial cable Ethernet is used, although the Backbone also could be Fiber Optics, Broadband, Token Ring or any other convenient networking standard. LAN Bridges are used to connect smaller departmental LANs or subnetworks to the Backbone.

The Backbone is the data highway for internetworked packets. Each of the LAN Bridges monitors data traffic on its

#### [ WHAT IS A LAN BRIDGE? ]

With the growth of the LAN market, several new devices have been created that make implementation of LANs more straightforward. Here I'll describe LAN bridge devices from the nontechnical perspective. It explains what they are, what they do and how they're used.

Before proceeding with the LAN bridge description, it may be useful to describe a LAN in nontechnical terms. Imagine a small country with cities, towns and villages that, in our simplistic model, represent different computers located throughout a corporate facility. The need to communicate between the different cities, towns and villages, and the benefits that are derived from such communication are clear.

Suppose that, in our model country, people communicate by sending messengers between the different cities, towns and villages. There are many messengers traveling around, each one carrying information from one specific location to another. In order to provide the messengers with a means of getting from one location to another, our model country has built a system of roads designed to accommodate the country's geographical size, number of traveling messengers and other factors that are specific to this particular country. The entire network of roads, messengers and methods by which they travel and traffic laws comprise this country's communication network.

In our analogy, the computers are connected by wires or fiber optics (roads) which they use for sending data (messengers) to each other. The way the data travels, its speed and transmission methods are the "traffic laws" that govern the network. The communications system just described is what's known as a local area network or a LAN. It gives computers and the people who operate them the ability to communicate and share data files, printers, modems and data storage devices. This capability enhances each computer's functionality and its usefulness.

Unlike many technological innovations, the LAN bridge does exactly what its name implies, that is, it bridges two networks. To continue our analogy, imagine that there are now two countries separated by a body of water. A bridge will be used to "interconnect" the two countries.

It's reasonable to assume that there are differences as one travels from one country to the other. For example, one country has cobblestone roadways while the other has six-lane divided highways. Using the same reasoning, the speed limit in one country is 35 MPH while it's 100 km per hour in the other. Other traffic laws, such as the side on which people drive, presence or absence of one-way streets, etc., also are likely to be different. The bridging device must take these differences into account when allowing messengers to pass from one country to another.

Technologically, the two countries actually are two different networks. One might be composed of fiber optics while the other uses coaxial cable. It's not important to understand the detail of the networks any more than it's necessary to understand why two countries have different traffic laws. What's important is that traffic going from one country to the other is able to adapt itself as it crosses the bridge in either direction.

LAN bridges perform exactly this function. LANs operate at different bit rates (speed limits), over different media (road beds) and with differing topologies (beltways, thoroughfares, one-way streets, etc.). The LAN bridge must take data packets (messenger traffic) and change their orientation so they effectively can travel from one network to another without violating the "local laws." The LAN bridge, in essence, "retrains" the messengers so they safely can travel from one country to another.


The LAN bridge performs another important function. It controls which data packets (messengers) are allowed to cross the bridge. Clearly, if the messengers have no business to conduct in

HP PROFESSIONAL

respective subnetwork and forwards (bridges) packets to the Backbone if they are destined for addresses on other subnetworks. At the same time, each LAN Bridge monitors the Backbone for data packets destined for addresses located on its local subnetwork. After identifying such a packet, it forwards (bridges) it to the subnetwork.

This type of network replaces a single large network, but offers several im-

portant advantages. First, a much larger geographical area can be covered than with a single LAN. LAN traffic is localized to the individual subnetworks resulting in less traffic experienced



on each subnetwork. At the same time, the LAN Backbone still provides full connectivity allowing any device on any subnetwork to establish a communication path with any other device on any other subnetwork.

LAN Bridges ensure that connectivity is protocoltransparent, giving users the convenience of mixing vendors and applications and allowing them to connect any device anywhere on the entire network. As a result,

any user can access any corporate resource regardless of its location. Finally, the backbone allows the use of smaller subnetworks which can be implemented with lower cost

the other country, their passage over the bridge will only add to traffic congestion and impede the progress of those packets that do need to get over to the other side.

Control is accomplished by putting on the bridge an immigration officer who screens the approaching messengers and determines whether or not they should be allowed to cross. Technical implementations of this process vary. In some cases, the "immigration officer" talks to the messengers to determine where they want to go. In other cases, he simply looks at the destination and return address on each message carried by the messenger and automatically makes the decisions.

The performance of a LAN bridge is judged on the basis of how many messengers are processed by the "immigration officer" on each side of the bridge and by how many passengers can travel over the bridge in any given time.

A well-designed LAN bridge must be able to accept many data packets from attached LANs, examine their destination and source addresses, and transfer only those that need to cross the bridge. In a typical application where two Ethernet LANs are being bridged, the bridge device ("immigration officer") must be able to process as many as 30,000 data packets per second and transfer over 9,000 packets per second.

Another important characteristic of a LAN bridge is its ease of use. Clearly if the bridge is to decide which data packets are allowed to cross from one network to another, it must have *a priori* knowledge about the networks and the type of devices that are attached to it.

The best bridges are designed to automatically learn the locations of all devices on the two attached LANs. The bridge builds a directory of names that represent devices on the two networks, then uses the directory as the database for making transfer decisions.

Therefore, if the bridge sees a data packet on LAN "A," it consults its address directory and determines whether the destination address of that packet is for someone who resides on LAN "A" or "B." If the destination address is on LAN "B," it transfers

the data packet from "A" to "B." If, on the other hand, the destination address is on LAN "A," then no transfer is necessary.

The self-learning process makes the operation of a LAN bridge easy. In fact, LAN bridges are much more difficult to explain than to use. A well-designed product requires absolutely no user involvement. It needs only to be attached to the two networks and powered up. The rest is done automatically.

The real world of LAN bridges is a complicated one because there are many LAN designs that are very different. There are at least five recognized industry standards that are used to design LANs and several proprietary designs as well. It's very common to find that a customer may have installed two or more different LAN standards to satisfy his particular computer communications requirements.

This multinetwork and multistandard LAN environment requires that many different LAN bridges be available to the customer so he can interconnect all of his LANs together into a company-wide network. For example, if there were only three LAN standards (such as the ones offered by IBM, DEC and AT&T), this would create the need for six different LAN bridges: DEC-to-DEC, DEC-to-IBM, DEC-to-AT&T, IBM-to-IBM, IBM-to-AT&T and AT&T-to-AT&T.

Because there are actually five LAN standards and several other communications networks that may require bridging, there are requirements for over 30 different LAN bridge designs.

Going back to our analogy for one more point, it should be obvious that it makes little sense to use a single style of road (freeway, two-lane, one-way street) throughout a country. By the same reasoning, it makes little sense for a corporation to design with a single type of network when interconnecting computers.

Fortunately, LAN bridges are appearing on the market that allow the interconnection of fiber optics, coaxial cable, twisted pair wiring and the like. These bridges assure the LAN user the ability to interconnect his networks together to achieve the maximum potential of his computer installations.

technologies such as Cheapernet or STARLAN.

LAN Traffic Reduction. The packet filtering feature of a LAN Bridge is commonly used to solve LAN congestion problems. A busy network such as the Ethernet shown in Figure 6 can be subdivided into two or more smaller segments which are connected with LAN Bridges. Devices on one segment still communicate with their peers on that same segment.


The important difference here is that this intersegment traffic is local: Bridge filtering prevents this intersegment traffic from appearing on the second segment since only packets that are addressed to devices on the second segment will be allowed to pass.


Thus the local packets don't unnecessarily congest other segments. The result is a substantial load reduction on each of the two LAN segments with no sacrifice in connectivity or performance.


Remote LAN Connections. Connecting LANs in remote offices or divisions can best be accomplished using protocol-transparent LAN Bridges. Remote LAN Bridges provide bridging and data communication interfaces in a single unit. Each remote LAN Bridge monitors packet traffic on its LAN, capturing those packets destined for remote locations. It converts these packets into serial data format for transmission over telecom-

munication lines like 9.6 KB/sec., 56 KB/sec. or T1 (see Figure 7).

At the other end of the serial link, the serial data is converted to the appropriate LAN standard and transmitted to the attached network. Bridge filtering assures that only those







packets destined for remote locations are transmitted over the serial links. This allows internetworking to take place on relatively lowspeed leased lines saving recurring line costs.

Protocol-independent remote Bridges further reduce cost by allowing many LAN users to send data to their remote peers without having any protocol restrictions or limitations.


This is in sharp contrast to remote Bridge capabilities provided by the suppliers of LAN File Servers. The latter requires that a telecommunication line be used for connecting LAN devices that use only that vendor's protocols.

HE ABILITY TO transfer data packets between different LANs independently of LAN standards or proocols is a feature that no other LAN product offers. LAN Bridges often are 10 to 100 times faster and significantly less expensive than other internetworking products such as routers or gateways. The nonintrusive nature of the Bridge and the resulting simplicity of application and maintenance also are major advantages.

As the need for internetworking of LANs continues to increase, the only device that maintains network performance and economy is the ILAN Learning LAN Bridge. —Tad Witkowicz is president and founder of CrossComm Cor-

poration, based in Marlboro, Massachusetts.

Would you like to continue to see articles on this topic? Enter on reader card yes 346 no 345



Are you searching for a better way to maintain your Image™ database?

PRESENTING IMF/1000 THE FAST, CONVENIENT WAY TO MAINTAIN YOUR DATABASE-ON-LINE

Now you can maintain, modify or change your HP 1000's Image database without bringing your operations to a standstill. IMF/1000 is the only program—including HP's own utilities—that gives you the power and flexibility to alter your database without the time consuming task of unloading and reloading the database each time. IMF/1000 is an easy to use, menu-driven program that has been installed on hundreds of systems in the last four years. So take a closer look at IMF/1000, and be confident that you—not your database—control your operations.

- Change data set capacity
- Locate and repair broken chains
- Modify paths between sets
- Modify fields
- Change data characteristics

Call today for more information and ask about our free demonstration program.






HP 1000 and Image are registered trademarks of Hewlett Packard Co.

COMSCI DATA SYSTEMS, INC. P.O. Box 20101, Atlanta, GA 30325 404-352-3533

# The Best And The Worst Of The Microcomputer Compatibility Sideshow

# Compatibility

[By Don Person]



purposes nonexistent outside the HP product line. I'm not including problems between HP models and operating system variations within lines in the HP captive market already. In the past two years, I've been facing the best and the worst of the microcomputer compatibility sideshow. Let me outline the dimensions of the problem for you.

Normally, if all your programs work the way you want on an IBM PC XT/AT (you fill in the letters), and each functions identically and accurately in the time domain on another computer, then the other computer is said to be "compatible." On the other hand, if a program doesn't work, data can't be exchanged, programs run but feel like they fell into the honey jar, or you add one more program to your suite and suffer a crash, then you have an "incompatible."

HP seems to have specialized in making IN-compatible PCs for as long as they've been mucking with MS-DOS. Mostly this has been attributable to the "creeping feature creature" syndrome that the in-house BIOS playboys can't seem to shake. Take the basic machine and mess with the operating system to add something proprietary (like touch, for instance) and you make the resultant box just that much less compatible with the IBM device you've tried (and failed again) to clone. That has become HP's specialty niche — maker of Almost PC and Almost UNIX clones.

There are other less innocent factors, but viewed charitably, that's the picture. Can you name all the UNIX hardware providers who can interchange disc information with HP-UX? Hint: The answer is believed to be in the region bounded by zero and none.

34 HP PROFESSIONAL

Time domain decoupling effects are the single most troublesome side effects of so-called compatibility packages. The problems range from the subtle to the obvious. This is the "honey jar" I mentioned. Products like the Viper simulator amply demonstrate it. A program runs on an alien "compatible" system, but the time domain performance is completely wacked out.

The situation is seen at its worst in simulators created totally in software, and this applies as much to devices running under MS-DOS as it does to the complement. It's a level of problem that's really beyond the scope of mortal user intervention.

What then is to be known about HP file compatibility that can help you beat the odds and actually move files at will?

Here are answers to three common questions I'm repeatedly asked by customers in need of support for non-HP compatibles.

UESTION #1: Why can't programs be interchanged between the PC and HP?

This is far more complicated than you think, because so often the petitioner isn't sure of what he's asking. Let's break this down a little further.

First, from the MS-DOS side of the fence. If the "program" is executable (EXE or COM), there's no hope, short of running it on an HP-PC clone in the Vectra line. Hopefully, the Vectra will have Phoenix BIOS Version B or beyond. If this is true, you have a 95 percent compatible and all major programs will run.

With the exception of keyboard drivers, the ES series has come as close to pure PC compatibility as you'll find. Of course you'll want to use Vectra DOS version 3.2; take my word for it! Upgraded as it has been, there still are nasty surprises.

If you run a standard IBM AT or clone keyboard on a Vectra ES-12, it eventually will lock up. While it works, it only has half the key-repeat rate experienced when used on a real AT. It appears that the ES may subtly damage non-HP keyboards. Two different keyboards that I was foolish enough to use on an ES failed after a while in rather peculiar ways.

If you have an older Vectra, the best way to get compatible is to install the BIOS upgrade right away. There's no help for upgrading the pathetic Human Interface Loop (HIL) keyboard at all. HIL would be better named InHuman Interface Loop, since it was another of those incompatible HP better ideas that blessed us with the IHIL mouse and a plethora of keyboard interface problems, most notoriously of the Honey Jar variety. That was a major incompatibility factor in the first generation of standard Vectras.

Other than the HP-UX MS-DOS adaptor that runs MS-DOS as a child process under HP-UX (at significant cash and time expense) there's no other HP computer that can "play" an MS-DOS program.

Now another view: Many HP micro folks really are talk-

ing about some version of HP-BASIC or PASCAL when they ask the question. There's some source code compatibility between HP and MS-DOS languages, but when we get down to a discussion of just what lines up, there still is precious little. Sometimes, there's hardly more than the line numbering to take comfort in. Since MS-DOS exclusively is an INTEL processor operating system and HP has "standardized" on combinations of Motorola and pure proprietary CPUs, you can see how essentially hopeless this is.

If you can move the source code to a language compiler with similar syntax, and you're willing to put in the time to do a whole new round of debug and keyword swapping, there's a ray of hope. Just how much hope depends strictly on how much you plan to make use of unique hardware features.

As I've discussed in the past, there's good support for HPIB, IEEE-488 input/output on PC-AT class computers. Serial I/O and parallel output are somewhat transportable from HP to MS-DOS, but the converse requires more sweat.

Any program that depends on READIO, WRITEIO, STATUS, CONTROL or specialty hardware doo-dads like BCD or GPIO ports will move the conversion up near the end of the scale of difficulty. In all likelihood, you'll have to learn C or assembly language to do what you want. Keyboard and CRT compatibility is pretty much out of the question.

The balance tips plainly toward the differences as soon as you get beyond simple PRINT DISP WRITELN statements. First-degree rework is the order of the day, and auto translation is considered pretty much a joke for other than code of such simplicity and brevity that you wouldn't bother to convert in the first place.

FileSwap-PC and other programs make it physically possible to move data and programs stored as string data back and forth between HP and MS-DOS computers, but there's no translator on the market that approaches completeness in auto translation for MS-DOS. This is hard manual labor should you be desperate enough to make the move.

UESTION #2: Why can't I read HP discs on another computer? When I copy BDAT files using a file translator, the result is crazy garbage. LIF files copy okay, so why won't BDAT move?

This is almost a corollary to number one, but opens a larger worm can. Let's take the simpler problem first. This gets right to the heart of a design-level decision that HP made way back in time.

It all started innocently enough with that venerable antique HPL. Specifically, data typing in BDAT files is controlled by the program that writes the file, NOT the language/operating system! This isn't a problem in itself, but there's no mixed typing identity provided for mass storage records.

The only other storage choice is LIF-ASCII, which per-

mits only serial strings to be read or written. Of the HP BASIC languages, only Series 80 BASIC and technical BASIC for the Integral provide data markers in record files, and that leaves Rocky Mountain BASIC programmers staring at one of numerous dumb throwback aspects of their language.

It's a tough choice. Use mixed data records or give up random access for compatibility. This could've been cleanly addressed if the RMB crew had decided to include a new random record structure when they bloated up the 5.0 version.

Here are your choices: Either program so that files are stored as LIF (which is a very nice interchange format) or serial port. Believe it or not, there's no way for a conversion program to know the structure of BDAT records without data headers. BDAT files physically can be moved, but the copy is still the binary image.

Are there any hot-shot programmers who can read a BDAT file without seeing the code that wrote it and successfully tell whether a record contains a collection of integer zeros or just null ASCII strings? No! Integer zeros each contain two ASCII zeros, while a null string is marked by four ASCII zeros. There's no difference between a program that writes two integer zeros or one that writes a single null string. The only way to make disc transport possible is to examine the program that creates the BDAT file and to make an intermediate program that reads the data types as they were written, and then dump the data as a string or its VAL\$() equivalent into a LIF-ASCII serial file. At this point, FileSwap or other translators can move it with ease.

The exceedingly wise choice of Series 80s designers to nip this problem is the main reason it's so much easier to move files from that family today. In Series 80, every datum has a unique way to identify its type, even if read on an alien machine. Know the header code and you know the file.

Now back to the first part of the question. Since we know that HP programs have unique data structures and a common compatibility format (LIF), it should be no surprise to find that a parallel also exists with MS-DOS.

Spreadsheets, word processors and graphics programs almost universally use proprietary formats (read undocumented), but usually include DOS ASCII as an option. This is what allows simple translators a shot at HP data in the first place. DOS ASCII prints ordinary strings terminated by a carriage return and linefeed pair. While not as flexible as LIF, since it can't convey character 13 or 10 as legal data, it's at least nearly universally recognized. This also happens to be the standard way text is stored under good old HP-CP/M.

To be sure of making a transform possible in a bidirectional sense, be sure to store "compatibility" data as ASCII on either medium. This is the sure way to move numbers into spreadsheets and text between documents. If the data is binary in nature, it still can be moved, but you'll have to do some amount of programmed conversion on the target side of the move.

And then we have the nasty ASCII Z-string "convention" promulgated by UNIX and the C programming language. Terminating strings with the ASCII zero character may appeal to Eunuches, but not to me. It's no better than the CR/LF combination I've already mentioned, and in other ways it's a lot worse. Making character zero illegal raises hell with translation, and if this is your lot, I only can offer my condolences. HP didn't bite you here; this is a problem bigger than both of us.

UESTION #3: What can I do to make files produced by the Integral and larger HP-UX computers transportable to other computers?

When I'm feeling facetious, I usually ask if the poor sucker knows where his serial port is. Disc organization under UNIX is pretty weird and HP-UX has moved bad to worse here. The folks in Corvallis have some one-way data transport tools for the Integral that make it read Series 80 and some version levels of MS-DOS, provided you have access to ss/80 disc drives.

If you have the larger desk models in the 300 family, you have the pricey option of running the MS-DOS compatibility plug-in. If data exchange is the only object, I hope your bank account is well charged. Otherwise, the old serial connection really starts to look attractive. For real-time users, HP-UX has been difficult enough, but the striking lack of data portability adds insult to injury.

HP is making strides to catch up with the rest of the PC-compatible industry. Unfortunately, even simple upgrades come a year or more after lesser-known innovators already have done the same thing. Simple add-ons like the 3½-inch drive and a DOS able to support them are a prime example.

You see, the compatibility issue will never be resolved, and for a good reason. HP doesn't really want the problem any more "solved" than it already is. We all know or suspect comfortable profit margins in the hardware HP sells us, but there are really terrific profits to be had elsewhere, and HP knows it.

By going to an extreme with the 150, HP learned that there were limits to what its sales force could do. We all stopped short of buying into an "open" system still rife with proprietary features. Flying tangentially to the established force of the genuinely open PC standard, HP learned that nobody with money and good judgement really wanted to buy a specially modified version of Lotus 1-2-3 and still not be able to exchange spreadsheets with IBM PCs.

This was the case with a lot of popular PC software that had to be converted to run on the Touch family, and still was incapable of anything approaching what you and I think of as easy data transfer, unless of course you count the HP-supplied terminal program that lets you connect your 150 to an HP-supplied minicomputer running HP-supplied system (and probably applications) software supported (and

HP PROFESSIONAL

understood) solely by your friendly HP staff.

This overall slant keeps independent repair service out of the picture, since only HP has the information and parts to keep your equipment running. I shouldn't have to explain what the economics of a captive market do to you. Usually your experience teaches that well enough. Perhaps now you know why HP has its own part numbering system. If you knew that the dead IC with the alien part number on the top was in fact a relabeled 74LS05, you wouldn't have to run to HP or pay so much. There's nothing in it for HP if you can fix a dead machine with generic parts.

For example, your IBM PC/AT power supply gives a great puff of smoke and everything comes to a halt. Finding no obvious short circuits on any of the outgoing supply pins, you decide that the power supply is indeed the problem. Almost anywhere in the country, you can buy a replacement power supply for about \$100 or less. Installation is accomplished with a screwdriver in under a half hour, and you're back in business.

Suppose you have a Vectra AT. HP has chosen a profile, mounting and power switch method that's incompatible with the vanilla design that virtually everyone else uses. The bottom line is that the same repair will cost you up to \$400 unless you've bought into the service contract numbers game. You'll pay about \$200 per year to carry this HP-supplied insurance, and here we see another way that not addressing compatibility

issues feeds the bottom line at HP. If you don't feel confident that anyone but HP can service your equipment, you're an easy mark when the sales force circles around to sell you some really lucrative stuff — the service contract.

Profits here can put even software to shame, and this is the big gotcha that HP has been protecting. Should HP make a fully compatible clone and risk defectors to third-party vendors for the whole range of options from software to service or continue with a minimal market share of captives? HP's choice has been pretty obvious. The company response has been to do no more than necessary with microcomputers, while moving all the research and development dollars upscale into the minicomputer line.

In spite of management's myopic obstinacy, HP languages like RMB still pull their weight, but just barely. Throughout the product line, old age is beginning to tell. Wake up, HP. Like it or not, MS-DOS machines are the standard for data analysis and word handling. While you drag your feet on MS-DOS issues, those of us who have to live with the consequences are more tempted to break the chains. There's nothing like the scorn of a betrayed lover, except perhaps a clone buyer. —Don Person is an independent consultant based in Albany, NY.

Would you like to continue to see articles on this topic?

Enter on reader card

yes 344 no 343

# ELECTRONIC FORMS The complete solution is now available!

The **IPRINT** Electronic forms products from **Indigo** provide the capability to print your data on laser printer forms. **No more pre-printed forms!** 

IPRINT is a powerful forms design product for PCs. The design on the PC screen corresponds to the output on the laser printer. The complete camera ready copy for this ad was prepared using IPRINT on the HP LaserJet Series II.

IMERGE provides production printing capabilities using compiled IPRINT electronic forms. These forms can be stored in the printer. When IMERGE prints your data with the forms, only the data is sent. IMERGE is available now for the PC, PC LANs, HP3000, DEC VAX, HP9000/300 and HP9000/840. Ask about IMERGE on your computer.

**IPROMPT** provides an automatic data entry and print facility using **IPRINT** electronic forms on a PC. The data entry screens can be customized.

#### **BENEFITS OF USING ELECTRONIC FORMS:**

- No investment in pre-printed forms inventory and storage is required;
- Short lead time and low cost to create new forms and change existing forms;
- No waste in discarding obsolete forms;
- Easy distribution to all your forms users;
- No operator is required to change forms;
- Improved operational efficiency and flexibility.

For more information contact:

Product Manager, Indigo Software Ltd.


Product Manager, Indigo Software Ltd. 560 Rochester St. #400, Ottawa, Ont., K1S 5K2 Phone: (800) 267-9976 or (613) 594-3026



38 HP PROFESSIONAL

# Connectivity And Communication

Improving Research And Development



Ever since computers were first developed, the need arose for connecting the machines to share information. Communication between machines is a natural progression of technology. The study of the optimum configuration for the connection between com-

puters includes ongoing research in graph theory, queuing theory and algorithmics. Often, advances in theory have immediate benefits to the user community and the research is well supported by telecommunication and computer companies such as Hewlett-Packard, GTE, AT&T, IBM and Digital.

WO TYPES OF NETWORKS and data flow management are packet switching, used to improve data communication, and circuit switching, used in telephone networks. Both technologies now may be considered vehicles for the integrated transmission of voice, data, video and other traffic.

In packet-switched technology, blocks of data, called packets, are transmitted from a source to a destination. Source and destination can be user terminals, computers, printers or any other types of data-communicating and data-handling devices. In this technology, packets from multiple users share

the same distribution and transmission facilities.

Other networks are of the

[By Dr. Michael M. Dediu]

Since computers require

transmission rates far in

excess of those possible

over telephone lines,

dedicated computer

networks are necessary.

circuit-switched type, most commonly portions of common telephone networks. In these networks, which generally transmit voice or data, a private transmission path is established between any pair or group of users attempting to communicate, and is held as long as transmission is required.

Integrated networks, combining aspects of both packet-

and circuit-switched technology, are now beginning to be deployed. They are expected to dominate the field in the 1990s or later.

The most common types of traffic handled are: interactive data, generally transmitted in short bursts of a few characters, to as many as 400 to 1000 characters between terminals and between terminals and computers; file transfer, involving the transmission of up to millions of characters (or bytes) between computers, or between mass

storage systems; and, increasingly, digital voice. Facsimiles, images and other types of traffic are being considered for transmission as well.

HE MOST COMMON communication networks today are the telephone networks. These are designed for voice communication and the technology is analog. Although telephone networks are used extensively for voice transmission, data signals normally must be converted (modulated) to voice-type analog signals using MODEMs (MODulator/DEModulator). This limits the rate of transmission of data to at most 14.4 kbps (9600-bps is a more common limit, due to noise), and then only using private, specially conditioned transmission facilities. Errors arise due to inherent noise. Therefore, error-correcting modems now are becoming the norm. Without error correction, transmission over dialed public telephone networks accommodate data bit rates of 300 to 2400 bps.

Digital modulation of voice onto digital networks is becoming more frequent with the introduction of fiber-optic transmission media. The switch to digital networks is a great advantage to data transmission, since transmission rates will exceed 1.544 Mbps (the T1 system). This type of digital carrier transmission is used extensively for so-called short-haul communication, up to 25 miles. The advent of long-haul fiber optic transmission systems will expedite the transition to all-digital telephone networks.

When telephone networks become all digital, any kind of data, whether of the interactive data type or computers communicating with one another, digital voice or digital images could traverse a network. Each type might be handled differently, or some could be multiplexed.

Since computers require transmission rates far in excess of those possible over telephone lines, dedicated computer networks are necessary. These networks are usually called local, since they don't span great distances. There are three types of local networks: local area network (LAN), high-speed local

network (HSLN) or local computer network (LCN), and computerized branch exchange (CBX).

A local network is a network of terminals, hosts and other devices that are physically close. The nature of a local network falls somewhere between a multiprocessor system and a longhaul data network. The characteristics of local networks are:

- High data rates (0.1 to 100 Mbps)
- Short distances (0.1 to 50 Km)
- Low error rate [10exp(-8)] to 10exp(-11)

The benefits of implement-

ing a local network include the potential of system evolution, high user availability and resource sharing. The problems that a local network can create are inoperability, lack of security and data integrity.

The local networks can be classified in function of their transmission medium and topology. Topologies include:

- *Star*, a set of nodes radially linked to a central controller. This topology is common for Computerized Branch Exchange (CBX) networks.
- Ring, a set of nodes or networks linked in a ring. Common in LANs.
- Bus, nodes attached to a common channel. This topology is typical of the Ethernet LAN.
- *Tree*, a set of buses attached to one point. This configuration is popular for networks of networks.
- *Mesh*, single connections between nodes. This topology is useful when redundancy is necessary for system integrity. An important question is whether a message can be sent to any node, even if nodes in the shortest path are down.


The transmission media include:

- Twisted Pair, with a capacity of 10 Mbps.
- *Coax Cable*, with 50 Mbps capacity over short distances. The data is not modulated onto a carrier frequency (also called baseband or single channel).
- CATV Cable, which can accommodate 20 Mbps over short and long distances. The data is modulated onto a carrier (broadband or multichannel), but physically, the wire is the same as Coax.
- Microwave (1.5 Mbps), for transmission between buildings.
- Laser (1.5 Mbps), used to transmit through air between sites.
- Infrared (150 kbps), the same idea as laser.

40 HP PROFESSIONAL

# A Communication Solution for Incompatible Hosts and Terminals.


For customers like Bell Operating Companies, Tri-Data Systems has created a unique way of linking incompatible hosts and network resources. It's called the Netway System.



Call us today and ask how we can help with your data communication needs.

#### Tri-Data Systems, Inc.

1450 Kifer Road, Sunnyvale, CA 94086 Telex: 172282 FAX: (408) 746-2074 Telephone: (408) 746-2900 Extension 300



## Access Any Host Protocol From a Single Workstation

With the Netway System you can access any host protocol from a single workstation and turn otherwise single-session terminals into multi-session workstations.

### **Connect Your Existing Resources And Minimize Costs**

Tri-Data's Netway System reduces your overall data communication costs by improving end-user productivity and allowing you greater flexibility in planning future communication requirements. Instead of replacing your equipment, you gain a unified system that has more functionality and increased resource-sharing capability.



TRI-DATA

Satisfying our customers for more than 20 years.

Netway is a registered trademark of Tri-Data Systems, Inc. Each standard has its

advantages, and the

proponents of each are

firmly entrenched.

- Fiber Optics [250 Mbps to several Gbps (billions of bits per second)], the most promising medium for its raw volume, speed, flexibility and security.
- FM radio (19.2 Kbps), good for long distance communication.

OCAL AREA NETWORK STANDARDS have been developed by the IEEE through a special committee called the IEEE 802 Committee. One of the two standards is almost identical to the Ethernet specification that was

developed jointly by Xerox, Intel and Digital Equipment Corporation in 1982. The Ethernet standard has enjoyed broad use, especially as part of DEC systems and UNIX installations.

The basic concept of the Ethernet (CSMA/CD) protocol is quite simple. All stations listen for transmissions on the line. A station that wishes to transmit does so only if it de-

tects the channel is idle. This procedure is called carrier sensing (CS), and the access strategy using it is termed CSMA (Carrier Sense Multi-Access) scheme.

It's clear that collisions may occur since stations are physically displaced from one another, and two or more stations may sense that the channel is idle and start transmitting, causing a collision. Once stations detect a collision (collision detection, or CD), they transmit a special jam signal notifying all other stations to that effect and abort their transmissions.

The second standard is the token-passing ring, developed by researchers at the IBM Zurich Research Laboratories. The token concept has a ring topology with no central controller. All stations operate in a decentralized mode. All messages (frames) move around the ring and are actively repeated by each station through which they pass.

A station reading its own address as a destination copies the frame while passing it on, bit by bit, to the next station on the ring. The information contained in the frame then will be passed on to terminals, controllers or other devices connected to the station. A circulation frame is removed from the ring by the station that transmitted it.

Each standard has its advantages, and the proponents of each are firmly entrenched. However, there is room for both in the world, and their use is likely to grow.

#### Advances in LAN Technology

AN USERS GET an important improvement from a recent enhancement to data PBXs, the addition of synchronous transmission facilities. When it debuted in

1972, the data PBX solved primarily asynchronous communication problems. Today many computer systems communicate with their terminal networks by synchronous transmission, and data switching technology has evolved to handle this development. In fact, the most recent advances make it more accurate to describe these systems as integrated network processors rather than as data PBXs.

For example, one of the functions that some of these systems can perform in a large synchronous data-com net-

work is management of the data links joining terminals, cluster controllers and host mainframes. This helps the network manager protect users from failures by allowing new links to be switched into the network when old links fail. Also, bandwidths can be consolidated, so multiple low-speed or intermittently used terminals and data links can be multiplexed onto

higher speed links. With the data networking system able to support synchronous interfaces to mainframes, additional functionality is possible on the terminal side.

ATEWAY FUNCTIONS can be added by means of integrated protocol converters. This enables asynchronous or synchronous terminals from one vendor to communicate with mainframes and other nodes provided by other vendors.

Similarly, today's network processor can provide LAN gateways. An integrated gateway on the network processor connects into a specific LAN, such as IBM's token ring. The gateway also provides software for protocol conversion, to allow a device on the LAN to communicate through the data PBX to another LAN gateway, or some other facility, such as a host mainframe.

In addition, users can benefit from high-speed digital communication interfaces available from some vendors. These include the new generation of switched 56 kbps services, 1.544 Mbps T1 communication in North America, and 2.048 Mbps European equivalent. Though PC prices are at their lowest, a corporate PC with hard disc, printer and software represents a substantial investment.

One recent data networking development from Gandalf brings PC capabilities to users without the PC investment. The solution is a pool of MS-DOS compatible processors integrated into the switch and connected to each other via a high-speed LAN, the Novell NetWare operating system.

An important aspect of a network is the performance analysis of the distributed routing algorithms. A formal quantitative comparison of shortest path distributed routing algo-

42 HP PROFESSIONAL

rithms is rather difficult to carry out, for two major reasons.

First, there are a number of performance criteria that one might want to use to assess performance. The performance of various algorithms may very well differ; some may have better performance on certain objective functions; others, on other objective functions.

Second, the relative performance of algorithms depends on specific network configurations. You can obtain general analytic results for certain regular graphs only. For "real" network configurations, you must rely on computer analysis and simulations.

What are some criteria you might want to use to evaluate the performance of a given shortest-path algorithm? Note that as long as the network is quiescent (at a steady state), routing tables remain unchanged. All shortest path algorithms provide the same results for the routing tables. The differences in the various algorithms arise when they adapt to changes in network topology. Thus, we must compare algorithms as to how they perform in response to a change. Various criteria are:

■ Speed of response. This is the time for a change in topology to propagate through the network, and for the routing tables to settle down to a new quiescent, shortest path state. As a

measure of speed, you can consider the average number of iterations required for the algorithm to converge to a new state. This performance measure obviously is important in a dynamic environment, for the speed of response must be faster than the rate of change of network topology. Otherwise, convergence won't occur and the routing algorithm will be useless.

- Number of control packets transmitted. This is the information that must be transmitted network-wide to propagate the desired topological change and routing-table updates. The larger the number of control packets, the larger the overhead and the greater the possible congestion introduced by transmitting topological and routing change information.
- Computational complexity. Algorithms require varying amounts of computation at a node to process the control packets, carry out the shortest-path computations and update the routing tables. This also is reflected in processing time at a node and, therefore, in processing speed.
- Size of control packets. Algorithms differ as to the amount of information transmitted per control packet.
- Buffer space required. Algorithms differ as to memory space required to update and hold the routing tables.
- Looping and loop freedom. Loop freedom refers to the transient, converging state of a routing algorithm. A loop-free



OSI compatibility provides

the users with LANs

and wide area networks

that support a large

variety of applications

and compatibility.

algorithm ensures that data packets won't return to nodes already visited, while the routing tables are in the process of changing.

To analyze and design communication systems that are operating in the presence of noise, it's necessary to use

statistical concepts. Communication systems are concerned with the transmission of information from a source to a sink or user.

N OUR AGE of information, communication and connectivity between computers are two very rapidly changing technologies. Some of the latest advances in communication are, for the first time, land mobile satellite systems received worldwide radio frequency allocation; European countries agreed to build a unified digital cellular communica-

tion system; optical fiber began to be used by the telephone companies for connections directly to the home; electronic and voice messaging, as well as videotext services, began to be commercially successful.

For the communication of data to and from laptop terminals in vehicles, Spectrum Cellular Corp. introduced the first cellular telephone modems, which transmit at 1200 bits per second. TAT-8 is the first optical-fiber transatlantic cable, and will be completed this year between the United States, Great Britain and France. HAW-4/TPC-3 is the first transpacific fiber-optic cable between California, Hawaii, Japan and Guam.

Hewlett-Packard began to develop distributed data processing products in 1973. Using international standards, HP started in 1981 to interconnect multivendor systems, installing over 40,000 nodes in networked configurations. HP Advance-Net is based on industry standards, uses the Open Systems Interconnect (OSI) Reference Model and offers a set of extensive networking products. OSI compatibility provides the users with LANs and wide area networks that support a large variety of applications and compatibility.

Let's see an example of the HP AdvanceNet Environment, based on HP 9000 Series 800: A user could connect a group of Vectras, PCs and ATs with HP 1000 A-Series, with HP 9000 Model 825S, then with an HP 9000 Model 850S. Then he could add some UNIX system workstations connected to a LAN based on IEEE 802.3 or Ethernet, then use the HP 9000 Series 300 to connect (using SNA) an IBM mainframe working on MVS, CKS, IMS or CMS, then put an HP 9000 Model 840S on the net, and don't forget to add all your DEC VAX clusters using their VMS or UNIX BSD. From this example, it's easy to understand the power and capabilities of this HP AdvanceNet.

HP offers multivendor communication by supporting in-

dustry standards that provide communication with a variety of minicomputers and superminicomputers. These standards include IEEE 802.3 and Ethernet, Transmission Control Protocol and Internet Protocol (TCP/IP), as well as ARPA and Berkeley networking services.

HP supports many network protocols, offering compatibility with most computer networks. For example, HP AdvanceNet connects with DEC VAX computers through a product that's compatible with DECNET and features file transfers between DEC VAX and HP computer systems. Communication to IBM systems can be done over SNA. HP Precision Architecture products, working in a networked environment, can help to exchange information among different systems and consolidate the network

In the supercomputer market, the National Center for Supercomputing Applications at the University of Illinois at Urbana-Champaign uses a Cray X-MP/48 Supercomputer connected through a backbone network to other supercomputers in the National Science Foundation support centers. The Cray may be accessed through a variety of workstations, including microcomputers from HP, Apple, DEC, IBM and SUN. This Center has a visualization facility.

RGINEERS AND SCIENTISTS can analyze their data in realtime, using graphical animations of their simulations and produce video tapes of their results. The use of supercomputers, communication, networks and colorimaging techniques will fulfill von Neumann's vision that computers would become the tools for solving non-linear partial differential equations. From these computer calculations it clearly will appear that the multi-dimensional dynamic solutions of non-linear partial differential equations can exhibit complex behavior compared to what you normally encounter in analytic solutions.


The intelligent use of computers, connectivity, communication and enhanced visualization is going to significantly improve the methods used in research and development in many areas of science, engineering and business. —Dr. Michael M. Dediu is president of Dediu Computer Consultants, Tewksbury, Massachusettes.

Would you like to continue to see articles on this topic?

Enter on reader card

yes 350 no 349

## DOES NIGHTLY BACKUP GET YOUR SYSTEM DOWN?



Then take a look at how



can help save you time and money!!!

HIBACK/3000 provides functional components which address two critical areas within your ongoing production environment:

- HI-SPEED Database and File
   Backup
- HI-DENSITY Data Compression

... all rolled into one easy to use product – with features such as: Unattended Operation, Hi-Speed Execution and Shared Access during database backup.

HIBACK/3000 will increase your system's availability, give your System Manager higher productivity and save you money every day you use it.

- Hi-density data compression for backup and network transfers can save you over 70% in both media and line transmission costs.
- Uninterrupted shared database access during store lets you backup databases while nightly reports are running or users are still online inquiring.
- Unattended backup to standard disc drives lets your system keep working while your staff is resting, by using your available freespace as a temporary or permanent backup media.
- Hi-speed combined database and file backup replaces DBSTORE and MPE STORE with a single high-speed facility.
- Full compatibility with all HP storage devices extends the usefull lifespan of what you've got installed today and lets you take advantage of what comes out tomorrow.
- Remote restore to systems which do not have HIBACK/3000 installed lets you transfer data to those who haven't caught on to our secret yet.
- Across network STORE for unattended backup of distributed systems under central control.

Call today and let HIBACK/3000 start saving your organization time and money!!!

**ENTER 135 ON READER CARD** 

HI-COMP Hinrichs GmbH Eichenlohweg 24 2000 Hamburg 60 Telephone: 040/6304011 Telefax: 040/6316004 Teletex: 2627-403960



HI-COMP America, Inc. 11 Cranberry Street Brooklyn, New York 11201 Toll free: 1-800-DBETUNE Telephone: 718/855-4437 Telefax: 718/875-4906

# HE NEW 350/835 TurboSRX

HP's Latest
3-D Graphics
Workstation

On April 1, HP announced the 350/835 TurboSRX, a high-performance 3-D graphics workstation that utilizes the most advanced and extensive feature set available in its price range. This increases customers' productivity and competitiveness by maximizing graphics interactivity while displaying superior photorealistic images.

It is the result of continued work with key customers and application suppliers. The customers have asked to remain anonymous, but applications suppliers such as McDonnell Douglas, SDRC, Patran and Deneb Robotics have helped us define this advanced and extensive feature set that maximizes graphics interactivity while displaying photorealism.

Graphics interactivity and photorealism (the ability to display very realistic-looking images) are critical to improving productivity. An engineer needs to interactively manipulate the model he has created so that he can try many different ideas. When he creates a model that's close to what he believes is correct, he wants to render that model as realistically as possible, so others quickly can understand what the model will look like when it's built and eliminate prototypes. Ideally, he would like to work interactively with the photorealistic image from the start. With the Turbosrx, he can.

The TurboSRX is designed to work on either Precision Architecture (835) or on 68000-based architecture (Series 300) to become a complete high-performance graphics workstation. The subsystem consists of a graphics display controller, a high-resolution 19-inch color monitor and 8-24 frame buffers with four overlay planes, 1-3 transform engines, a scan converter and 16 planes of Z buffer.

Like the SRX, the system is very versatile. When configured as individual pieces, the system can grow by adding frame buffer memory, transform and scan conversion boards and Z buffer boards. Beginning with an eight-plane low-cost color system, the system will expand to a high-performance system with 16.7 million colors. This means a customer can configure a system that will meet his needs exactly and can grow as his needs grow.

All the features of the SRX are maintained and their performance has been improved three to 10 times. It is object code and source code compatible, so all an application program that now runs on the SRX needs to do is relink to the new driver. However, the TurboSRX also includes a significant number of new features.

#### **Graphics Interactivity**

The Non-Uniform Rational B Spline (NURBS) with trimming curves was one of the most important contributions made to the SRX. A NURBS is a graphics primitive that allows applications to generate both geometric and free-form curves and surfaces parametrically, rather than generating segments of polygons directly. In TurboSRX, we have improved this from fourth order to sixth order.

For application suppliers, the benefit of NURBS is that it increases the flexibility in defining and controlling desired curves and surfaces without increasing the data involved. In addition, exact conic sections can be represented and it can provide precise ways to remove surface and intersecting points. For users it increases interactivity. It means that the data stored about the object is mathematically correct, rather than a geometric approximation, and it can reduce data storage by 75 times.

MOMA windows stands for Multiple



WORKSTATIONS

**Andy Barlow** 



The new 350/835 TurboSRX workstation features Ray Tracing, a method used to produce very realistic highlights, reflections and transmittance effects.

Obscurable Movable Accelerated windows. What this means is that multiple windows can be created, moved and obscured and still each of the windows will be accelerated by the graphics hardware.

Thus, different operations can run simultaneously in different windows and utilize all the hardware performance features of the TurboSRX. X Version 11 will be shown at introduction and will be fully incorporated with MOMA windows at the earliest possible date.

The Polygon Mesh Primitive is a Phigs + feature that substantially increases the polygon performance by reducing the lines necessary to draw the polygon. Two primitives have been implemented, the quadrilateral mesh and triangle strip. Preliminary tests show a

10x performance over the SRX for the triangle strip primitive.

Cursors now have been put in hardware so they can be moved independently and rapidly. The benefit of this is that cursor movement will not affect other features such as rendering performance and windows. In addition, full screen cursors are possible, or the cursor can be implemented as a 63 x 63 pixel icon. The cursors also provide considerable improvement in "rubberband" rectangles and line performance.

The Fast 16-Bit Z Buffer is now separate memory that's available for hidden line removal. It reduces the time to render drawings with hidden lines or surfaces by as much as 6x. A complete system now can consist of 24 color frames, four overlay planes and 16 frames for Z buffer.

Hardware Blending is a feature that allows individual images stored in the frame buffer to be selectively superim-

posed to detect more information. This feature will be particularly beneficial for imaging applications.

Pixel Pan and Zoom allows you to treat your monitor like a magnifying glass to view the entire frame buffer or to enlarge portions of it.

#### For Photorealistic Images

Radiosity is a method to render an object very realistically. It's a technique that accurately models the global illumination of diffuse surfaces. The strengths of the radiosity algorithm are highly realistic lighting, shading and shadowing effects. The advantage of Radiosity is that it allows users to change the view without having to recompute the image and in TurboSRX it is hardware assisted.

Ray Tracing is a method used to produce very realistic highlights, reflections and transmittance effects. Like Radiosity,




wenty-two percent of HP PROFESSIONAL Readers . . . have DEC VAXs at their site. Are you one of them?

a buyer of DEC hardware, software, peripherals?

the leading monthly magazine for DEC computing?

- . It's FREE!
- It's informative.
- It's monthly.
- It's read by over 94,000 professionals like you.
- It's time you had a free subscription too!

Read *DEC PROFESSIONAL* for information on the latest hardware, software, programs, new products, industry trends, problem solving suggestions and more. Each issue has timely, relevant DEC computing information. And each issue is a valuable reference you'll want to keep on hand for months to come. (Some of our subscribers have *DEC PROFESSIONAL* "libraries.")



Enter 151 on the Reader Information Card and we'll send you a subscription application today!

It's Free!




	FIGURE
	KEY ENHANCEMENTS
1. GRAPHICS INTERACTIVITY	
NEW FEATURE	BENEFIT
6th Order NURBS w/Trimming	Increased accuracy plus control.
Polygon Mesh Primitive	Increased performance of mesh models.
16-bit Z Buffer	Improves hidden line and surface removal performance.
Hardware Cursors	Cursors tracking do not affect application performance.
MOMA Windows	Multiple, obscurable, movable accelerated windows for simulatneous application performance.
Pixel Pan/Zoom	Increased ability to manipulate pixel data.
Frame Buffer Blending	Ability to interactively blend and overlay multiple images.
2. PHOTOREALISM	
NEW FEATURE	BENEFIT
Hardware-Assisted Radiosity	Interactive models with shading and shadows.
Ray Tracing	Highly realistic models with reflections and highlights.
Gamma Correction	Color accuracy in smooth shading.
Wireframe Lighting	Wireframe clarity.
16 Colored Lights	Improved lighting realism.

it usually takes time to render the first image. One major disadvantage of Ray Tracing algorithms is that they produce static images. Every time you change the view angle, the analysis must be recomputed. Both Ray Tracing and Radiosity are optional extensions to the Starbase library, thus any starbase application program that runs on the SRX or TurboSRX can be "ray traced" or "radiositised " or both.

Gamma Correction is a method of increasing realism by adjusting the displayed colors to compensate for non-linearities in the CRT monitor.

Wireframe Lighting allows hardware lighting models to be applied to the wireframe to increase the clarity.

Up to 16 hardware lights improve the lighting realism.

#### **System Components**

The *Display Controller* provides the resolution performance and the number of displayable colors necessary for highend graphics applications. The display controller is a box with the following components:

**Master Board** (opt) — This contains a transform engine and a scan converter. The transform engine converts

the 3-D world coordinates to 2-D screen coordinates based on the location of the viewer. It also performs clipping, color calculations and several other operations. The scan converter takes these commands and generates actual pixel information. Both these functions are implemented in VLSI technology.

**Slave Board** (opt) — This board adds two more transform engines, permitting transformations to be done in parallel and increasing performance.

#### Frame Buffer Controller Board

- The frame buffer controller board

# WHAT IN THE WORLD is an OPEN-ENDED PAYROLL SYSTEM?

We probably all know what a Closed-ended Payroll System is, but the idea of an Open-Ended system seems so ... well... open-ended ... that it might be hard to get a grip on what having one would actually be like.

So we thought we'd give you a look at just one little part of one.

For example, when you need a new data item in the employee master file, you press function key F3, then function key F4, then type the new item's name, then type an A for Alpha, an N for numeric, or a D for date, then type the number of character positions it is to take up and you're done. This normally takes about 15-30 seconds.

THE PAYROLL then includes that item in the employee master file data automatically, and you can use it in reports as a printed item or as selection criteria, and you can even include it in your own computations when needed.

We call this USER-DEFINED data.

You'll call it fabulous!

So if you're still struggling with a clunky old Closed Ended (ugh) payroll system give us a call today. There's a copy of

THE PAYROLL just right for your firm starting at only \$1200 from Cort Directions, Inc.

#### CORT DIRECTIONS

Cort Directions, Inc. 71-591 Biskra Road Rancho Mirage, California 92270 (619) 568-4681



and color map board are nothing more than very large memory where the color of each pixel on the screen can be stored. The frame buffer controller also provides the overlay planes. The overlay planes provide capabilities such as inSPU and graphics subsystem. Cabling is provided for three types of signals:

- *HP-HIL* for the keyboard, mouse and other HP-HIL input devices.
- Audio for the speaker to provide audio output for the system.

The 32-Bit High-Speed Local Graphics Bus (LGB) provides direct access to system memory, increasing total system performance.

teractive windows and menus and are alpha independent of the frame buffer.

1-3 Frame Buffer Boards — These boards add additional colors to these capabilities. Frame buffer memory can be added in increments of eight planes. The additional boards permit a system with up to 24 graphics planes, four overlay planes and a 16-bit Z buffer.

**Z Buffer Board** (opt) — This board increases the performance of hidden line removal and hidden surface removal and contains 16 planes of Z buffer.

**1-2 Power Supplies** — These provide power to the subsystem.

The 19-inch Color Monitor is the same 1,280 x 1,024, 19-inch color monitor used for the SRX. It has a high-quality 60-Hz non-interlaced refresh rate and a P22 phosphor for realistic colors. The CRT offers a clear, vivid image that doesn't wash out. The cylindrical face and antiglare coating are ergonomic design features for maximum eye comfort.

The 32-Bit High-Speed Local Graphics Bus (LGB) provides direct access to system memory, increasing total system performance.

Interface Card, RGB Video Cables, Cabling Extensions, and Input Devices: Through HP cabling extensions, human interface devices such as the display, keyboard, mouse and control dials can be placed up to 30 meters from the host  $\blacksquare$  *RGB* for the video signal to color display.

The bundled 350 TurboSRX and 835 TurboSRX systems will sell for \$70,000 and \$91,500 respectively. The Series 300 will compete in the mid-price range and the Series 835 will compete in the high end. Both systems come standard with 8 MB RAM, I/O Expander, HP-IB, DMA, LAN connection, HP-UX, mouse, NS-ARPA services, NFS software and a 1,280 x 1,024 pixel (60 Hz non-interlaced) 19-inch monitor. The display processor contains 24 image planes, four overlay planes, 16-bit Z buffer and three transform engines. In each price range, the graphics workstation will offer superior price performance.

A very aggressive upgrade program to move customers from the SRX to the TurboSRX also will be available. Existing users of a 350SRX or an 825SRX can upgrade to a fully configured system. The TurboSRX upgrade for the Model 350SRX will sell for \$15,000. The upgrade for the 825 (and 835) will sell for \$10,000. Typical upgrade programs in the past have preserved only 25 percent to 40 percent of the original investment.

Shipments are planned for June (350) and October (835). —Andy Barlow is Graphics Product Marketing Engineer, Hewlett-Packard, Ft. Collins, CO.

# BBS-PRISM FULL SCREEN EDITING FOR THE TERMINALLY SLOW

To run a healthy business, you need a computer system that won't keep your people waiting.

BBS-PRISM is a powerful full screen editor that lets you off-load just about all your editing functions to **PCs**, leaving the host system free for everything else. Your host won't get bogged down, and your people won't get frustrated.

We call this feature "Remote Program Development." You'll call it a lifesaver.

BBS-PRISM is the only rational approach to remote development, with its powerful features and the fact that only changes in the source file are transmitted back to the host, not the entire file. You get faster, smoother editing, with greater capabilities, in a package that is totally compatible with SPEEDEDIT, our 3000-based full screen editor and even EDIT/3000.


BBS-PRISM is loaded with useful features like built-in word processing.

Get all the details. Call Bradford Business Systems today. We've got an entire line of software designed to bring your business up to speed.

BBS-PRISM. A genuine contribution to office productivity.



25301 Cabot Road, Suite 201 Laguna Hills, CA 92653 (714) 859-4428



# PRINT

## Forms Follow Function Keys

Electronic forms can be a genuine time and money saver for any business. Using classical techniques of typesetting, paste-up and printing, forms can be expensive to produce and costly to inventory (paper is bulky). New electronic forms packages can deliver both responsive design capability and production on any PC and laser printer.

IPRINT is a powerful, easy-to-use forms-design package. You can create complicated, multipage forms visually on screen, merge them with data from text files and worksheets at print time, and even include predesigned logos, signatures and graphic images.

Many businesses might not think they have a burning need for custom-designed forms, but a form can be extremely useful in presenting information in a clear, easy-to-read style. A single short form can outline and highlight the same information as a 10-page internal memorandum. Combined with a data capture facility such as Indigo's *IPROMPT* or a print merging utility like *IMERGE*, forms can enhance existing data processing operations.

When you first call up *IPRINT*, you're presented with a self-explanatory function-key menu of routines. First you must "load" the form to be designed before you can work on it or print it. After we decided we wanted to "design" a form and loaded a form name, the function key labeled "execute" begged to be pressed.

The "execute" key is like the "DO IT" key on other programs. If you're in the design menu, it allows you to start designing. If you're in the print menu, choosing it prints the form. We couldn't agree on whether we liked it though; one of us thought it was a good idea to have a universal function key, the other didn't.

The main design screen is divided into

two parts, the menu on the left and the workspace on the right. A border drawn around part of the workspace represents the page, and since *IPRINT* works on a "what you see is what you get" format, it's easy to place the lines and boxes and such exactly where you want them.

The initial screen colors are disconcertingly difficult to distinguish on a CGA. On an EGA screen, they show as pale blue lines on a white background. After playing around with the menu choices, we discovered a key called "set," which led to another menu, one of whose choices was "color" (the index leads you to this command "color," but you have to flip back several pages to discover that this is a subcommand under "set").

Set color is a simple, intuitive procedure to change the colors of the five basic areas on the screen — menu, menu background, worksheet line, worksheet background and highlighting. Alas, there's no capability for setting the default colors while in the design mode; you must quit and edit a configuration file.

A second and more sinister note to CGA users: Since there are five regions on the screen and only four colors available at one time on your monitor, two of the regions have to have the same color, making it difficult to distinguish between them. It's probably best to have both the menu and the worksheet lines black.

However, once you've set the screen colors to something readable, the rest of the program will proceed without much of a snag — at least as far as the design phase goes. The



#### **SOFTWARE**

Ashley Grayson and Dafydd ab Hugh only major problem we encountered in the program was in getting the form we designed to print, but more about that later.

Making the user interface more consistent would be a definite improvement in *IPRINT*. Most commands are given by function keys suggested by the screen display. Forms design, however, is mouse-driven, but some of the menus are accessible only by the arrow keys, even in the middle of the design mode. Thus, to change fonts or line style, you first must use the mouse to select font or line style, and then, when the second-level menu flops down in front of you, go find the keyboard and poke at an arrow key until your choice is highlighted.

You can't just point at your choice with the mouse; indeed, the cursor disappears entirely.


The program purports to be usable even without a mouse, but only if you have megabytes of patience and not very much else to do that day. Our best suggestion: Get a mouse! Fortunately, *IPRINT* recognizes several different mice, from the Logitech to the Hewlett-Packard.

The general procedure for designing a form is to select a command (box, line, text) with the mouse and then fix the object on the screen. The whole procedure has a vaguely Macintosh-like feel to it, especially since the menu choices are mostly represented by icons, rather

than words. (Anyone experienced with a CAD system should have no problems.) The majority of these icons were clear — a shaded box for a shaded box, for instance. But a few are rather obscure, such as a box with an X through it for delete, or a question mark for help.

Unfortunately, since the icons weren't listed in the index, and since there was no quick reference, the only ways to track down what each icon meant were to experiment or skim through the entire command section in the manual.

The actual design process is straightforward. Since every box, line or block of text on the screen is a separate



object, it can be moved anywhere else, including overlapping another object. A command called "area" (represented by a box with dashed borders) allows multiple objects to be moved, copied or resized as a group (you cannot resize logos or fonts). There seems to be no way to alter the size of your text except for specifying a larger or smaller size as an alternate font (assuming your laser printer has such a larger or smaller size font internally or on one of its cartridges).

A certain amount of "graininess" must be put up with in *IPRINT*; the pro-

# You can create complicated, multipage forms visually on screen, merge them with data from text files and worksheets at print time . . .

gram divides the worksheet into a number of "cells," and then it restricts you to moving or sizing an object by integer numbers of cells (like graph paper). You can set the cell size using another non-intuitive icon to a minimum x-

direction movement of .027 inches and a minimum y-direction movement of .033 inches, which should be precise enough for most applications. However, if the cells are that small, it is hard to line up boxes and text and such. If the cell size is larger, the fact that you cannot place an object between two cells interferes with design aesthetics (such as centering text between two boxes).

It's possible to redefine the cell size in order to move an object and then redefine it again when you've finished; but it would have made more sense to be able to turn this aligning device off at will if you wanted to make an arbitrary move or set an arbitrary size.

Another minor cavil is that text is displayed only as solid blocks that approximate the size of the individual words. You have no clue to what the text says unless you either select the text as an object, in which case the complete text appears at the top of the screen, or you select an area of the page including the text and zoom in on it. Even then the words appear in screen fonts inside the solid blocks; you still don't get to see the text as it will appear on the page.

IPRINT is mostly intuitive, which is fortunate, because the manual is poor. The commands are arranged by function key number, rather than conceptually; there is no trouble-shooting guide; and the index covers only five and a half pages (in large type) for a 16-page manual.

EVEN WITH THESE petty grievances, *IPRINT* is a fun program to work with. A good number of vertical and horizontal line styles are supported, including

#	Application For	Visa for Resident Aliens
1		23]:
	Purpose of Visit to Terra:	
	Diplomatic Status Code [See Bo	x 17]:
	Are you a Fugative From Justice	e on Your Home Planet?YES NO
		0
	Planet of Origin Code [See	* There Ain't No Justice On My Planet
30000	Timilet of Origin Odde (occ.)	201.
*****		
	17	23 Planetary Orgin Codes
	Diplomatic Status	101Sirus Major VII 5Sirius Major XIX

All of IPRINT's demanding aspects were used to create this sample form.

The Graphics Gallery difference has to be experienced to be believed. So we've arranged for you to experience our business graphics software for yourself. Just call now to get your free demonstration

Find out for yourself how easy Graphics Gallery is to use. Take a look at the high quality output. Discover how quickly it turns ordinary worksheet files from Lotus® 1-2-3® into extraordinary charts and graphs. And see how effortlessly it works with all the most popular desktop publishing programs to enhance your results.

Because until you've actually slipped Graphics Gallery into your own disc drive, you simply won't know what a difference Graphics Gallery can make in your day—every day.

That's why we simply can't offer anything less than a real demonstration copy of the actual program. Use it just as you would a purchase copy (except

> for printing and saving files) and prove everything we say for yourself.

Graphics Gallery software is everything you'd expect from the industry leader in graphics devices like plotters and laser printers—and from the people who never

stop asking "What if ... '

## Take Graphics Gallery for a desk drive. But don't take our word for it. To order your free demonstrate the state of th

stration copy—or for more product or purchase information—just call 1-800-752-0900, Dept. 234i. Or write to Hewlett-Packard, Dept. 234i, 1000 N.E. Circle Blvd., Corvallis, OR 97330



#### JUST IMAGINE

A SOFTWARE PACKAGE
THAT INCLUDED THE
CAPABILITIES OF:

- PC to Host Printing
- 2392 Terminal Emulation
- ASCII/Binary File Transfer
- Host to Host Communication
- User Defined Operating Environment
- HPDESKMANAGER Interface
- And much more...

**IMAGINE** 

#### Universal ACCESS

#### MiniSoft, Inc.

15600 Redmond Way NE Suite 305 Redmond, WA 98052 800/682-0200 or 206/883-1353

Universal ACCESS is currently available for the HP3000, HP3000 9X0, VAX, HP9000, HP9000 8X0, HP1000, HP150, HP110, Integral PC, Vectra PC, IBMPC, and APPLE Macintosh.

[ ELECTRONIC FORMS ENVIRONMENT ]

A great deal has been written about the relative merits of PostScript from Adobe Systems and PCL (Printer Control Language), the language used by the Hewlett-Packard family of LaserJet printers. One or the other of these two page description languages is now used in most non-impact page printers currently on the market. What are their relative strengths and weaknesses when it comes to the "electronic" forms environment?

"Electronic" forms are printed repeatedly, with data filling in the blanks. They are a production data processing tool. Speed of printing is a critical factor in a successful implementation of "electronic" forms. PCL has several distinct advantages over PostScript in this area.

PCL is a very compact escape code driven language, while PostScript is an "English-like" language. PostScript can take 1.5 to 2 times as much data to draw the same form. This data must be sent to the printer. More data means a longer print time.

PCL uses bit-mapped fonts. Each point size is stored separately in the printer. PostScript stores only one size of a font. All other sizes are generated algorithmically at print time. These calculations take a great deal of time, especially on forms that are text intensive. Another point for PCL.

PCL allows the user to store the instructions needed to draw a form as a "macro" in the memory of the printer. PostScript has a similar capability, but the complexity of the forms that can be stored is so trivial that this feature is not viable. In PCL, instead of transmitting a form to the printer every time it is printed, it can be loaded once at the beginning of the "day" and then used repeatedly by sending a simple five-character escape sequence to the printer just before the data file is sent. Over the course of a day, an enormous amount of time can be saved using this feature of PCL.

PostScript does have one advantage over PCL. When it comes to forms design, PostScript is a much richer language. Its graphics capabilities are far beyond those of PCL. If an "artistic" form design is required, PostScript is more suitable. On a more practical level, PostScript allows text to be in both portrait and landscape mode on the same page. PCL does not have this capability. Of course the user pays for these more complex features. The additional complexities of PostScript slow it down. For most forms the more advanced features of PostScript are not required.

In summary, Hewlett-Packard's PCL has the features required to quickly and efficiently print forms merged with data. This speed advantage is critical in a sophisticated production "electronic" forms environment.

-Barry Gillespie, Indigo Software, Ottawa, Ontario.

dotted, dashed and invisible, while all lines (including diagonal lines) have a variable width. The boxes can be shaded in any one of a dozen ways, ranging from light gray to black to checkerboard, to vertical, horizontal, or diagonal (left or right) lines, and their borders can be any of the line types, any thickness, or even non-existent. Shading and borders don't appear as entries in the index, of course.

The logo facility is quite useful. You can design the logo with PC Paint, PC Paintbrush or Windows Paint and port the image file into *IPRINT*. To put

a logo on the form, you only need to select logo from the menu; *IPRINT* then will give you a drop-down menu containing the names of all logo files that have been defined (three predefined logos are included in the program — an *IPRINT* logo, a logo for Indigo and a picture of Snoopy). There's no facility in *IPRINT* itself for generating logos; you can't paint one with the mouse.

Once we got used to some of these strange conventions and limitations, however, we had no trouble designing

ENTER 141 ON READER CARD



# The application builder for the HP3000

#### "Must I buy a runtime system?"

A single copy of ARTESSA/3000 for your development site is all you need, because you can despatch compiled code to your user sites. ARTESSA/3000 saves you money!

#### "But what if I need to change my DP environment?"

Because ARTESSA/3000 generates COBOL source, migration couldn't be easier. ARTESSA/3000 protects your investment!

#### "Won't it restrict my choice of design?"

No, ARTESSA/3000 allows you to define your own standards, and ensures that they are consistently employed throughout your applications. ARTESSA/3000 gives you quality control!

#### "How can I ensure that we deliver what the user wants?"

Using ARTESSA's powerful prototyping facilities, you can interactively design the man/ machine interface, together with the user. ARTESSA/3000 will lead to satisfied end-users!

#### "How will it help with my maintenance workload?"

To accomplish a change, mostly only requires a simple update to the System Inventory, and re-generation of affected programs.

The ARTESSA/3000 user has a shorter maintenance backlog, and is not afraid of changes!

ARTESSA/3000 is a powerful, sophisticated tool, designed for the professional COBOL development environment.

#### Call or write today!

1-800-3383772

Assyst Computer Services (UK) Ltd N.V. RAET Belgium S.A. Arden House, West Street Leighton Buzzard Beds. LU7 7DD United Kingdom +44-525-382626

RAFT Netherlands PO Box 407 6803 EB Arnhem The Netherlands +31-85-246911

Excelsiorlaan 4 a Zaventem B-1930 Brussels +32-2-720-9060

Field Technologies Pty Ltd 62 Wellington Parade East Melbourne Victoria 3002 Australia +61-3-4175661

COA Computer Systems, Inc. 3370 South Service Road, Suite 207 Burlington Ontario L7N 3M6, Canada (416)333-0611

Wescom Systems 212 Pleasant Street Massachusetts 02062, USA (617)769-4344

Quality Consultants, Inc. 1775 The Exchange, Suite 380 Atlanta Georgia 30339-2016, USA (404)980-1988

Hawaiian Software Company 4025 Avati Drive San Diego California 92117, USA (619)270-6316

Artessa/3000 is a registered trade-mark of RAET Software Products B.V., PO Box 4077, 6803 EB Arnhem, Netherlands, +31-85-246218 a few forms. Our problems began when we tried to print one we designed.

Upon first installing *IPRINT*, you're asked what type of printer you have. Many common printers are offered as choices, including the LaserJet II, which is what we used. After installation, *IPRINT* offered appropriate choices of cartridges available and fonts found on them.

However, when we tried to print a form with text, all of which was in the resident HP Courier 12, *IPRINT* announced it couldn't find the font file and refused to print anything. Debugging proved difficult, first because it had displayed the font-file name as a string of object code characters (and then immediately covered up the screen with a menu), and second because of the lack

of an error or troubleshooting section in the *IPRINT* manual. The closest thing is a section of "commonly-asked questions" about *IPRINT*. None of these non sequiturs were of the form, "What do I do if it doesn't work?"

After some fiddling around and changing all of the text to a different font (a cartridge font), we got the same error message and the same non-performance. Upon further reflection, we removed all the specially accented international characters that *IPRINT* says it allows and tried again. This time we actually got output from the printer; unfortunately, the output consisted of a file dump of the iprint.cfg file rather than our document.

Curiously, when we created another form, we had no trouble printing it out, aside from the perplexing fact that both before and after it printed the form, it displayed the error message, "Printer not available (abort, retry, ignore?)."

Indigo product support was prompt and helpful and suggested the answer to the first printing problem. Our initial work was done on a PC's Limited 286 system driving a Tandy CGA monitor. We then brought over the predefined form to a Vectra ES that ran the LaserJet II. Subtle differences in the *IPRINT* configuration files caused the confusion.

Specifying "reset" before loading the form caused the form to match the new configuration. Our test form also uncovered two other problems. If part of the form slops over the border line that represents the edge of the printable part of the paper, by even as much as a single cell, trouble will result. This is a common problem with the LaserJet family, but the software ought to tell you. A trouble-shooting guide would be most helpful here.

Even after correcting these sundry subtle problems, the form still wouldn't print. Eventually, after visiting Indigo in person at a trade show, we determined that we had found an actual bug in the program.

One of the line types that IPRINT

## **Share Laser Printers**

Share any printer.

Laser, letter quality, plotter, dot matrix, even FAX.

Connect any PC/any application.

Even provides a 3287 link between your laser and a mainframe.

Set up is easy.

Reliable and familiar asynchronous connections plus Auto-Install to get you going quickly.

Popup menus for instant access.

Easy-to-understand, the popups let you access the full functionality of PrintDirector from within any application.

Printer Management.

Make printer use easier to manage and get better looking documents with printer feature selection libraries, font selection, collated copies, tray control, forms selection, resource utilization reporting, even use different types of printers with Printergration.

Call Digital Products today: 1-800-243-2333; in California: 1-800-247-2006.



Digital Products, Inc., 108 Water Street, Watertown, MA 02172 617-924-1680

PrintDirector is a trademark of Digital Products Inc.





ENTER 107 ON READER CARD

# INTRODUCING TSI WITH 2392 EMULATION SOFTWARE.

# AND A FULL LINE OF HP3000 UPGRADES.



4080 Woodcock Drive Jacksonville, FL 32207 904-396-7068

Offices in Atlanta, Boston, Chicago, Dallas, Denver, Los Angeles, Miami, New York, and Orlando.

**ENTER 139 ON READER CARD** 

#### Connect with TSI.

When you make the PC-HP3000® connection with TSI's new HPE3 software, you get more than the usual menu-driven 2392 emulation software.

You get the most versatile script processor in any emulation package. With testing and conditional branching. Day-, date- and time-related functions. Multiple and nested scripts. A processor that makes any and all DOS™ calls, provides automatic PC-to-host sessions, supports wildcard functions and provides PC file back-up based on update flags.

HPE3 features complete binary and ASCII file transfers, and macro keys in addition to HP softkeys and on-line help with user-definable functions.

You also get a real bargain. This powerful emulation package costs only \$195.00.

HPE3 is typical of the value you get from working with TSI. Typical of the value thousands of HP,® Prime,® Digital and Wang VS® users receive from our system upgrade packages, and from our commitment to responsive customer service.

In addition to emulation software, our products for the HP3000 include high density memory, communications, printers, and advanced disk and tape subsystems.

Whether you need a reliable and versatile PC-HP3000 link or performance enhancements for your 3000, you'll get the most for your upgrade dollar with TSI.

Connect with us. To order HPE3, call us at 800-222-3475 (in Florida, 800-421-4135), or complete and return the coupon.

☐ Check enclos	ed 🗆 Purcl	nase O	rder Number
Name			
Title			
Company			
Address			
City	St	ate	Zip
Telephone			

Copyright © 1988. TSI.

HP and HP3000 are registered trademarks of Hewlett-Packard Corporation.

DOS is a trademark of Microsoft Corp. Wang is a registered trademark of Wang
Laboratories, Inc. Prime is a registered trademark of Prime Computer, Inc.

supports is an arc, or part of a circle. You're allowed to specify the radius, and to rotate the arc an arbitrary number of degrees. However, if the arc is rotated to any position other than a right angle from the horizontal, the form will crash when you try to print it.

Indigo plans to correct this flaw in a future release; in the meantime, if you

restrict your arc rotation to 90-degree increments, and are careful not to have any piece of any object slopping over the edge of the "paper," you should have no trouble printing.

Once you've designed your form with IPRINT, you either can make a laser printer master for commercial printing, print forms on demand with your laser,

IPRINT Release 3 Indigo Software Ltd. Suite 400 560 Rochester Street Ottawa, Ontario K1S 5K2 ENTER 300 ON READER CARD


Runs on PC and compatible computers. Output to a variety of laser printers including: HP LaserJet family, Canon, AST Turbolaser, Xerox 4045, IBM 3812 and PostScript printers. It also supports other laser printers that emulate the LaserJet. Price \$350.

or do data entry and merging with two related products.

The IPROMPT package will compile your form into a screen-prompting data entry and data capture program. Running on a PC like the Vectra, anyone can fill out a form, press a key and print the data on a predefined form stored in a local laser printer. Data also can be written to a DOS text file for later importing into a PC-based database or other program.

The IMERGE packages allow data stored on HP 3000, HP 9000 (HP-UX) and DEC VAX computers to be merged with forms designed with IPRINT on a PC. Merging can occur as an overlay, where the current page image is superimposed on the form (operationally identical to pre-printed forms), or on a field basis. The latter offers more flexibility and direct dumping of field delimited databases.

All in all, IPRINT is a worthwhile program for anyone who can use custom designed forms. It can present vital information in a much clearer and less dense mode than a simple report or memo, in a standardized format for quick absorption. We found it easy to learn, despite the poor manual, and relatively bug-free. We would unhesitatingly recommend it to any small business that sends a lot of information up and down the chain. -Ashley Grayson is the founder of ADG, a high-technology marketing services organization based in San Pedro, CA. Dafydd ab Hugh is a member of the ADG technical staff.



#### **WANTED: Communications Wiring System**

#### Isn't it about time you hire the best!

The MOD-TAP Communications Wiring System is a modular solution for voice and data building wiring. MOD-TAP System is not biased towards any particular manufacturer's equipment or Local Area Networking scheme. MOD-TAP System is guaranteed to interconnect any compatible equipment utilizing twisted pair wiring.

**MOD-TAP System** 285 Ayer Road P.O. Box 706 Harvard, MA 01451 (617) 456-3500

MOD-TAP System UK Ltd. City Commerce Centre Marsh Lane Southampton Hants, S01 1EX. England 44 703 212120

ENTER 122 ON READER CARD

MOD-TAP. System Trademarks are the property of their respective owners.

Call today 1-800-252-1100/617-772-5630 for our new 1988 Applications Catalog

60

Most sales order management systems promise a great fit.



# If you happen to wear their size.


In sales order management, "great fit" means doing the job the way *you* do business—using *your* unique order types and *your* way of processing them. It also means adapting to your changing needs. And it means doing all of this without the time or cost of custom program development.

If you have unique requirements for export orders, consignment orders — any kind of order — Cardinal can automate them quickly and easily at a fraction of the cost of custom software development. No one else

can offer you this combination of exact fit and easy adaptability.

The secret: the Cardinal Configurator, an exclusive architecture that lets you specify, in detail, an unlimited number of order types and how each is processed. As your needs change, your systems can change with them — without programming.

So why settle for an inflexible order management system? Or spend a fortune on custom software development? Call Cardinal. And get the best of both worlds.



75 Second Avenue, Needham, MA 02194 • (617) 449-0066 Distributors: Los Angeles (714-554-1551) • Sydney (2-436-4022)

INTEGRATED SOFTWARE FOR: ORDER MANAGEMENT • PURCHASING • INVENTORY
• RECEIVABLES • PAYABLES • GENERAL LEDGER

ENTER 102 ON READER CARD



# ULTITASKING PERFORMANCE

Monitoring
Performance When
Running More Than
One Program On
The Integral

One feature that continues to set the HP Integral apart from most of the other personal computers popular today is its ability to run many programs simultaneously. This capability guarantees that you never have to wait for one program to finish before you can access any other information or program on your machine. This full-time availability undoubtedly will be a standard feature taken for granted in future PCs.

Multitasking opens up a new way to interact with your computer. A classic example is offered by the Integral demonstration program. In it, the user is writing a letter using an HP word processing program, Memo-Maker, and runs a calculator program to compute a figure needed in the letter being written. Since this easily could be accomplished in a single-tasking computer using a memoryresident program such as Sidekick (Borland International, Scotts Valley, CA), it presents a weak case for the virtues of multitasking. A more powerful example and one commonly used by Integral owners is running a communications program while running other programs concurrently.

With electronic information sources becoming commonplace, I frequently find myself using electronic mail, remote electronic databases and bulletin board systems. While my data communications program is busy at work downloading articles, programs, selected data records, etc., I can be found doing other frequently unrelated applications on my Integral. This greatly improves human efficiency!

Another time when multitasking is appreciated is during compilation of huge programs. Most programmers using compiled languages have experienced the frustration of waiting for a compile to finish before they could get their editing program to work on the next section's

documentation. (HP programmers document before they code, right?) This is a particularly good application of multitasking because editing tends to be limited by the programmer's typing speed. Therefore, very little of the computer's time is diverted away from the compiling in order to support user editing. Neither the compiling program nor the editing program is greatly degraded in speed by the other program's presence.

When more than one program is running, they share the computer's resources and even may compete for them. If no explicit arrangements are made, each program receives an equal amount of attention (time) from the computer. If two identical programs are running, each gets half of the computer's power and each takes twice as long to run than if it had the machine to itself.

There are many factors that affect this relationship, however. For example, while the editor (editing program) is waiting for the user to type in some text, the editor isn't actually running, so the compiler runs at nearly full speed.

There are programs (unlike our friendly editor in the compile/edit example) that don't "get out of the way" when they aren't doing anything. When several programs that use the computer heavily are running at the same time, the speed of all the programs running is greatly reduced. In order to get an idea of how heavily burdened the computer was, I wrote the BASIC program called Monitor shown in *Program 1*. (*Program 2* shows a slightly more elaborate version written in C.)

When run with no other actively running programs (PAM, the Personal Applications



Joe Bormel

62 HP PROFESSIONAL

Manager doesn't count as a running program), the Monitor prints the percentage of the computer it used during approximately the last second. Usually, this number is around 92 percent to 93 percent because of system overhead. When BASIC is run as a real-time program (using rtprio), it produces 100 percent. If two copies of the program are running, each reports seeing approximately half of the available machine.

MONITOR BECOMES VERY INTERESTING and useful when run in combination with other programs, because it tells you indirectly how much the other program is using the computer. For example, when running HP's Datacomm program, Monitor reports that it's getting to use half of the computer every second, even when the Datacomm program is just waiting for characters from the user or the modem.

In contrast, when using Kermit (a public domain datacomm program available as freeware and resident in the software engineering ROM) as the datacomm program, Monitor reports that it's getting to use all of the computer when the Kermit datacomm program is waiting for characters from either the user or modem. Because of

this aspect of HP's Datacomm program, I try to use Kermit whenever I need a datacomm program. (There are several other differences between these two programs that make it ideal to have them around.)

Another use of Monitor is testing the way other programs work. For example, running Monitor and time\_\_of\_\_day(1) shows that time\_\_of\_\_day doesn't use the computer during the minute in between updates. On the other hand, the BASIC WAIT statement does its wait by using the computer time during the wait, instead of sleeping and leaving the computer fully available to the other running programs. Thus, a BASIC program that displayed the time and WAITed for one minute would slow down significantly other programs running at the same time.

Using Monitor, you can access the load of each program running on your Integral and tune the performance of your applications to avoid unnecessary, unproductive and wasteful use of your multitasking computer. —Joe Bormel is a free-lance writer based in Columbia, MD.

Would you like to continue to see articles on this topic? Enter on reader card yes 342 no 341

## Program I.

BASIC Implementation of Monitor: The program is very simple and should be easy to translate to multitasking machines other than the Integral.

- 5 ! Monitor: program to monitor CPU utilization. See article text
- 6 ! for description of use. Written by Joe Bormel, 1/88.
- 10 ! save "/usr/Joe/basic/monitor" ! embedded save command
- 20 f=100/178 ! adjustment factor to normalize counts to 100%
- 30 ! CPU availability based on counts achieved in real time
- 40 start=TIME ! TIME is a function that returns system seconds
- 50 elapse=TIME-start
- 60 IF elapse>1 THEN 90
- 70 c=c+1
- 80 GOTO 50

Continued.

#### High Quality HP Computer Supplies At Low, Low Prices!

Stop paying more for your high quality HP computer supplies! All orders are shipped within 24 hours of your call, no minimum purchase required. Call for prices on a wide assortment of other supplies not listed in this ad.

#### Diskettes (10/bx)

Sony 3.5" SS	18.95
Sony 3.5" DS	27.95
Sony 5.25" MD-2DD DSDD (96 tpi)	24.95
Sony 5.25" MD-2HD DSHD	29.95

#### **Supplies**

3.5" Disc File Holder	15.95
5.25" Disc File Holder	19.95
Inkjet paper (500 sheets)	8.95
HP92261A Inkjet cartridges	8.95
HP10833B 2 meter HPIB cable	80.95
HP92205Y HPIB ABC Switch box	229.95

#### **Plotter Supplies**

Multi-Media plotter pens (4/pk)	3.95
Multi-Media plotter pens (5/pk)	4.75
Rollerball plotter pens (4/pk)	7.95
Disposable plotter pens (4/pk)	15.50
Premium gloss paper 8.5x11	4.95
Plotter bond paper 8.5x11	3.75

#### Memory Boards Series 9000 200/300

649.00
1249.00
2549.00
5419.00
1 1749.00

#### **Peripherals**

HP7475A 6 pen plotter, B size	Call for
HP2225A Thinkjet printer	prices

#### **Data Cartridges**

3MDC600HC 600' Data Cartridges	26.95
3MDC615HC 150' Data Cartridges	23.95
HP88140LC 600' Data Cartridges	37.00
HP88140SC 150' Data Cartridges	27.00

Questions? Talk to our friendly technical staff for help on all your HP supply needs. Visa and MasterCard accepted. \$2.00 shipping charge for orders under \$100.00. Call or write for school and government discounts.



**ENTER 138 ON READER CARD** 



#### Program I...continued

```
90 DISP USING "DDD" ; INT(c*f/elapse) ! display counts/second times f 100 c=0
```

### Program 2.

```
C Language Implementation of Monitor
```

This version of the Monitor program is portable to any machine with a C compiler running UNIX. Implementation on a non-UNIX multitasking machine requires changing the system time accessing functions. By setting the variable "factor" to one, a machine-specific value for factor may be obtained to yield 100 percent.

```
# include <stdio.h>
# include <time.h>
# include <sys/types.h>
# include <sys/times.h>
# define TICKS 60.
# define SIZE 60
long c,elapse,start,tc,telapse ;
long times();
static struct tms tbufl;
float factor =1.0;
int index,q ptr;
long count_history[SIZE], elapse_history[SIZE];
main()
       printf("Percentage of CPU available shown followed by a minute average.\n");
       start = times(&tbuf1) ;
       factor = 100 / 12.5
                                        /* factor has been chosen so that */
       /* real-time performance is 100%
       for(index=0; index < SIZE ; index++) {
    count_history[index] = 0;</pre>
             elapse_history[index] = 0;
       q_ptr = 0;
       while(1) (
             elapse = times(&tbuf1) - start;
             if (elapse >= TICKS) {
                        printf("%4.1f\t",(float) ( c * factor / elapse ) );
                         count_history[q_ptr]=c;
                         elapse_history[q_ptr]=elapse;
                         q_ptr++;
                         if (q_ptr>=SIZE) q_ptr=0; /* update circular que ptr*/
                         tc=o.
                         telapse=0:
                         for(index=o; index < SIZE ; index++) {</pre>
                                  tc += count_history[index]
                                  telapse += elapse_history[index];
                         printf("%4.1f\n", (float)
                                  tc * factor / telapse );
                         fflush(stdout):
                         start = times(&tbufl) :
       )
             /* end of while() */
```

#### SUPRTOOL



#### Why Fight with QUERY?

While within SUPRTOOL, you can switch to DBEDIT, a powerful and easy-to-use editor for database entries. DBEDIT allows you to add, list, modify, delete, and change individual dataset entries, and chains of entries.

Use the EDIT command and notice the new prompt (#).

>edit

Modify Critical Fields. QUERY does not allow you to modify search or sort fields -- you must delete and add the entry, re-typing all of the unchanged values without error. Instead, use the MODIFY command with UPDATEKEY.

#modify d-sales;updatekey
CUSTOMER-NO >

My Product Number Is Wrong. What if you want to change the key value of an entire group of details and their master? Use the CHANGE command.

CHANGE prompts you for a key value and a new, replacement, key value. It replaces the key value in the master and in all related detail entries.

Find Those Records. To review related entries, use LIST with RELATED.

#list m-customer; related
 CUSTOMER-NO >

This command prints a master entry and all detail entries with the same search value in all datasets that are linked to the master dataset by an explicit path. Or, it prints a specified detail entry, followed by the master entry of each search field in the detail.

SUPRTOOL is compatible with Turbo IMAGE. The license fee is \$3000, including one year of service. No charge for trial.

ROBELLE Consulting Ltd.

8648 Armstrong Road, R.R. #6 Langley, B.C. Canada V3A 4P9 Phone: (6O4) 888-3666 Telex: O4-352848

Australia 03.420.5400 England 01.262.5050 (x363) France 06.907.7079 Germany 07621 791101 Holland 4242.15655 South Africa 021.61.9001 Sweden 08.35.4666 Switzerland 031.46.1664

ENTER 127 ON READER CARD

# DS, LONG POINTERS AND C

Solving Portability
Problems With
Extended Data
Addressing

One well-known limit to HP 3000 architecture is the short addressing reach of its instructions. Born in a 16-bit world, the maximum amount of directly addressable memory any program on the 3000 may access is a little more than 31K words. To augment this address space, the MPE operating system offers extra data segments (XDS). Extra data segments are, effectively, memory disc drives. The user may allocate extra data segments and then transfer blocks of data to and from the XDS.

Doing this causes two problems. First, source code either must be designed to use XDS or it must be modified. With few exceptions, compilers on the 3000 don't support the XDS concept other than to give programmers access to XDS intrinsics. The amount of work necessary to change an existing program to use extra data segments can be profound, depending on the program's logic and basic design.

The second XDS problem is portability. For example, if you develop a program under MPE making use of extra data segments, you must change the program again if you move to an IBM PC. Like the 3000, the PC has its own memory size problems, but the solutions provided are quite different from those found on the 3000. Likewise, if you want to port to HP's Precision Architecture (PA) computers running HP-UX, you have a different set of problems. Because the PA computers are 32-bit, there's no need for trick memory management. All the memory you've ever wanted is waiting to be directly accessed, so all XDS code should be removed when porting to PA machines.

These problems become more apparent when using C because its portable nature tends to cause programmers to want to port existing

code. It's not unreasonable to want to develop a C program that will be targeted to run on PCs, HP 3000s, 1000s and PA machines, all without source-code changes.

At Corporate Computer Systems, we faced this challenge in the design of our C compiler for the HP 3000. How would we efficiently integrate the concept of extra data segments and yet remain portable to machines that do not have the same capability? To meet this requirement, CCS borrowed from existing C implementations. Ideas were taken from both PC versions of C and from HP's C for the 800/900 Series computers. The result is what CCS calls eXtended Data Addressing (XDA).

The basic concept behind XDA is the addition of a *long pointer* type to the C language. The HP 3000's natural pointer size is 16 bits, but long pointers provide the programmer with an additional type of pointer 32 bits long. With 32 bits, the C compiler has a way to access direct memory as well as any extended memory the host computer may support.

Because there's a time penalty for using 32-bit pointers, you're allowed to mix 16- and 32-bit pointers freely. If a 32-bit pointer is appropriate, then one may be used. If you don't need a 32-bit pointer, then the compiler won't automatically force you to use one. You can make the basic space-versus-speed design trade-off by choosing the correct pointer type at any given time.

Although new to the 3000, this technique is old and time-tested. For example, Microsoft's QuickC and 5.0 compilers provide this feature with their *far pointer* concept. HP's PA machines have long pointers that provide 64 bits of addressing reach.

Because of their extra size, CCS/C long pointers have the ability to point to any word or byte in any data segment. When a program



PRECISION ARCHITECTURE

Tim Chase

is operating in privileged mode, this includes even system data segments.

Once set to point to a location within an extra data segment, a long pointer may be "dereferenced" using the same source syntax as would be used for any normal (16-bit) pointer. The dereference operation in the case of a long pointer, however, causes an extra data segment reference. Depending on the use of the pointer, the data segment reference either can get information from the data segment or store information to the data segment.

When programming in C, extra data segments may be allocated two ways. The net result of each method is that a long pointer is set to point to a location in an extra data segment. As a degenerate case, long pointers also may be used to point to data objects that are in your local stack space. Thus, long pointers make all storage (XDS or process stack) appear homogeneous. Data structures, therefore, may span several different extra data segments.

The two ways to allocate extra data segments referenced by long pointers are:

■ Calls to the GETDSEG intrinsic

This is the normal way to allocate extra data segments on the 3000. The resulting extra data segment number is passed to a CCS/C library routine named "to\_long", which converts

it into a long pointer to the first location of the extra data segment. This pointer may be adjusted to point to any location within the XDS simply by adding an offset to it. Using this technique results in noncontiguous extra data segment address spaces. This means that the largest data structure that can reside in an XDS will be limited by the size of the largest XDS that the system can allocate. For all practical purposes, this is about 31,000 decimal words.

Calls to ()

A special heap management routine called "emalloc" is provided in the C library. This routine will allocate extra data segments and treat them as an extended heap space, meaning that if you were to request 1,000 words from emalloc, an extra data segment would be allocated, 1,000 words would be taken from it and the remaining storage would be kept pending another call to emalloc. The companion routine "efree" deallocates blocks allocated by emalloc. Calls to emalloc may or may not generate calls to GETDSEG, depending on whether or not emalloc has any "free" extra data segment room to allocate.

One important feature of emalloc is that it's able to allocate blocks of space that are larger than the largest extra data segment allowable in the system. This is done by allocating multiple extra data segments and managing them



© 1988 MARTINSOUND INC.

"American Built Quality and Service Since 1971"

Martinsound Technologies

1151 West Valley Boulevard, Alhambra, CA 91803-2493 FAX: 818-284-3092

**ENTER 129 ON READER CARD** 

# Spectrum in sight?

Adager began shipping Spectrum-compatible software in August 1987. This new version of Adager works on ANY HP3000 computer running IMAGE/3000 or TurboIMAGE under MPE or MPE-XL.



# Be sure to have Adager on site.

The only difference is performance: Adager really flies on Spectrum! For example, the BARUG Shootout Benchmark (which Adager runs in 2 hours 29 minutes on a Series 42) takes 29 minutes on a Series 950.

## Program I.

```
struct S (
   int type;
   char buf[100];
   float value:
struct S ^b;
                             /* used as an XDS "array" */
                             /* local structure */
struct S loc;
/* Allocate array of 10 XDS "S" type structures */
b = (struct S ^)emalloc(sizeof(struct S) * 10L);
/* copy i-th structure locally to work on it */
                            /* same as DMOVEIN call */
loc = b[i];
loc.type = 0;
                            /* reference locally */
strcpy(loc.buf, " ");
/* now move back to XDS */
b[i] = loc;
                             /* same as DMOVOUT call */
```

as a unit. Each extra data segment allocated by emalloc is 16,384 words in length.

For example, you may call emalloc and pass a request for a block with 50,000 words in it. Emalloc automatically will allocate four extra data segments, each 16K words in length. The long pointer scheme is designed so that the 50,000-word block will appear to be contiguous rather than broken up into four different extra data segments.

Another important use for long pointers is to access system tables. Although clearly not for all programmers, CCS/C's long pointer makes system tables much easier to access correctly. Using C, you're much less apt to make dangerous mistakes when getting information from system tables. As with SPL, however, the C program must be executing in privileged mode in order to gain access to system tables.

Most system tables actually are collections of well-defined structures. Accessing them from C provides a way to formalize the structures and then treat the table as arrays of the structures pointed at by long pointers.

#### **Using Long Pointers**

The CCS/C long pointer declaration syntax was selected to minimize the impact on existing source code and to maximize compatibility with other compilers on different host computers. The only difference in syntax associated with long pointers is that used during their declarations.

In order to achieve compatibility with various implementations, CCS/C supports both the far pointer syntax found on PCs and the special A syntax found on the HP and C Precision Architecture compilers. The far keyword is used as a

modifier to the  $\star$  character during pointer declarations, while the  $\wedge$  character is used instead of the  $\star$  character.

The far keyword or the  $\land$  character is used only for the declaration of pointers or for casts involving those pointer types. All pointer dereferencing is done with the \* and -> operators, so only pointer declarations need to be changed when altering an existing program to use long pointers. All code that references the pointers remains the same.

For example, the declaration of a long pointer to an integer is either:

```
int ∧ p;
```

or:

```
int far *p;
```

The same declaration with a short pointer would be:

```
int *p;
```

Once a long pointer contains a value, it may be used like a short pointer. For example, to store a value of 12 into the extra data segment pointed to by the long pointer "p", we would write:

```
*p = 12;
```

Long pointers may be declared to point to any type of object except functions. A long pointer to a character string would be declared as:

```
char ∧ cp;
```

or:

```
char far *cp;
```

and a long pointer to a (previously defined) structure tagged as S would be:

```
struct S \land sp;
```

or:

```
struct S far *sp;
```

Likewise, dereferencing these pointers is performed in the same way as with 16-bit pointers:

```
*cp = ' ';
sp->field = 0;
```

Because standard C defines all pointers to behave much

70 HP PROFESSIONAL

# 



"Collier-Jackson's integrated payroll/personnel data system was phased in during the year. It substantially upgrades the reporting and payroll processing capabilities while saving \$400,000 annually. This state-of-the-art system appears to be the best on Wall Street."

— Kidder, Peabody Group, Inc. 1986 Annual Report

When Kidder, Peabody went looking for an interactive payroll/personnel combination, they took stock of what was on the market, then invested in Collier-Jackson.

Who better to handle the payroll/personnel requirements of more than 7,500 employees (and 3-4,000

applicants annually) than management systems designed to work together to better work for you.

Systems backed by a nationally acclaimed software firm with all the support and services that status implies. A positive profile earned by providing human resource systems that keep pace and outdistance others. Products adaptable by design to keep you on top — no matter how many changes to taxes, deductions and company-paid benefits are on the horizon.

If you're looking for payroll and personnel systems, look to Collier-Jackson. They're

part of a comprehensive business system that integrates financial and human resource information. So, your payroll can be automatically passed to the G/L during processing — providing current, comprehensive information for timely reporting.



Collier-Jackson, Inc. a CompuServe Company

3707 West Cherry Street Tampa, FL 33607 (813) 872-9990 the same as arrays, pointers (both normal and long) may be indexed. In C, the pointer expressing p[i] is defined to be identically equivalent to  $\star((p) + (i))$  for any pointer expression p and any integral expression i. Because of this, long pointers pointing to extra data segments can behave as if they were arrays of objects. This is the normal way that long pointers are used. For example, to allocate an array of 10,000 integers and clear it all to zero, we'd write:

```
#include < stdlib.h >
                /* define the array base as a pointer */
int Aa;
a = (int \land )emalloc(10000L); /* allocate the space */
for(i = ); i < 10000; + + i)
                                /* clear to 0 */
    a[i] = 0;
```

A slightly more efficient way to use long pointers on the 3000, yet remain portable, is to store structures in XDS and then move structures to local memory to reference individual members. Although not necessary (individual members may be referenced directly in XDS), moving a structure locally does improve the access efficiency for individual members. In fact, moving an XDS structure to local storage is the C equivalent of the MPE intrinsic DMOVEIN. Program 1 is an example of this technique.

With long pointers, programmers have control over the speed/complexity trade-off. If you wish, you may access individual words in extra data segments just as if they were in local memory. This reduces program complexity, but increases execution time. On the other hand, you may elect to optimize code so that it's more complex (as in the previous structure example), but runs faster.

Long pointers provide an interesting alternative to calling extra data segment intrinsics directly. They enable the concept of the extra data segment to be directly incorporated into the memory model supported by ANSI standard C, yet because of their near-universal acceptance on other host machines, long pointers are quite portable.

Although sometimes not required for smaller projects, long pointers need to be considered seriously by anyone embarking on sophisticated software development where portability and large memory requirements will be issues. —Tim Chase is the project manager for Corporate Computer Systems Inc.'s C compiler on the MPE V and HP 1000 systems, as well as co-owner of the firm which is based in Holmdel, NJ.

> Would you like to continue to see articles on this topic? Enter on reader card yes 340 no 339



The Ninth Annual Eastern American HP Users Conference will be held Tuesday evening, May 31 through Friday noon, June 3, 1988 at the TRUMP PLAZA Hotel/Casino on the Boardwalk in Atlantic City, N.J.

Hosted and organized by the Northeast Central HP Regional Users Group, Inc., the conference will feature: a keynote speaker, quality technical presentations and roundtables, exhibits by more than 40 vendors, and many opportunities for information exchange with fellow professional users. A range of beginner to expert level tutorials will be held on Wednesday, June 1, 1988, on such key topics as: PC's IN THE 3000 ENVIRONMENT, DATA COMMUNICATIONS, SYSTEM MANAGEMENT/SECURITY and PERFORMANCE. Technical and managerial presentations will be held on Thursday and Friday, June 2-3, 1988.

The all inclusive fee is just \$300 if paid by April 29, 1988 or \$340 thereafter. For NECRUG members, deduct \$25. This fee also includes: valet parking, three breakfasts, two luncheons and evening receptions, and all coffee breaks. Bradmark Computer Systems, Inc. of Houston, Texas will be hosting the kick-off reception on Tuesday evening, May 31. Conference sessions are preapproved for recertification through ICCP.

Don't miss this challenging and rewarding experience.


Please make your TRUMP PLAZA reservation directly by dialing 800-441-0909. The special conference rate is \$85/night for single/double occupancy. Register early by May 3 to guarantee a room at this rate.

For more information call **NECRUG** c/o Jeri Fuller at 215-825-4666.

See you in ATLANTIC CITY at the NECRUG East Coast Conference this spring; THE East Coast Conference you should not miss.

I will attend the Eastern American HP Users Conference

on May 31 - June 3, 1988.	
Name	
Company	
Address	
City/State/Zip	
Phone No./Extension	
I have booked my room at t	the TRUMP PLAZA for:
Monday Tuesday Wedne	esday Thursday Friday
Enclose check payable to:	Mail to:
NECRUG for	NECRUG
\$300 before April 29th	c/o Jeri Fuller
\$340 thereafter	U.S. Mortgage Insurance Co.
less \$25.00 for	P.O. Box 190
NECRUG members	Blue Bell, PA 19422



# SPECTRUM NEWS

**HP PRO Staff** 

# New Systems Unveiled

Earlier this month, HP introduced seven new computer

models based on its Precision Architecture (HP-PA) design, including the highest performing systems in the company's history.

As in the past, HP compared the aggressively priced models with similar systems from IBM, Digital Equipment Corporation and others.

The new models, which extend both the HP 3000 and HP 9000 lines, include:

- mid-range HP 3000 Series 925 (\$80,000), 925LX (\$50,000) and 935 (\$150,000) systems,
- a high-end HP 3000 Series 955 system (\$390,000),
- mid-range HP 9000 Model 835S (\$45,000) and 835SE (\$99,000) systems, and
- a high-end HP 9000 Model 855S (\$320,000) system.

Also introduced were two entry-level HP 3000 business computers — the Micro 3000LX (\$10,900) and Micro 3000GX (\$15,950).

The HP 3000 Series 955 is the highest performing commercial system ever introduced by HP, providing 50 percent more performance than the previous high-end system — the Series 950 computer (which remains in the product family).

The Series 955 is capable of supporting more than 400 users and provides mainframe-class performance comparable to high-end IBM 4381 systems and large DEC VAX systems at half the price. Like all of the new HP-PA systems, it uses a single-chip central-processing unit based on proprietary NMOS III VLSI (very-large-scale-integration) technology. This technology enables all of the processing power to be deployed on a single printed-

circuit board, resulting in higher reliability and lower maintenance costs.

HP can increase the performance of any installed Series 950 to that of a Series 955 by exchanging the processor board at the customer's site. Increases in performance do not require customers to purchase entirely new systems. The Series 955 will be available in the first half of 1989.

At the mid-range, the Series 925 can support as many as 152 users and is comparable in performance to a DEC VAX 8530 at one-third the price and provides more performance than the IBM 9375-60 at about half the price. The Series 925LX has the same performance as the Series 925 at a lower price for configurations of up to 32 users. The Series 925 and 925LX are available immediately.

The Series 935, which supports as many as 240 users, provides up to twice the performance of a Series 925 and about 85 percent of the performance of the Series 950. The system also provides more performance than the DEC VAX 8550 at one-third the price and more performance than the IBM 9377-90 at about half the price.

The Series 935 replaces the first HP 3000 based on HP-PA (Series 930), with about 30 percent more performance at a 17 percent lower price. It will be available later this year.

At the low end are the HP Micro 3000 LX and Micro 3000GX which are based on traditional HP 3000 architecture. The Micro 3000LX reduces the price of an entry-level HP 3000 to \$10,950, half the price of the previous low-end system. Both systems are targeted toward small businesses, branch offices and small departments. These low-end systems are available immediately.

The HP 9000 Model 835S and

Model 835SE are the new mid-range members of the HP-UX family. They will be available this summer.

The Model 835S is well-suited for computationally intensive tasks or multiuser environments with up to 30 users. The Model 835SE is targeted for commercial and technical applications requiring larger configurations — up to 70 users — such as software development and office work groups.

The Model 835 systems include a new subsystem that offers 2.02 double-precision MFLOPS of floating-point performance. Using this measure, the Model 835S is four times faster than a DEC MICROVAX 3600 at a lower price and 75 percent faster than a Sun 4/260 at a comparable price. The Model 835SE exceeds the performance of a VAX 8550 and 8700 at less than one-third the price.

Graphics workstation versions of the Model 835 were introduced in March. They include the 2.02-MFLOP superworkstation, the Model 835 TurboSRX (see "The New 350/835 TurboSRX," by Andy Barlow, p. 46, this issue).

The Model 855S, which will be available in the first half of next year, becomes the new performance leader of all HP computers that run the HP-UX operating system. It offers more than 50 percent more performance than the current high-end system, the Model 850S.

In addition to the new systems, HP also introduced two new enhancements to the HP 9000 Model 850S: a new field-installable floating-point upgrade that doubles the unit's floating-point performance, and a terminal expander that triples its terminal connectivity.

HP also introduced the HP-FL fiber-optic disc interface for HP-PA systems.



#### DEVELOPMENT

#### Lisa Burns Hartman

# TurbolMAGE Logging

Unless you're a data center manager, you may not have

had this particular nightmare:

It's 3:00 p.m. the last day of the month, quarter and fiscal year. Your operator comes running into your office. He's in a state of panic. "The Sales machine is down! The entire Order Processing Department is screaming!" he shouts. You're not too worried, since you always can RESTORE last night's DBSTORE of the Order Processing database. But just then, the Order Processing data entry manager storms into your office. "What do you mean, reenter my data?" he says. "Are you crazy? We booked half a million dollars worth of business today. My people go home in an hour, and we still have stacks of P.O.'s to book!" he says. "Oh boy," you think, "the entire company needs that data." This could be a long night for Order Processing.

Sure, HP hardware is extremely reliable. However, failures do occur. Moreover, lightning storms, floods, fires and even plane crashes can endanger data centers and valuable hours of work. Re-entry of transactions after a RESTORE from the previous day is time-consuming and expensive. Also, if the data source is a phone call rather than a printed purchase order, re-entering the data may not even be possible. Reliable hardware alone is not enough to protect your users.

TurboIMAGE provides excellent data insurance with database transaction logging. With logging, transactions are written to a log file as well as to the database itself. The log file then can be reapplied to last night's DBSTORE, bringing the old copy of the database

eliable hardware alone is not enough to protect your users. TurboIMAGE provides excellent data insurance with database transaction logging.

back up to date (see *Figure 1*). No reentry of data is necessary — happy users, happy data center staff. Here I'll describe TurboIMAGE logging, the different types of database recovery with logging, and offer suggestions on how to implement logging within your own shop.

TurboIMAGE logging, when enabled for a given database, captures database changes in a sequential file which then can be used to recover from a system failure. This file is called the log file for the database. The log file contains data from any intrinsic that changes the contents of the database. This means that when a program calls the DBPUT intrinsic, TurboIMAGE will write the buffer for the DBPUT to both the database and to the log file.

Similarly, data for DBOPEN, DBUP-DATE, DBCLOSE, DBDELETE, DBBEGIN, DBEND and DBMEMO intrinsics also will be written to the log file. Execution of a DBGET or DBFIND intrinsic, however, will not update the log file, since these intrinsics do not alter the contents of the database. When the time comes that a recovery is necessary, the log file can be used to recapture work done after a DBSTORE of the database was taken.

### **Physical Integrity**

To completely ensure that the database is consistent following a recovery, how-

ever, Intrinsic Level Recovery (ILR) is necessary. Remember that if your database contains any Automatic Master sets, a DBPUT intrinsic call within your program to add to the detail actually will cause a record to be added to both the detail and the Automatic Master set. In this case, TurboIMAGE logging needs to know whether or not the second add was completed before the system came down. The ILR file on disc contains a flag indicating the success of the second add. Thus, with ILR enabled, broken chains are prevented, since an entry in a detail set always will have an entry in the corresponding master set.

Similarly, if a DBDELETE intrinsic is called within your program, a delete to a detail set will cause a record to be deleted from both the detail and the associated Automatic Master. Again, TurboIMAGE logging will check the ILR file to see whether or not the second delete was completed before the crash. Physical integrity is ensured with ILR.

#### **Logical Integrity**

But wait — what about details associated with Manual Master sets? ILR won't help us here. Applications programmers need to ensure that a database is logically intact. Only they know that adding a new order to the database

# Two ways to solve your system backup problem: BackPack™ ... and BackPack!



BackPack offers two ways to lighten the burden backup places on data center operations. First, you can take the 'traditional' approach, simply substituting BackPack for HP STORE in your job streams. BackPack cuts backup time by 35-50% on most systems, and halves tape usage as well. What's more, by incorporating DBSTORE into daily backup, BackPack eliminates the need to backup each database separately — an additional time and tape savings for IMAGE users.

A second alternative is to institute unattended backup procedures. In BackPack's "operatorless" mode, you start the store, mount a tape, and leave. BackPack fills the first reel, stores remaining data in compressed format to disc, and resets all store bits. In the morning, you copy the data to tape concurrent with normal system usage. For an unattended full dump, you need one-third of your total disc space free. With less space, you can probably still do daily backups unattended and full dumps partly unattended.

With versatile options like these, BackPack solves just about any HP 3000 backup problem. Why not put BackPack to work for you?

BackPack. From Tymlabs.



means that five DBPUTs and one DBUP-DATE must be executed in order to add a complete new accounting entry to the database.

This is where the intrinsics DBBEGIN and DBEND become important. By bracketing a complete transaction with DBBEGIN and DBEND intrinsics, the programmer can ensure that TurboIMAGE logging maintains the relationship between Manual Master sets and their associated details, and between different detail sets. Logical database integrity is ensured through DBBEGIN and DBEND intrinsic use.


Now we know how to preserve the integrity, both physical and logical, of our precious database. How do we go about saving the data entered by our poor friends in Order Processing? Assuming we already have enabled our database for logging, ILR and Roll-Back Recovery, we have a lot of options.


#### **Roll-Back Recovery**

If the system crash we just experienced was caused by a "soft" failure, we may be able to recover the database using Roll-Back Recovery. This recovery method, new with Turbo, allows us to

return our database to a physically and logically consistent state without the need for a DBRESTORE and reapplication of log files. Once the machine has been WARMSTARTed successfully, the Roll-Back Recovery process examines the last transaction in the TurboIMAGE log file and backs out the results of an incomplete multiset transaction. Figures 1a and 1b illustrate this process.

Enabling a database for Roll-Back Recovery requires ILR. This is so that if the last intrinsic written to the log file was a DBPUT or DBDELETE to a detail





```
!JOB LOGONID.ADMIN/ADMPASS.MAS/MASPASS.OMSDTA/DTAPASS
! COMMENT
               OMSZLOGJ - OMSZLOGJ is used to setup an existing OMS database for IMAGE logging.
! COMMENT
! COMMENT
! COMMENT
            The OMS log identifier is acquired for the log file.
The logid and flags are set in the data base for the
            OMS backup.
The OMS database is backed-up.
The log file is built.
! COMMENT
! COMMENT
! COMMENT
            Flags in the database are set for logging.
! COMMENT
!COMMENT +------
         STEP 10 - SETUP EXISTING OMS DATA BASE FOR IMAGE
! COMMENT
! COMMENT
                        LOGGING
!GETLOG OMSLOG; PASS-OMS; LOG-OMSLG001, DISC; AUTO !COMMENT +---
! COMMENT
! COMMENT
LCOMMENT
              STEP 20 - SET LOGID INTO DATA BASE
! COMMENT +---
IRIN DRUTTI PUR SYS
SET OMS LOGID-OMSLOG
COMMENT +----
1 COMMENT
            STEP 30 - SET USER FLAGS PRIOR TO BACKUP OF DATA BASE
! COMMENT
LCOMMENT
DISABLE OMS FOR ACCESS
ENABLE OMS FOR RECOVERY
ENABLE OMS FOR LOGGING
ENABLE OMS FOR ROLLBACK
! COMMENT |
              STEP 40 - "DBSTORE" OMS DATABASE
! COMMENT
!TELL ADMIN.MAS | OMSZLOGJ - STEP 40 | !TELL ADMIN.MAS |----+
```

```
ITELL ADMIN MAS
                    TAPE MOUNT FOR "OMS"
                    PLEASE MOUNT A SCRATCH TAPE
!TELL ADMIN.MAS
!TELL ADMIN.MAS
                   This step will perform a DBSTORE of the OMS Turbo IMAGE data base.
!TELL ADMIN.MAS
!TELL ADMIN.MAS
!TELL ADMIN.MAS
ITELL ADMIN MAS
FILE DBSTORE-OMSDB; DEV-TAPE
RUN DBSTORE PUB SYS
OMS
! COMMENT +----
COMMENT
              STEP 50 - BUILD NEW CURRENT LOG FILE
! COMMENT
BUILD OMSLGOO1: CODE=LOG: DISC=10000 32 1
! COMMENT
LCOMMENT
              STEP60 - START IMAGE LOGGING FOR OMS
! COMMENT
TELLOP
! TELLOP
TELLOP
          NOTE: OPERATOR ACTION REQUIRED!
!TELLOP
!TELLOP
          Please start IMAGE logging for
          OMS by typing the following
! TELLOP
              : LOG OMSLOG, START
!TELLOP
ITELLOP
! COMMENT +-----
! COMMENT |
            STEP70 - RESET OMS DATABASE FOR ACCESS AND DISALLOW
! COMMENT
                        RECOVERY.
! COMMENT
!RUN DBUTIL.PUB.SYS
DISABLE OMS FOR RECOVERY
!TELL ADMIN.MAS: OMS LOGGING AND DBSTORE HAS COMPLETED
```

set with an associated Automatic Master, Roll-Back Recovery can check the ILR file to see if both parts of the transaction must be removed, or if only one was completed before the failure. For this reason, enabling a database for Roll-Back Recovery will enable ILR automatically as well. In this way, TurboIMAGE logging can ensure both logical and physical data integrity.

Because it eliminates the need for a DBRESTORE and the reapplication of log files, Roll-Back Recovery is very fast. Users can be back online in as little as five minutes. This makes it an extremely attractive recovery method.

#### **Roll-Forward Recovery**

If the system crash we just experienced is due to a hardware problem, especially

a disc problem, we may not be able to recover using Roll-Back. A "hard" failure forces us to use the Roll-Forward Recovery method. We begin with a DBRESTORE of the last available DBSTORE tape. Then, one or more log files are applied to the database. Roll-Forward Recovery will apply only complete transactions to the database. This means that no part of an incomplete logical transaction (bracketed by DBBEGIN and DBEND intrinsics) will be applied to the database, as shown in Figures 2a and 2b. Logical integrity is maintained.

The use of Roll-Forward Recovery with TurboIMAGE logging doesn't require the use of ILR. However, ILR provides additional protection and its use is recommended, especially if DBBEGIN and DBEND calls are not provided in the application programs. If ILR is enabled,

and the last intrinsic written to the log file was a DBPUT or DBDELETE to a detail set with an associated Automatic Master set, Roll-Forward Recovery will check the ILR file to see if both parts of the transaction were completed. If not, neither part will be applied. Again, logical and physical data integrity are maintained.

Because of the need for a tape mount and a DBRESTORE, Roll-Forward Recovery is certainly more time-consuming than Roll-Back. However, it's the only choice in the case of a hard crash. Also, it's certainly faster than having our poor Order Processing friends re-enter their data. Depending on how many transactions have been processed against the database, users

# professional press publications

Professional Press launched the DEC-specific publishing industry in 1979 with the publication of its first DEC magazine RSTS PROFESSIONAL.

Today Professional Press offers two DEC-oriented publications and a third, geared to the Hewlett-Packard marketplace. Plus two important texts for computing pros who want to learn about C language and VAX/VMS.



#### HP PROFESSIONAL

A monthly magazine written for professional users and managers of Hewlett-Packard's business/commercial and technical computer systems. With 30,220 buyer-qualified subscribers\*, it offers by far the largest and most clearly targeted circulation in its marketplace.

#### DEC PROFESSIONAL

The largest circulation DEC publication in existence - 100% buyer qualified\*\* and dedicated to improving staff and equipment performance at DEC installations.

**VAX PROFESSIONAL—The Software Journal for VMS** This bimonthly publication is the only technical journal dedicated solely to the users of VAX/VMS. It's the source of practical advice on how to write better software and make better use of the hardware on every VAX system — from the MicroVAX to the 8800.

#### INTRODUCTION TO VAX/VMS, SECOND EDITION


This revised and expanded self-teaching text explains and illustrates how to use VAX/VMS systems. Easy to learn for the computing novice . . . an excellent reference for VAX/VMS pros. Covers the basics and teaches systems and programming as well, plus glossary and appendices. Authors: David Bynon and Terry Shannon.

#### LET'S C NOW

A complete guide to learning C language in two volumes. Over 300 pages in 26 chapters in a selfinstructing workbook format. All the information needed to become proficient in C. Plus chapter summaries, glossary, and author Rex Jaeschke's hints and suggestions.



\*HP Professional, December 1987 BPA Publisher's Statement. \*\*DEC Professional, December 1987 BPA Publisher's Statement.



## When Every Order is Different...

You Need Hands-On Control Of Job Planning And Costing.

If your company manufactures made-to-order products or provides services on a contract basis, you're in the order-driven business. Which means you need a management information system to schedule work and track costs for each order. The problem is finding a software package to handle the job.

Virtually every software package on the market today is driven by sales forecasts and inventory requirements. Which is fine for large-volume manufacturers of standard goods, but inadequate for the order-driven business.

So we developed JOBSCOPE—software that gives you hands-on control of job planning and costing. JOBSCOPE is the software standard for manufacturers and service companies that operate on an order-by-order basis.

Using JOBSCOPE with a Hewlett-Packard HP 3000 system, you can ensure accurate estimates and work scheduling, efficient manufacturing, and delivery of services. JOBSCOPE permits constant cost updates and materials tracking, from initial bidding to final delivery—all in one easy-to-operate system.

For more information on JOBSCOPE and how it can address your management information requirements, call 1-800-443-5794, or write to JOBSCOPE, 555 N. Pleasantburg Dr., Suite 214, Greenville, SC 29607. We'll show you why an off-the-shelf software package is perfect for your business.



The Software Standard for the Order-Driven Business

See us at AMS '88, Booth #1344

**ENTER 120 ON READER CARD** 

	FIGURE	
OMSRECVJ,ADMIN/ADMPASS.MAS/MASPASS,OMSDTA/DTAPASS	PUN DBRECOV. PUB. SYS RECOVER OMS	
MENT	RUN	
MENT   OMSRECVJ - OMSRECVJ is used to restore the OMS	!COMMENT +	
MENT   database and apply the pending	!COMMENT	
MENT   transactions from the log file	!COMMENT   STEP 50 - "DBSTORE" OMS DATABASE	
MENT   to bring the OMS database back	!COMMENT	
MENT   to a current status.	!COMMENT ++	
MMENT   The log process for OMSLOG Id is stopped and flags	!TELLOP   OMSRECVJ - STEP 50   TAPE MOUNT FOR "OMS"	
MENT   in the data base appropriately set for recovery. The	!TELLOP  + PLEASE MOUNT A SCRATCH TAPE	
MENT   OMS database is then restored and the pending	!TELLOP	
MENT   transactions applied from the IMAGE log files.	!TELLOP   This step will perform a DBSTORE of the	
MENT   A new log file is created, after which the log process   MENT   is started.	!TELLOP   OMS IMAGE database.	
MENT   18 Started.	!TELLOP	
MENT	!FILE DBSTORE=OMSDB; DEV=TAPE	
IMENT .	!RUN DBSTORE.PUB.SYS	
MENT ++	OMS	
MENT   STEP 10 - STOP IMAGE LOGGING FOR OMS	!COMMENT	
MENT   STEP 10 - STOP TRAGE LOGGING FOR ONS	!COMMENT   STEP 60 - PURGE OLDEST GENERATION OF LOG FILES AND	
MENT +	COMMENT   BUILD NEW CURRENT LOG FILE	
LOP ++	! COMMENT	
LOP   OMSRECVJ - STEP 10	!COMMENT +	
LOP	PURGE OMSLOG3D	
LOP   Please stop IMAGE logging for OMS by typing	!RENAME OMSLOG2D,OMSLOG3D !RENAME OMSLG001,OMSLOG2D	
LOP   in the following command:	BUILD OMSLGOO1; CODE-LOG; DISC-10000, 32,1	
LOP	!COMMENT +	
LOP   :LOG OMSLOG,STOP	! COMMENT	
LOP	!COMMENT   STEP 70 - ENABLE OMS FOR ACCESS AND DISABLE OMS FOR	
MENT	COMMENT   RECOVERY TO ALLOW USERS TO ACCESS   COMMENT   THE DATABASE, LOG TRANSACTIONS, AND NOT	
MENT +	!COMMENT   ALLOW RECOVERY.	
MENT	COMMENT	
MENT   STEP 20 - "PURGE" OMS DATABASE	!COMMENT +	
MENT	!RUN DBUTIL.PUB.SYS	
DBUTIL. PUB. SYS	ENABLE OMS FOR ACCESS DISABLE OMS FOR RECOVERY	
E OMS	EXIT	
	!COMMENT +	
MENT +	!COMMENT	
MENT   CTER 20 DECTORE ONE DATA BACE	COMMENT   STEP 80 - START IMAGE LOGGING FOR OMS	
MENT   STEP 30 - RESTORE OMS DATA BASE	!COMMENT	
MENT +		
LOP ++	!TELLOP ++ !TELLOP   OMSRECVJ - STEP 80	
LOP   OMSRECVJ - STEP 30   TAPE MOUNT FOR "OMS"	!TELLOP   OMSREOVS - SIEP 80	
LOP  + PLEASE MOUNT LAST OMS	!TELLOP	
LOP   DATABASE BACKUP TAPE	!TELLOP   Please start IMAGE logging for OMS by typing	
LOP	!TELLOP   in the following command:	
LOP   DBRESTOR OF OMS data base	!TELLOP	
LOP +	!TELLOP   :LOG OMSLOG,START   !TELLOP	
LE DBRESTOR-OMSDB; DEV-TAPE	!TELLOP +	
DBRESTOR.PUB.SYS	!TELLOP +	
ALENIA .	!TELLOP   OMSRECVJ - NORMAL COMPLETION	
MENT ++	!TELLOP +	
	! EOJ	
MMENT   STEP 40 - RUN DBRECOV		

should be back online within 45 minutes or less.

So, you say, sounds great, but what is the cost of this data insurance? Well, nothing is free, but TurboIMAGE logging is very cheap. Long gone are the days when enabling a database for logging caused significant performance problems. I would challenge a user to notice any performance difference today between a database enabled for ILR and TurboIMAGE logging and a database without it. However, there are some

things to be aware of with logging:

First, databases must be enabled for logging. For maximum flexibility — to allow both Roll-Forward and Roll-Back Recovery — databases should be enabled for ILR and for Roll-Back. Jobstreams to enable these capabilities can be supplied by the application teams. Figure 3 is an example of a jobstream to enable a database for Roll-Forward and Roll-Back Recovery. Note that since Roll-Back Recovery is enabled, ILR will be enabled automatically. Figure 4 shows examples of executing Roll-Forward Recovery against a database.

Next, logging must be explicitly

started and stopped. Jobstreams should be written by the application team and supplied with software. *Figure 5* shows an example of a daily logging job.

Another thing to be aware of is that, like any other file, log files take space. If you log your files to disc, you must have adequate space for the files. If you're already low on disc space, this can be a problem, since *all* activity against a database will come to a screeching halt if there's no space available in the log file.

An additional warning about log-

or maximum flexibility — to allow both Roll-Forward and Roll-Back Recovery databases should be enabled for ILR and for Roll-Back.

ging transactions to disc files involves the problem of a disc failure. Since all data on a particular drive may be irrecoverable in the case of a head crash, care must be taken to place the disc log file on a separate logical device from the datasets in the database being logged. This way, if the database drive takes a hit, the log file still can be used. Ap-

plication teams can specify the LDEV when BUILDing the log file. This is done in the daily logging job shown in Figure 5.

An alternative is to log transactions to tape. However, this requires a dedicated tape drive. Furthermore, tape logging can be cumbersome and errorprone, since operator intervention is re-

quired to change tapes. This can lead to over-writing data, or to the stopping of activity against the database if the tape becomes full and another is not mounted

Finally, to ensure logical consistency, programs running against a database must be coded using the DBBEGIN and DBEND intrinsics. This will ensure that only complete transactions are posted to the database. If DBBEGINs and DBENDs aren't used, logging still can be used, but only physical integrity (through ILR) will be ensured.

How is logging used within our shop? First, not all application databases are enabled for logging. For some fairly stable resource files, like our validity table database, logging is unnecessary and isn't used. Since this file is updated only once a month, it's easy to recover. Update transactions sent from a central source simply can be reapplied. In this



In today's rapidly expanding and highly competitive computer

In today's rapidly expanding and highly competitive computer marketplace, making the right move in equipment and service options takes careful strategy. Sometimes, buyers "Play it safe" by purchasing well known, high quality products from the manufacturers, and end up paying royal prices.

HyPoint Technology chose to concentrate our expertise on Hewlett Packard and their high quality 3000 series. By offering previously owned HP equipment, often more reliable than brand new components, at costs of up to 50% less, we are leading our customers to make the right moves. And this equipment is guaranteed eligible for maintenance.

right moves. And this equipment is guaranteed engible for maintenance.

When you buy direct from HyPoint Technology, you are guaranteed to get quality selection, fast delivery, and performance you can depend on. Add this to our low price and professional service and you come up with a winner, every time

### HYPOINT TECHNOLOGY. INC.

4343 East Royalton Road • Cleveland, Ohio 44147 • (216) 526-0323

Specializing in the full line of HP 3000 hardware.

ENTER 111 ON READER CARD

### If your job depends on your computer... why haven't we heard from you yet?



Best Power Technology's UPS systems deliver clean, computer grade power more reliably, more efficiently, and more quietly than any other. With less heat, too. Best technology represents a true breakthrough in UPS design, and never relies on the raw incoming AC line as a backup.

Find out more about the elegant simplicity of a Best UPS. Find out why we're more reliable, and why we cost less to own, less to operate. Find out why Best is #1 in the world.\* Call for our NEW FREE CATALOG today!

Call 1-800-356-5794, ext. 3170 TODAY!

In Wisconsin call (608) 565-7200, ext. 3170



Best Power Technology, Inc. P.O. Box 280, Necedah, Wisconsin 54646

"Advanced Technology . . . for less."

\*The world's largest manufacturer of single phase UPS, based on KVA shipped.

**ENTER 101 ON READER CARD** 

case, the updates and the update program act as a substitute for TurboIMAGE logging.

For our volatile, heavy data-entry database applications, however, logging has been enabled by applications teams. For example, the repair order dispatching application has been using logging for many years. For this application, data entry input comes via telephone calls from customers needing service. This means that re-entering data is not only undesirable, but may be impossible! Logging ensures that no data will be lost in the case of a failure.

Our sales order processing system also now makes use of logging. In the past, this system made use of a central order file as a backup and insurance in the case of a system failure. With a new enhancement, not all data entered is

passed on to the central file. This makes logging mandatory for data recovery.

The application team has just completed the full implementation of DBBEGIN and DBEND calls around multidataset transactions. This will ensure that only complete transactions are written to the database. A sample program is shown in *Figure 6*.

Applications within our shop have supplied the data center staff with jobstreams to enable databases for logging, ILR and Roll-Back. These jobstreams also are careful to place log files on specific drives, away from the database's datasets. They also have supplied jobs to stop logging, store the database and start logging again. Finally, they have supplied jobs to recover the database in both Roll-Forward and Roll-Back methods.

Our experience with recovery situations is blessedly little! Some sites who have had major applications enabled for logging for years have never had to recover. However, logging recovery has been tested for each application using it, in rehearsal for what we hope never occurs. The few sites who have experienced power surges and other problems have recovered successfully and quickly with logging.

Implementing logging within your own shop will help you avoid that fiscal year-end situation I described earlier. Hopefully, the examples provided here will help you. Section 7 (Maintaining the Database) and Section 8 (Using Data Base Utilities) of the *TurboIMAGE Manual* can offer further information and assistance.

HP hardware and software is ex-

#### FIGURE JOB OMSBKUPJ, ADMIN/ADMPASS.MAS/MASPASS, OMSDTA/DTAPASS; OUTCLASS=XDEV, XRI !TELLOP COMMENT ! TELLOP STARTLOGJ - STEP 30 | TAPE MOUNT FOR "OMS" | OMSBKUPJ -OMSBKUPJ is used to backup the OMS COMMENT database and start a new logging ! COMMENT ! TELLOP !TELLOP This step will perform a DBSTORE of the OMS database. LCOMMENT Flags are set via DBUTIL prior to STOREing the data base and OMS backed-up. The logging files are then re-initialized, after which the log process is started and the data base flags reset for on-line updating. ! COMMENT ! TELLOP COMMENT !FILE DBSTORE-OMSDB; DEV-TAPE ! COMMENT !RUN DBSTORE. PUB. SYS COMMENT ! COMMENT ! COMMENT ! ! COMMENT ! COMMENT STEP 40 - PURGE OLDEST GENERATION OF LOG FILES AND BUILD NEW CURRENT LOG FILE ! COMMENT ISTEP 10 - STOP IMAGE LOGGING FOR OMS LCOMMENT ! COMMENT +----! ! PURGE OMSLOG2D TELLOP !RENAME OMSLOG2D.OMSLOG3D |OMSBKUPJ - STEP 10 !TELLOP !BUILD OMSLG001: CODE-LOG: DISC-10000.32.1: DEV-7 !COMMENT +-!TELLOP Please stop IMAGE logging for OMS by typing in : LOG OMSLOG, STOP ! TELLOP ! COMMENT STEP 50 - START IMAGE LOGGING FOR OMS !TELLOP ! COMMENT ! COMMENT +----!TELLOP + ! COMMENT !TELLOP STEP 20 - THE USER ACCESS FLAG IS DISABLED SO THAT !TELLOP IF THE DATABASE IS RESTORED FROM THE BACKUP MADE IN THE NEXT STEP, USERS WILL NOT BE ABLE TO ACCESS THE DATABASE UNTIL ! COMMENT ITFILOP ! COMMENT Please start IMAGE logging for OMS by typing !TELLOP in the following command !TELLOP COMMENT ALL THE RECOVERY STEPS HAVE COMPLETED :LOG OMSLOG START RECOVERY IS ENABLED SO THE DATABASE WILL BE ! COMMENT TELLOP READY FOR "DBRECOV" IF THE BACKUP IS RESTORED. ! COMMENT ! COMMENT ! COMMENT !COMMENT +----! COMMENT STEP 60 - RESET OMS DATABASE ACCESS AND LOGGING FLAGS TO ALLOW USERS TO ACCESS THE DATABASE, LOG TRANSACTIONS, AND NOT ALLOW RECOVERY. ! COMMENT LOGGING AND ILR ARE ENABLED FOR DESTORE ! COMMENT ! COMMENT ! COMMENT !RUN DBUTIL. PUB. SYS IRUN DBUTIL PUB.SYS DISABLE OMS FOR ACCESS ENABLE OMS FOR RECOVERY ENABLE OMS FOR LOGGING ENABLE OMS FOR ROLLBACK ! COMMENT ! COMMENT -! RUN DBUTIL.PUB.SYS ENABLE OMS FOR ACCESS DISABLE OMS FOR RECOVERY ! COMMENT + !TELLOP +-STEP 30 - "DBSTORE" OMS DATABASE !TELLOP | OMSBKUPJ - NORMAL COMPLETION ! COMMENT

82 HP PROFESSIONAL

tremely reliable. Murphy and natural disaster still can produce expensive data processing disasters, however. Wouldn't you sleep better at night knowing that by implementing logging, you've done all you can to prevent data loss? I know I do. —Lisa Burns Hartman manages an internal business software programming team at Hewlett-Packard Corporate Headquarters, Palo Alto, CA.

Would you like to continue to see articles on this topic?

Enter on reader card

yes 348 no 347

#### FIGURE 2110-ADD-ENTRY THIS PARAGRAPH ADDS A NEW USER TO THE PARAMETER THIS PARAGRAPH ADDS A NEW USER TO THE PARAMETER DATABASE. THE TRANSACTION WILL NOT BE LOGICALLY COMPLETE UNTIL THE USER IS ADDED TO BOTH THE MANUAL MASTER DATASET "SUPERVISOR-MAST" AND TO THE DETAIL DATASET "SUPERVISOR DETAIL DATASET "SUPERVISOR DETAIL DATASET "SUPERVISOR DETAIL DATASET SUPERVISOR DETAIL PAIR REASON," THE TRANSACTION IS BRACKETED BY DBBEGIN AND DBEND IMAGE CALLS. WHEN RECOVERY IS EXECUTED, THE DATABASE WILL BE LOGICALLY CONSISTENT, AS EITHER BOTH DBPUT'S WILL BE COMPLETED, OR NEITHER ONE WILL. THIS PARAGRAPH IS USED TO END TRANSACTION LOGGING INPUTS: ICP-BASE ICP-TEXT ICP-TEXTLEN COME-FROM-NUM OUTPUTS: NON-ERROR STATE ERROR STATE ICP-STATUS ICP-STATUS ERROR-FLAG ERROR-MSG COME-FROM-NUM (UNCHANGED) MOVE "2110" TO PARAGRAPH-NUM MOVE ALL SPACES TO NEW-SUPR-NAME SUPR-NAME SUPR-NAME OF SUPR-NAME OF SUPR-NAME OF SUPR-NAME OF SUPR-INFO. MOVE SUPR-NAME OF SUPR-SCREEN TO BRANCH OF SUPR-INFO. MOVE SUPR-INFO TO ICP-BUFFER. MOVE ICP-ALL-LIST TO ICP-LIST. MOVE SPACES TO ERROR-FLAG CALL "DREND" HISTNG TCP-RASE ICP-TEXT ICP-MODE1 TCP-STATUS \*Add to SUPERVISOR master PERFORM DB-BEGIN THRU DB-BEGIN-EXIT IF ICP-COND-CODE = 0 MOVE SUPERVISOR-MAST TO ICP-DSET PERFORM DB-PUT THRU DB-PUT-EXIT. GO TO DB-END-EXIT ELSE IF ICP-COND-CODE = -153 AND \*Add to SUPERVISOR detail ICP-BEGIN-CODE = 71 MOVE 0 TO ICP-BEGIN-CODE, ICP-COND-CODE MOVE SUPERVISOR-DTL TO ICP-DSET PERFORM DB-PUT THRU DB-PUT-EXIT PERFORM DB-END THRU DB-END-EXIT GO TO DR-FND-FXIT MOVE "I" TO ERROR-FLAC \*SHOW "SUCCESSFUL ADD" MESSAGE MOVE ICP-BASE TO ERR-FILE MOVE TOP-BASE TO ERR-FILE MOVE TOBERD FATAL ERROR TO ERR-MSG MOVE ICP-STATUS TO IMAGE-GEN-STATUS GO TO 9999-FATAL-ERROR-EXIT. MOVE "SUPERVISOR WAS ADDED SUCCESSFULLY" TO V-MESSAGE. PERFORM VIEW-PUTWINDOW THRU VIEW-PUTWINDOW-EXIT. DB-END-EXIT FXIT 2110-EXIT. EXIT DB-BEGIN. THIS PARAGRAPH IS USED TO ADD NEW ENTRIES TO A MANUAL MASTER OR DETAIL DATA SET. THE DATA BASE MUST BE OPENED \* IN ACCESS MODE 1, 3, OR 4. THIS PARAGRAPH IS USED TO BEGIN TRANSACTION LOGGING. INPUTS: ICP-BASE INPUTS: ICP-BASE ICP-TEXT ICP-TEXTLEN ICP-DSET ICP-LIST ICP-BUFFER COME-FROM-NUM COME - FROM - NUM OUTPUTS: NON-ERROR STATE ERROR STATE OUTPUTS: NON-ERROR STATE ERROR STATE ICP-STATUS ICP-STATUS ERROR - FLAG ICP-STATUS ICP-STATUS ERROR-MSG \* COME-FROM-NUM (UNCHANGED) \* COME-FROM-NUM (UNCHANGED) # \* \* \* \* \* \* \* \* \* \* \* \* \* \* \* MOVE SPACES TO ERROR-FLAG MOVE SPACES TO ERROR-FLAG CALL "DBBEGIN" USING ICP-BASE ICP-TEXT ICP-MODE1 ICP-STATUS CALL "DBPUT" USING ICP-BASE ICP-TEXTLEN ICP-STATUS ICP-LIST ICP-BUFFER IF ICP-COND-CODE = 0 OR = 71 MOVE ICP-COND-CODE TO ICP-BEGIN-CODE MOVE 0 TO ICP-COND-CODE GO TO DB-BEGIN-EXIT IF ICP-COND-CODE = 0 GO TO DB-PUT-EXIT ELSE MOVE "I" TO ERROR-FLAG MOVE "I" TO ERROR-FLAG MOVE ICP-BASE TO ERR-FILE MOVE "DBBEGIN FATAL ERROR" TO ERR-MSG MOVE ICP-STATUS TO IMAGE-GEN-STATUS GO TO 9999-FATAL-ERROR-EXIT. MOVE ICP-BASE TO ERR-FILE MOVE "DBPUT FATAL ERROR" TO ERR-MSG MOVE ICP-STATUS TO IMAGE-GEN-STATUS GO TO 9999-FATAL-ERROR-EXIT DB-BEGIN-EXIT EXIT DB-PUT-EXIT. EXIT.

Continued from page 24.

links to MPE/V systems using the same version of BACKCHAT running in compatibility mode.

The company also announced immediate availability of its Q-GEN reporting system in both native and compatibility modes. In addition, the native mode version generates native mode compiled report programs that reinforce the high performance of this product.

Full support of FLEXIBASE (its database management utility) on MPE/XL also is available.

Contact Randy Safier, Proactive Systems, P.O. Box 7102, Bloomfield Hills, MI 48302; (800) 356-7117; in Michigan (313) 333-7200.

Enter 394 on reader card

# RI030 Collects Simultaneous Data

Rapid Systems recently announced the R1030, a four-channel datalogger for PC XT/AT and compatibles. It collects eight-bit, simultaneous data continuously in real time to disc, printer or screen at rates of 10KHz and above, depending on your computer type and configuration.

The turnkey R1030 contains software and hardware to get users up and running in two minutes. The menu-driven software allows you to pass data directly to disc, printer or monitor in real time. Disc storage data format is well-documented so it can be readily retrieved for analysis.

Product highlights include one- to fourchannel simultaneous acquisition with multiplexing, internal/external analog/digital triggering, programmable start/stop time, burst mode for short highspeed data collection, Epson printer support, scrolling feature for data viewing, and more. Contact Rapid Systems, 433 N. 34th St., Seattle, WA 98103; (206) 547-8311.

Enter 374 on reader card

# Touchstone I.6 Improves Simulation Program

EEsof Inc. has introduced Touchstone 1.6, the newest generation of its linear simulation program for the design, analysis and optimization of microwave/RF circuits.

Touchstone 1.6 (\$9,900) features a new sparse admittance matrix reduction capability, full-feature screen editor commands, increased variable and equation faculties and more.

Touchstone 1.6's capability to perform sparse admittance matrix reduction of circuits lets you analyze large, complex circuits faster and provides more efficient use of computer memory. This technique offers an alternative and an addition to the existing scattering parameter reduction analysis presently available in Touchstone.

The user interface has been enhanced with new full-screen editor commands, including search and replace; repeat find command; file read/insert; and select, delete, move, copy and undo block. These features simplify the preparation of circuit files, especially large circuit files, where sections of code are repeated and/or available to be read from separate files.

Up to 250 variables plus equations can be represented in a circuit file. This feature offers you a greater capability to model relationships and characterize non-standard or proprietary circuit parameter relationships.

Touchstone 1.6 is available on the HP 9000 Series 300, IBM PCs and compatibles, DEC VAX series, Apollo and Sun Microsystems.

Contact Donn Mutch, EEsof, Inc., 5795 Lindero Canyon Rd., Westlake Village, CA 91362; (818) 881-7530.

Enter 397 on reader card

# T.S.I. To Distribute Communications Software

371355 (Alberta) Limited has appointed Timesharing Inc. (Jacksonville, FL) as the sole distributor of the HPE3 range of PC to HP 3000 communications software in the U.S. and Canada.

T.S.I. will be selling HPE3 through its own sales network of offices in Boston, New York, Chicago, Atlanta, Orlando, Denver, Jacksonville and Dallas, and through Value Added Resellers such as Micro Marketing and Sales Inc. of New York. T.S.I. will be selling HPE3 in tandem with its own range of external disc subsystems for the Hewlett-Packard minicomputers.

HPE3 is the second-generation evolution of the HPE2 product, developed in association with the Plessey Company in the U.K. and includes features such as a script processor/command language for the automation of PC-host sessions and file transfers, and online user-definable help.

Contact Glenn Johann, Timesharing Inc., Jacksonville, Florida; (800) 222-DISK.

Enter 375 on reader card

### CAPTURE, MANAGER Run On 800 Series Under UNIX


Industrial Computer Corporation has announced the release of its CAPTURE and MANAGER product lines running under UNIX on HP's 800 Series Precision Architecture systems.

CAPTURE was made a member of HP's National Account Program (NAP) in April 1987. It has been used to provide Shop Floor Data Collection and Control applications in a wide range of industries.

ICC also reports discussions with HP's European Marketing Center (EMC) in Lyon, France. ICC signed licensing agreements with Systems Integrators in Holland and the United Kingdom last year and is targeting availability of the first non-English versions of its products later this year.

Contact Industrial Computer Corp., 6065 Barfield Rd., Suite 114, Atlanta, GA 30328; (404) 255-8336.

Enter 390 on reader card



The R1030 four-channel datalogger collects eight-bit, simultaneous data in real time to disc, printer or screen.

4 HP PROFESSIONAL

# Expose the secret world of your **HP3000** with CIA. Gain the power to manipulate it simply, quickly.

This is top secret from Down Under. CIA is simply operating in Australia.

CIA stands for CPU I/O Analyser. It's the best way to improve the performance of your HP3000 without spending a fortune. And nothing, but nothing beats it for simplicity.

#### REVEAL ALL WITH CIA.

CIA simply and clearly displays all activity on your HP3000. Its carefully structured screens and reports give you quick and easy access to information vital to fine tuning your installation.

#### **ON-LINE MONITOR** SPILLS THE BEANS.

It's so simple! CIA displays a heading and six full screens for on-line monitoring. Switch between screens with just one function key.

#### 24-HOUR STAKE OUT.

CIA has a simple answer for reports on machine activity over extended periods. It monitors the system by taking 'snap shots' at intervals specified by you. Nothing complicated at all.

#### EXPERT DETECTIVE'S GUIDE.

CIA's manual is a model of clear, simple communication. You are briefed and guided through all the workings of your HP3000 and given all the pointers you need to collar culprits.

#### **GLOBAL EYE.**

CIA delivers all the goods on global activity to you, allowing you to review global CPU, memory and Disc I/O as well as individual processes activity. All simultaneously and simply.

#### CONCENTRATED POWER.

Want to narrow your field of investigation? CIA simply provides a comprehensive set of filters that allow you to concentrate on the important and ignore the unimportant.

#### PUT THE 'CPU HOG' IN ITS PLACE.

When your machine is unexpectedly attacked by that CPU Hog, you simply change the hog's queue priority with CIA. Presto! Everything's back to normal.

#### **NO NEED TO STEAL EXTRA FUNDS** OR LAUNDER MONEY.

CIA is remarkable indeed. But may be the cost is CIA's most remarkable feature of all. You don't need a bundle of money to pay for it.

### FREE DEMONSTRATION.

Arrange for our free demonstration of CIA today. Let us show you how CIA can simply and quickly put you in control of your HP3000.

Remember, more control over your HP3000 gives you more control over your career!

ENTER 108 ON READER CARD

### FAX DIRECT TO +6124845709 IN AUSTRALIA.

To: Facer Information Design	Name
PO Box 270, Epping, NSW 2121, Australia.	Company
Yes. Please send me a free demo tape of CIA.	Address
Yes. Please send me a free CIA manual.	State Zipcode
Yes. Please call and tell me more about CIA.  To speak to us personally at our secret	Phone
CIA Australian base, ring +61 2 484 3979	
after 4 pm US time.	
	SIMPLY EXPOSES SECRETS

# BayTech Develops Data Exchange System

BayTech has developed a high-performance Data Exchange System, Model 24, that allows peripheral sharing, computer-tocomputer communication plus buffering of print data.

The unit has a 16-bit CPU, plus multiple high-performance I/O processors that allow super high-speed transfer of data demanded by new faster computers and software.

Each Model 24 (\$895 - \$1,895) is customized by combinations of serial and parallel ports installed in four-port I/O modules to a maximum of 24 total ports. Ports are user-set as computer or peripheral ports, and data input and output are simultaneous on all ports. The standard 512-KB buffer is expandable up to 4½ MB. Computer-to-computer communication provides file transfer and database sharing capabilities concurrent with all operations.

The Model 24 is fully compatible with virtually all computers, printers, plotters, modems and other peripherals.

Contact Bay Technical Associates, 200 N. Second St., Bay St. Louis, MS 39520; (601) 467-8231.

Enter 373 on reader card

# Image-Pro II Provides New Interface


Media Cybernetics has released Image-Pro II, a new version of its image processing software.

Image-Pro II has a new interface and many enhancements. It gives users an option to select a single-monitor configuration with pull-down menus on the display monitor, or a dual-monitor configuration in which the menus appear on the system monitor.

Image-Pro II also provides free-form processing, a feature that allows processing on "n vertex polygonal areas," which users can specify by tracing the area they wish to process.

A new Install program walks the user through the procedure step by step. It creates the necessary directories and copies relevant files.

In Image-Pro II, Media Cybernetics introduces the HALO Format File (HFF), a new file format. HFF is an extension of the Tagged Interchange File Format (TIFF), which is endorsed by Aldus, Microsoft and Hewlett-Packard. It allows faster reading and writing of images and adds the ability to store the entire image definition in one file. HFF also will be portable across the family



BayTech's high-performance Data Exchange System, Model 24, allows peripheral sharing, computer-to-computer communication and buffering of print data.

of Image-Pro supported devices. Contact Media Cybernetics, 8484 Georgia Ave., Silver Spring, MD 20910; (800) 992-HALO.

Enter 377 on reader card

# I-2-4 Add-On Memory For LaserJet II

Pacific Data Products has announced upgradable add-on memory for HP's Laser-let Series II printers.

The "1-2-4" board (\$295) is fully compatible with the Series II memory expansion slot. It comes without memory in standard configuration and uses a unique socket arrangement to accept either 256K or 1-MB memory chips. The board can be configured to 1, 2 or 4 MB and may be upgraded at any time.

The LaserJet Series II requires extra memory for applications such as desktop publishing or design and drafting. The expandable "1-2-4" board eliminates the risk of selecting a memory board too small for an application. Resellers need to stock only one memory board instead of three and can offer memory upgrades at low cost as customers' application requirements change. Contact Pacific Data Products, Inc., 8525 Arjons Dr., Suite M, San Diego, CA 92126; (619) 549-0922.

Enter 388 on reader card

# CCS/C 3000 Implements XDS, Long Pointers

Corporate Computer Systems (CCS) recently announced ANSI function prototyping and long pointers on its CCS/C C Language Compilers. With versions available for both the HP 3000 and 1000, CCS/C now makes portable programming in C easier.

Release 2.0 of CCS/C 3000 is the only compiler to implement the draft ANSI C standard for function prototyping, which provides function argument typechecking and automatic type conversions. Function prototyping makes it easier for the programmer to generate better code with fewer bugs.

Even with ANSI standards, the MPE operating system provides a unique challenge for the C Language's portability feature in terms of its memory architecture. The MPE operating system provides extra data segments (XDS) to augment address space. However, source code has to be specially designed to XDS, causing problems when porting a program to another system. CCS has added long pointers to integrate the concept of XDS so the programmer can take full advantage of extended memory without sacrificing portability.


CCS/C 3000 allows transparent access to XDS that makes the program's stack and XDS homogeneous. Long pointers provide an extra benefit for programmers by making it easier to correctly access system tables. Although not ANSI standard, CCS/C's implementation of long pointers is compatible with C on the Spectrum class computers and IBM PCs.

Special features have been implemented for CCS/C 3000 so that programmers have a choice in development methods. Experienced HP 3000 programmers will find that it produces standard USLs, while C users coming from other environments like DEC, UNIX or IBM can produce "standard" C relocatables with the linkage edit approach, giving programmers a unique option for program development on the HP 3000.

Contact Corporate Computer Systems, Inc., 33 West Main St., Holmdel, NJ 07733; (201) 946-3800.

Enter 378 on reader card

# REE SUBSCRIPTION OFFER



If you're a Hewlett-Packard computer user, and buyer of HP-related hardware, software, or peripherals, HP PROFESSIONAL, the monthly magazine of Hewlett-Packard commercial and technical computing, is for you. It's really something. But it costs you nothing!

It's Informative. It's Monthly. It's Read by 30,220 professionals like you. It's FREE!

Read HP PROFESSIONAL for information and insights on the latest hardware, software, trends and developments.

Start your free subscription today . . .

Send us the coupon below. You'll receive a subscription application in the mail. Fill out and mail the application and if you qualify, we'll start your free subscription.

# Professional

### SUBSCRIPTION APPLICATION REQUEST

YES, I'd like a FREE subscription to HP PROFESSIONAL. Send a subscription application to:

Name	Title
Company	
Address	

State \_\_\_\_\_

Mail to: HP PROFESSIONAL, P.O. Box 445, Spring House, PA 19477-0445.


# **Teach Me/** 3000<sup>™</sup>

- \* Train new employees on the HP 3000
- \* Modules range from introductory material to system management
- \* Modules on IMAGE, VPLUS, COBOL and Dictionary for the programmer
- \* Less expensive than sending your staff to off-site classes
- \* Better trained employees become more productive, they have higher morale
- \* Improved job satisfaction leads to lower employee turnover
- \* Authoring language available to write your own modules
- \* Free demonstration tape available of all modules and authoring language

For more information, contact: Innovative Software Solutions, Inc. 10705 Colton Street Fairfax, VA 22032 U.S.A.



ENTER 116 ON READER CARD



#### NEW PRODUCTS

# Magnetic Tape Subsystem Supports 1000s, 9000s

A new dual-density 1600-/6250-bpi magnetic tape subsystem has been added to the family of IEEE-488 (HP-IB)-based subsystems available from Digital Automation Associates, Inc.

The Model 2444S supports the HP 1000 and HP 9000 computer families. The 2444B supports the AT&T 3B2 computer family and includes the IEEE-488 feature card and cable. The 2444P supports the IBM PC, XT/AT family and includes a host adapter and cable.

All three models of the new subsystem interface to the host over the IEEE-488 (HP-IB) bus and executes a command set compatible with HP 7970 tape transports. The Model 2444S runs with HP 1000 under RTE-A and HP 9000 under BASIC and HP-UX. The Model 2444B runs on AT&T computers under UNIX. The Model 2444P runs on PC-DOS or MS-DOS.

Contact Digital Automation Associates Inc., 310 W. Gypsy Lane Rd., Bowling Green, OH 43402; (419) 352-7526.

Enter 392 on reader card

# FASTRAN PLUS Increases CPU Speed

Performance Software Group recently announced FASTRAN PLUS, a significant enhancement to FASTRAN, its compiler for HP 3000 TRANSACT programs.

FASTRAN PLUS adds to the increase of CPU speed and file access speed in programs that access records sequentially, including records that come from IMAGE, KSAM and regular MPE files. In addition, any program doing sorts will run faster.

FASTRAN PLUS is a joint effort of Performance Software Group and RunningMate (Sacramento, CA).

Contact Performance Software Group, 12 Hillview Dr., Baltimore, MD 21228; (301) 242-6777.

Enter 383 on reader card

# MPEX/3000 Offers REDO Capability

VESOFT Inc. has announced that its MPEX/3000 productivity and system control tool has a REDO command that allows its users to redo any of the last 20 or more commands entered. The REDO facility frequently was requested by users to save personal time and effort when programming.

The REDO command is useful when correcting typing mistakes and helpful in utilities such as QUERY, FCOPY, SPOOK,

EDITOR KSAMUTIL, LISTDIR and other third-party utilities.

MPEX users can LISTREDO, REDO or DO commands by number or name, even in visual mode. MPEX also provides a special program, MPEXHOOK, which enables users to interface almost any utility to MPEX, allowing them to use this super-REDO facility inside EDITOR, QUERY, BASIC, etc. In addition, users can execute such commands as COBOL, PREP RUN and UDCs from within these utilities. Contact Eugene Volokh, VESOFT Inc., 1135 S. Beverly Dr., Los Angeles, CA 90035; (213) 282-0420.

Enter 391 on reader card

## VALUE-PACK Announced For HP Series 200/300

Applied Microcomputer Systems recently announced VALUE-PACK for the HP Series 200/300.

VALUE-PACK (\$145) provides wild-card copy, purge and catalog of disc files. An automatic central menu is easily configured to run any program on the system with a single soft-key. For those who use the system clock, VALUE-PACK sets and verifies time, or the clock can be set automatically by connecting an optional modem-clock.

VALUE-PACK runs on Series 200/300 computers with BASIC 3.0 or higher, and can be installed on any disc drive.

Contact Microcomputer Systems, Page Hill Rd., Chocorua, NH 03817; (603) 323-8666.

Enter 387 on reader card

# DRAWBASE Interfaces With SPACE Program

The DRAWBASE computer-aided design (CAD) software from SKOK Systems Incorporated now interfaces with the SPACE program from Graphic Systems Inc.

DRAWBASE (\$1,995 - \$4,995) includes 2-D drafting, 3-D design and database management capabilities. The integrated database is useful in facilities management because components such as areas, furniture and equipment that appear in the computer drawing are tracked with the database manager. As the drawing changes, the database manager updates the quantities automatically.

SPACE (\$495) is a planning and decision-making software for architects, interior designers and facilities managers. The package can perform affinity analysis and generate blocking and stacking diagrams. SPACE enables decision-makers to consider growth and shrinkage scenarios and their

costs before generating space plans.

The bidirectional interface can be used to import floor plans from DRAWBASE into SPACE's blocking module and export saved blocking and stacking diagrams from SPACE into DRAWBASE, which allows DRAWBASE designs to be analyzed with SPACE. Layouts that have been created with SPACE can be developed and detailed with DRAWBASE.

DRAWBASE is compatible with the HP Vectra 286-based model, IBM PC/XT and compatibles, and supports the HP ThinkJet printer and all HP pen plotters. SPACE supports the HP Vectra, IBM PC/XT and compatibles.

Contact SKOK Systems Inc., 222 Third St., Cambridge, MA 02142; (617) 868-6003.

Enter 386 on reader card

## QCI Announces BCL3000 Release 2.0

Quality Consultants, Inc., developer of BCL3000 (Bar-Code and Label Management System for the HP 3000), has announced Release 2.0 of the software, which allows users to design labels and/or bar-code formats and then modify them as needed.

BCL3000 (\$2,000 - \$5,000) accommodates almost any labeling need by generating user-defined labels using menu-driven screens. Release 2.0 allows users to define labels ranging in size from .1 by .1 inch to 13.2 by 16.5 inches. This enhancement allows printing of small labels for filing and mailing or large labels for shipping/manufacturing applications, signs and banners. Developers now are reporting that one hour of label/bar code development using BCL3000 is roughly equivalent to 40 hours of programming printer code.

With the addition of the Application Printing Module (APM), in Release 2.0, bar codes/labels automatically can be printed from any application system. Users need only define output from the application as an MPE Message File and define the Message File as data input in the APM Job Stream. As data is written from the application, bar codes/labels are printed to the specified device(s). In addition, the online "helps" in BCL3000 have been improved.

BCL3000 supports output to the HP 2934, HP 256X (with the HP Label Card and serial interface), Printronix printers (with the QMS Magnum Board) and the ATC 20/20 Thermal Transfer printer.

Contact Ken Kimbrough, Quality Consultants, Inc., 1775 The Exchange, Suite 380, Atlanta, GA 30339; (404) 980-1988.

Enter 382 on reader card



**ENTER 103 ON READER CARD** 

### Two Systems Provide Link For PROTOS Users

Perpetual Software And Consulting recently announced Release 1.0 of MyReport! End User Report Writer, and MyDictionary! Reporter for PROTOS users. Both software programs operate on the HP 3000.

MyReport! End User Report Writer (\$2,500 per HP 3000 system) interfaces with PROTOS software. A data dictionary is created on the HP 3000 and a file is passed on to a PC. The user walks through seven interactive screens to pass specific information about the report. A PROTOS code program is generated from the data and automatically transferred back to the HP 3000. The end user doesn't need any prior programming background to run the PC portion of the system; he may use actual names of datasets and fields, or may type in alias

MyDictionary! Reporter (\$1,000 per HP 3000 system) creates four separate reports from the ROOTDB. It may be run at any time without disturbing data already entered. The second program allows the DP department to enter specific descriptions about all databases, KSAM and MPE files, and fields into the database. The third program will permit printouts of database reports, fields within datasets and field-by-field reports. Contact Perpetual Software And Consulting, P.O. Box 704, Draper, UT 84020-0704; (801) 571-5749.

Enter 379 on reader card

### WIN/H3000 Provides HP 3000 MPE/V Support

The Wollongong Group, Inc. has announced WIN/H3000, a new addition to the Wollongong Integrated Networking Solutions (WINS) product family.

WIN/H3000 is a TCP/IP User Level Service product for HP 3000 MPE/V systems users who require TCP/IP user services over LANs and wide area networks. It provides TELNET (virtual terminal), FTP (file transfer) and SMTP (mail), which interfaces through the HP DeskManager.

WIN/H3000 uses the IEEE 802.3 stan-

dard for data transmission and is distributed on HP magnetic-reel tape. Options offered by Hewlett-Packard permit interconnection onto the Defense Data Network (DDN).


WIN/H3000 (\$7,500—\$12,000) features user-level TCP/IP services (governmentmandated protocols for system-to-system communication) for use with the ARPANET and MILNET components of the DDN, and allows HP 3000 users to network with other vendors in mixed-system environments. Contact the Wollongong Group, 1129 San

Antonio Rd., P.O. Box 51860, Palo Alto, CA 94303; (415) 962-7100.

Enter 389 on reader card

#### Correction

In the February issue, p. 82, the announcement "Printer Plot Converts HPGL To HP PCL" did not reflect a recent price increase. The correct price of Printer Plot is \$195. Contact James Associates, 1525 East County Road, Ft. Collins, CO 80525; (303) 484-5296.



### Hewlett Packard users worldwide know that the MegaRam is the most cost-effective way to lower system response times!

With access times in the microseconds, the MegaRam lets you add more users and applications while simultaneously improving performance. Increased performance results in better system utilization and

The MegaRam is particularly wellsuited for frequently accessed data, such as index/database files, scratch files and CAD/CAM, as well as for disk based operating systems. Or, use it as a high speed swapping and paging disk.

- Fully software compatible
- Easy to install; low maintenance
- Multi-ported
- Capacities from 2 to 128 Mbytes
- Both battery and magnetic backup
- Ideal for harsh environments

Interfaces via the HPIB, and supports the CS80 protocol, or via the I/O bus as a replacement for the MAC controller. Emulates the HP 79XX series of disk subsystems... and, the MegaRam is available now!

Request our new free brochure today!

**ENTER 112 ON READER CARD** 



With the MegaRam, the only thing going up is your productivity.

Imperial Technology, Inc. A Subsidiary of System Industry 831 S. Douglas Street · El Segundo, CA 90245 Telephone: (213) 536-0018 Telex: 664469 · Fax: (213) 536-0124

Remember how computers remembered? Mercury delay lines? Punched cards with 90 columns and round holes? Hand-wired magnetic cores? In case your memory needs refreshing, The Computer Museum would like to share its memories with you.

The Computer Museum Memory Poster We have created a limited edition, 20"x32" poster of the picture shown below. Printed in

full-color, it includes an identification key to help you recall the memories you've forgotten. To get your poster, along with an information kit on museum membership, exhibits and activities, send a tax-deductible contribution of \$25 or more to:


Memory Poster, The Computer Museum, 300 Congress Street, Museum Wharf, Boston, MA 02210.

Please allow six weeks for delivery.

**ENTER 148 ON READER CARD** 

## **COMPUTER MEMORIES FOR SALE**

Special thanks to this publication, Scitex America Corp. (color separations), Grafik Communications, Ltd. (design), David Sharpe Studio (photography) and VM Software, Inc. (poster).



# Need a total solution or just looking for the finishing touch?

#### Let the S/S/T TEAM

work for you! — Our purpose is to supply quality solutions in both software & hardware applications. In a timely manner at a reasonable cost. S/S/T is proud to be a Value Added Reseller for Hewlett-Packard


#### S/S/T Expertise

#### Software

- Membership/Contributor
- Portfolio Management
- Distribution
- Desk Top Publishing Document Scanning
- Loan Collection
- MCBA Software
- Q-DOC The Documentor
- DBTUNE/3000™
- HIBACK/3000™

#### S/S/T Services

• Training • Time sharing • System Conversions • Consulting



#### S/S/T Software Systems Technology, Inc.

305 Broadway New York, New York 10007 212-964-9600 (Phone) 212-233-4678 (FAX) 4996348 SST (Telex)

S/S/T carries the full line of

#### Dataproducts™ printers

#### Other locations:

Hardware (New and Used)

• IBM-Personal Computers

• Dataproducts Printers

Local Area Networks

Document Scanners

Zentec Terminals

• Texas Instruments Laser Printers

1581 Wayne Crest Plaza Route 23, South Wayne, New Jersey 07470 201-696-0112

1403 Northcrest Drive Silver Spring, Maryland 20904 301-384-1449

& West Germany

**ENTER 149 ON READER CARD** 

DBTUNE™ & HIBACK™ are registered trademarks of HI-COMP American

# Use your printer as an HPGL plotter

- √300 dpi on the LaserJet
- ✓ Color on the PaintJet
- ✓ Different line widths and line types on any HP-PCL printer

### **Printer Plot**

for Series 200/300 Basic, Pascal, HP-UX also available for IBM-PC and compatibles



James Associates 1525 E. County Rd. 58 Ft. Collins, CO 80524 (303) 484-5296

# ATTENTION WEST COAST HP PROS

HP PROFESSIONAL is searching for a West Coast editor in the San Francisco Bay area. If you have knowledge of Hewlett-Packard computer systems and are interested in writing feature and news articles, as well as software and hardware reviews, send your resume and writing samples to:

Managing Editor, HP PROFESSIONAL P.O. Box 445 Spring House, PA 19477

# HPS Scheduler Provides Batch Processing

HPS Software Developments Limited recently announced new features for the HPS Scheduler, a batch-processing controller for the HP 3000.

Now HPS Scheduler can catch every job as it is streamed ad hoc into MPE. New features include re-routing, conflict prevention and "hog control."

HPS Scheduler has a number of features that enable it to make the best use of system resources for batch jobs:

- streams jobs depending on the success or failure of previous jobs without the need for complex JCL or database setups;
- prevents jobs running with conflicting jobs or sessions while allowing freedom of choice in runtime and multistreamino:
- allows repeat running of regular jobs at any interval specified (i.e., daily, weekly, monthly);
- multiple streams of jobs can be managed to allow low-priority jobs to run in the background while high-priority job turnaround is unaffected;
- avoids the need for a wait queue that may be lost if the system fails;
- jobs can be submitted with simple commands or UDC;
- full job reporting; and
- runs outside privileged mode.

Contact HPS Software Developments Ltd., 196a Whittington Rd., London, England N22 4PD; telephone: 01-881 6644.

Enter 375 on reader card

# HP DeskManager Accesses Gateway/3000 For MCI Mail

HP DeskManager installations now can have worldwide public access with their Gateway/3000 for MCI Mail product.

Gateway/3000 from E-Mail Incorporated provides a cost-effective bridge between the capabilities of HP DeskManager and the various services offered by the public access network of MCI Mail.

Capabilities include electronic mail, telex and mail-delivered courier or postal. Gateway/3000 hosts this connection with an ordinary phone line and a standard terminal port without the hardware complexity and upkeep of bisynchronous protocols. In addition, it provides complete independence of HP DeskManager up/down times, node security, scheduling and message monitoring, multiline addressing, ASCII and binary file transfer, event logging and automatic error recovery.

Contact Customer Support, E-Mail Inc., 10905 Venice Blvd., Los Angeles, CA 90034; (213) 204-5540.

Enter 393 on reader card

#### **BUY • SELL • TRADE** Preowned HP

SYSTEMS - DESKTOPS - PERIPHERALS MISC

(509) 662-9039

#### **ELECTRONIC** SERVICES, INC.

PAYING TOO MUCH? GIVE US A CALL. IF WE DON'T HAVE IT. WE'LL GET IT!

FAX 509-662-8271

7 a.m. - 4:30 p.m. Pacific Time 10 a.m. - 6:30 p.m. Eastern Time 5187 - Suite A, Malaga-Alcoa Hwy Malaga, Washington 98828

**ENTER 182 ON READER CARD** 

### BUY . SELL . TRADE Series 80/100/ 200/300/9800

#### TED DASHER & ASSOCIATES

1220 33rd St. So. Birmingham, AL 35205 (205) 324-8526 (813) 855-9555 Fax# 205-324-1974

We specialize in 310's. 9816's. 9817's. 9836's and all peripherals

ENTER 193 ON READER CARD



1000 3000 9000 HP systems & peripherals Bought & sold with integrity

Guaranteed for HP maintenance Personalized

1209 U.S. Hwy. 19 N. Suite 223 Palm Harbor, FI 34684 813-785-6003

SERVICE

**ENTER 190 ON READER CARD** 

# UNBEATABLE

Due to a bulk purchase agreement with the manufacturer, Century Peripherals can now offer the high quality Zentec 8392, that normally sells for \$849.00, at the unbeatable price of \$595.00.

HERE'S WHAT YOU GET

- Fully compatible with the HP 2392A and the HP 700/92

  Brand new terminals, amber or green phosphor

  Full one year factory warranty

  30 day money-back guarantee

  Immediate delivery

  Nationwide maintenance network

Call today to order while stock lasts! (U.S. and Canada only)

CENTURY PERIPHERALS\_

6020 Washington Blvd. Culver City, CA 90232

(800) 443-0100 Extension 165B Orders only (213) 202-0401 Extension Z Questions only

**ENTER 175 ON READER CARD** 

### **HEWLETT-PACKARD**

BUY and SFIL

REPAIR and SERVICE

Computer Exchange

**HP Systems Specialists** 

US (800) 824-8418 (209) 823-6777 FAX (209) 823-3304

**ENTER 171 ON READER CARD** 

### Why Not ... Used HP

Delivery, Savings, **Guaranteed Maintenance** HP 3000/9000/1000/100/80 Buy, Sell, Lease, Trade

- SPECIALS -3000/37W/1Mb, PIC, ATP-37

7945A & 9144A . . . . . . . . . \$9,500 Add 7945A . . . . . . . . . . . 2,500 Add 7914P . . . . . . . . . . . 4,200 Add I/O Bay ......3,500

WESTCHASE COMPUTER COMPANY 800-538-8013/245501 713-589-7671 FAX 713-589-7690

**ENTER 195 ON READER CARD** 

### **HP CAREERS NATIONWIDE**

#### TIME TO MAKE A CHANGE IN YOUR CAREER?

To aid in your search, call DIANE AMOS for experienced, professional, confidential, and friendly help. Specializing 100% in the HP market nationwide, here is your connection. Tell me where you want to live and the position you desire, and I'll find it! Numerous opportunities available.



Call Diane Amos, C.P.C.

Amos & Associates

633B Chapel Hill Road Burlington, NC 27215 (919) 222-0231

### LARGE DISCOUNTS

82906A Graphics Printer ....\$400 82901M 51/4" Dual Disc . . . . . \$425 9845A Needs Repair, Buy For Parts .....\$1000 98256A 256K Memory . . . . . . \$150 98627A RGB Interface . . . . . . \$495 98635A Math Floating Pt. . . . . \$395 9134XV 15 Mbyte Hard Drive . \$795 7475A 6-pen plotter, R\$ 232 . . \$750

We have a large stock of used HP 310's B & W, Color, all monitors, video boards.

> TED DASHER & ASSOCIATES (205) 324-8526 (813) 855-9555 Fax# 205-324-1974

\* HP Cables (Custom Lengths)

\* ATP Connectors (3 & 5 Pin/Male)

**ATP** Octopus Cables

- \* Custom Cables
- \* Excellent Delivery

Call Joe Walton Illinois Computer Cable, Inc. 1-800-323-2612 (312) 810-0200

# IBM HP File Interchange

PCLIF is a software utility which permits the transfer of files between IBM PC's, PS/2's and HP technical (LIF) computers thru the exchange of floppy disks. Using the PC for 5.25" or the PS/2 for 3.5" transfers does not require additional hardware. An internal and an external 3.5" disk drive is available to allow the PC family to perform 3.5" disk transfers.

Innovative Software Systems 14252 Culver Dr., Suite A-444 Irvine CA 92714 (714)249-2056

**ENTER 185 ON READER CARD** 

### 30-60% OFF LIST

in Inventory
Fully Guaranteed



Performance — Not Promises!

8370 Dow Circle • Cleveland, OH 44136 216•234-8040

**LDLA** 

BUY • SELL • LEASE • TRADE

WANG digital

**ENTER 187 ON READER CARD** 

#### HP1000 & 3000



- BUY·SELL·LEASE·RENT
- Repair & Exchange
- \$3,000,000 Inventory
- 120 Day Warranty
- 20 Years Experience
- Hardware · Software · Service

Computer Solutions, Inc.

NJ 201/672-6000 • CA 213/541-7171 TLX 130098 • FAX 201/672-8069

**ENTER 178 ON READER CARD** 

#### FOR SALE OR LEASE

HP 2680A LASER
INTELLIGENT PAGE PRINTER

With Ext. Mem/Graphics Package 3.5 Million Rotations

HP CERTIFICATE
OF MAINTAINABILITY

C.S.U. INDUSTRIES, INC. (516) 239-4310

**ENTER 173 ON READER CARD** 

### HP

9000,3000,1000,

100,80 series or ATE CompuChange

813-796-8388

Buy • Sell • Trade

**ENTER 176 ON READER CARD** 

# C.S.U. INDUSTRIES, INC.



# The second source for HEWLETT-PACKARD 3000 equipment

- Complete Configurations
- Individual CPUs Peripherals
   Memory Upgrades and Feature Enhancements

WE BUY: Highest Prices Paid

#### WE SELL:

All Items Sold Are Guaranteed for HP Maintenance
\* Trade-Ins Accepted \* Short and Long Term Leases Available \*
Over 850 satisfied Hewlett-Packard users
are our customer references.

CALL (516) 239-4310 ASK FOR CAROL.

135 Rockaway Turnpike • Lawrence, NY 11559

ENTER 180 ON READER CARD

### **HP 3000**

WE BUY & SELL Guaranteed for HP Maintenance

Call 713-690-6100 CBSI

4407 Clark, Houston, TX 77040

## The HyPoint Advantage . . . INVENTORY

"Specializing in Full Line of HP 3000 Products"

Buy ■ Sell ■ Trade ■ Lease

HyPoint Technology 550 E. Royalton Road Cleveland, OH 44147

1-800-231-5500 216-526-0323

#### **HEWLETT-PACKARD**

1000 • 3000 • 9000 • 250

BUY-SELL RENT-LEASE

Maintenance Disaster Recovery Services

Processors, Peripherals, & Systems

# EURODATA INC. 613-745-0921

2574 Sheffield Rd. Ottawa, Ontario, Canada K1B 3V7 Fax: 613 745-1172 Telex: 053-3259

ENTER 183 ON READER CARD

**ENTER 174 ON READER CARD** 

**ENTER 184 ON READER CARD** 

HP 3000 S/70 & S/68

### HP 7933H

404 Mb Disc Drives

#### Can for current price

COMPLETE HP 3000 SYSTEMS AVAILABLE

All items in stock — immediate delivery.

Subject to prior sale.

All warranted to qualify for manufacturer's maintenance.

#### **ConAm Corporation**

It's Performance That Counts!

800/643-4954 • 213/829-2277 FAX 213/829-9607

**ENTER 179 ON READER CARD** 



**ENTER 189 ON READER CARD** 

#### **HP-IB** to Centronics Converter



MicroPrint 45C
NEED AN EXTRA PRINTER FOR YOUR HP
COMPUTER? The MicroPrint 45C is the solu-

tion you've been waiting for - an inexpensive way to use an inexpensive printer with your HP computer.

\*Use with any HPIB Computer

\*Use with any Centronics Printer

\*No programming, transparent to system

\*Laser Printer compatible

\*1 year warranty

INTELLIGENT INTERFACES INC. 1-800-842-0888

In Georgia (404) 381-9891 Telex: 9102502628 INTELLIGENT UD

**ENTER 186 ON READER CARD** 

### **HEWLETT-PACKARD**

Buy, Sell, Rent and Repair Computers, Peripherals and Options

\* \* \* \* \* \* \*
SALES SERV

**SERVICE** 

(408) 270-1100 (408) 270-1170

\* \* \* \* \* \* \* \* \* FAX — (408) 270-1183

ELM - 62015192

ELM = 62015192

TELEX — 9102500341

### CRISIS COMPUTER CORP.

2298 Quimby Road San Jose, CA 95122-1356

**ENTER 181 ON READER CARD** 

### 9000, 3000, 1000

SYSTEMS
PERIPHERALS
COMPATIBLES

Buy • Sell • Trade Maintenance



(206) 883-4107

**ENTER 197 ON READER CARD** 

### Save up to 60%!

Top dollar when you sell!

We buy or sell any HP equipment, including:

COMPUTER SYSTEMS • DISK DRIVES SOFTWARE • ACCESSORIES TERMINALS • MAG TAPES

All Equipment Guaranteed.

Specialists in hard-to-find equipment. Immediate delivery of in-stock items.

CALL Bill Alexander at

312-916-1400 FAX 3129161361

COMPUTER MEDIA, INC.

1420 Brook Drive Downers Grove, IL 60515

**ENTER 177 ON READER CARD** 

### VT 100/102/220

Terminal Emulation File Transfer

- For Series 200/300
- Runs Under Basic



\$395.00

30-day unconditional money-back guarantee

#### SYSTEM WORKS

4318 Centennial Trail Duluth, GA 30136

(404) 446-6098

Preferred by major
U.S. industries & educational institutions.

### **BUY • SELL • RENT • LEASE**

### HEWLETT-PACKARD Computer Equipment

SERIES 80, 100, 200, 300, 9800

ALSO . . . Plotters, Printers, Disk Drives, CPUs, Printers, etc. Available for Immediate Delivery

800-422-4872 FAX 713-855-1213

### **TSA**

TECHNICAL & SCIENTIFIC APPLICATION, INC.

4654 Highway 6 N., Suite 101 Houston, TX 77084

ENTER 192 ON READER CARD

# NORCO COMPUTER SYSTEMS, INC.

Hewlett-Packard Quality at a NorCo Price

1000 • 3000 • 9000 • 250

BUY — SELL TRADE — LEASE

Processors, Peripherals and Systems 925D Bassett Road

925D Bassett Road Cleveland, OH 44145-1108 FAX 2168925507

**216-892-1920 1-800-892-1920** (Outside Ohio)

ENTER 188 ON READER CARD

#### **ADVERTISERS INDEX**

Reade	r Service Number	Page	Re
137	Adager	.68-69	11
171	Advant Computer	93	11
172	Amos & Assoc	93	11
101	Best Power Technology, Inc	81	11
	Bradford Business Systems Inc		11
150	Bradmark Computer Systems, Inc	5	18
102	Cardinal Data Corp	61	11
103	Carolian Systems International, Inc	89	18
174	CBSI	94	11
175	CBSICentury Peripherals	93	14
104	Cognos Corp.	1	12
105	Collier-Jackson Inc.	71	12
176	CompuChange	94	18
197	Computech Systems Corp	95	14
177	Computer Media Inc	95	12
148	Computer Museum	91	12
178	Computer Solutions, Inc	94	18
106	COMSCI Data Systems Inc	33	12
179	Con Am Corp	95	13
145	Cort Directions	50	18
181	Crisis Computer	95	13
173	CSU Industries Inc	94	12
180	CSU Industries Inc	94	
151	DEC Professional	48	12
107	Digital Products	58	12
131	Dynamic Information Systems Corp	19	
182	Electronic Services, Inc	93	19
136	EMC Corporation	9	14
183	Eurodata Inc.	94	14
108	Facer Information Design	85	19
	Hewlett Packardsupp	lement	13
109	Hewlett-Packard (Finance/Remarketi	ng).43	19
117	Hewlett-Packard (PC VECTRA)	6-7	19
130	Hewlett-Packard (Software)	55	19
135	Hi-Comp International	45	14
	HP Professional	87	12
111	Hypoint Technology	81	14
184	Hypoint Technology	94	14
196	Illinois Computer Cable, Inc	93	19
134	IMACS Systems Corp	11	14

Read	er Service Number	Pag
112	Imperial Technology	90
113	Indigo Software Ltd	37
114	Industrial Computer Corp	21
115	Infocentre Corp	17
116	Innovative Software Solutions	88
185	Innovative Software Systems	94
118	Intelligent Interfaces, Inc.	4
186	Intelligent Interfaces, Inc.	95
119	IOTECH	88
146	James Associates	92
120	JOBSCOPE	79
129	Martinsound Technologies	67
187	Martinsound Technologies	94
141	Minisoft, Inc	56
122		60
123	NECRUG	70
188	Norco Computer Systems, Inc	95
124	NSD, Inc.	25
133	OPT	2
189		
	P.C.M	
125		
	Professional Press64	
126		
127		65
	SAS Institute	-27
190		93
147		4
149		92
191		
139		59
192		95
193		
194	Ted Dasher & Associates	
142	Tri Data Systems, Inc	
	Tymlabs Corp.	13
140		/5
143	Walker, Richer, & Quinn, IncB.Co	vei
195		93
144	Zentec CorpI.F.Co	vei

### [CALENDAR]

#### [ APRIL ]

**18-20:** Interex HP 1000 Users Conference, Lyon, France. Contact Interex, Conferences, 680 Almanor Ave., P.O. Box 3439, Sunnyvale, CA 94088-3439; (408) 738-4848; Telex: 4971527.

**24-26:** SIGRAPID Users Group Conference, Red Lion Inn/Seatack, Seattle, WA. Contact Robert F. Meissner, Welding Engineers Inc., R. D. #1, Kulp Rd., Pottstown, PA 19464.

**26:** CINMUG (Cincinnati Metropolitan Users Group) half-day seminar on "HP Fourth Generation Language," Hewlett-Packard, Cincinnati, OH. Contact P.G. Landwehr, Vulcan Corp. (513) 621-2850.

#### [ MAY ]

9-10: Performance Maximization Seminar, Toronto, Canada. HP 3000-related seminar sponsored by Volz Associates (Winthrop, MA). \$525 includes course materials, lunches and refreshments. Discounts available for three or more from the same company attending the same session. Contact Charles H. R. Volz, Volz Associates, Inc., 15 Pauline St., Winthrop, MA 02152-3011; (617) 846-3837.

17-20: SCRUG '88 Technical Conference and Vendor Show, The Pasadena Center, Pasadena, CA. Pre-conference tutorial for new users May 17 (extra charge). Two-day vendor show May 18 and 19. Conference fee

\$175 for full conference, \$75 per day. Call Karen at (213) 453-5664 or write P.O. Box 84219, Los Angeles, CA 90073.

**18-20:** CAP International 1988 Hard Copy Supplies Conference, Marriott Long Wharf, Boston, MA. Contact Martha Johnson, CAP International, One Snow Rd., Marshfield, MA 02050; (617) 837-1341.

**19:** GHRUG, Inc. (Greater Houston Regional Users Group, Inc.) one-day meeting, Hilton Hobby, Houston, TX. For more information, contact Suzanne Spitzer (713) 977-3193.

25: DAYMUG (Dayton Metropolitan Users Group) and KYRUG (Kentucky Regional Users Group) joint meeting, Ramada Inn, I-71 and Pfeiffer Rd. exit, Cincinnati, OH. Speakers are Brian Duncombe (Triolet Systems) and Mike Hornsby (Hewlett-Packard, Cincinnati, OH) on "System House-keeping." Contact P.G. Landwehr, Vulcan Corp. (513) 621-2850.

**30-June 3:** The International HP Users Conference, Goteberg, Sweden. Write Box 266, S-421 23 V. Frolunda, Goteberg, Sweden.

31-June 3: NECRUG Ninth Annual Eastern American HP Users Conference, The Trump Plaza, Atlantic City, NJ. Fee for members \$275 if you register by April 29; \$315 thereafter. Early/late non-member fees, \$300/\$400. Exhibitors call Jeri Fuller, U.S. Mortgage Insurance Co., (215) 825-4666.

### **SALES OFFICES**

ASSOCIATE PUBLISHER/
MARKETING & SALES

ADVERTISING
SERVICES MANAGER Connie Mahon
ADVERTISING
COORDINATOR Lori Goodson
LIST RENTAL COORDINATOR Cathy Dodies

VICE PRESIDENT Helen B. Marbach

POSTCARD DECKS Mary Browarek

#### **REGIONAL SALES MANAGERS**

CANADA Helen B. Marbach
MID-ATLANTIC Mark Durrick
SOUTH ATLANTIC Cynthia Leitzel
MIDWEST/SOUTHEAST Peter Senft

Professional Press, Inc. 921 Bethlehem Pike Spring House, PA 19477 (215) 542-7008

#### NEW ENGLAND/ INTERNATIONAL

(617) 861-1994

Leslie Ringe Professional Press, Inc. 238 Bedford Street, Suite 3 Lexington, MA 02173

### NORTHERN CALIFORNIA and NORTHWEST

A. G. Germano Regional Sales Manager Alonna Doucette Account Executive

Professional Press, Inc. 715 El Camino Real, Suite 206 San Bruno, CA 94066 (415) 873-3368

#### SOUTHERN CALIFORNIA/ SOUTHWEST/COLORADO

David Beardslee Regional Sales Manager

Karen Altonaga Account Executive

Professional Press, Inc. 1010 East Union Street, Suite 101 Pasadena, CA 91106 (818) 577-5970





### SmarTerm 2392. HP terminal emulation. Perfect solution.

To access Hewlett-Packard 3000 applications, you no longer need an HP terminal. SmarTerm® 2392 emulation software, running on an IBM® or compatible PC, provides host-system connectivity for a perfect \$225.


Virtually every HP 2392 terminal capability, including printer support, is duplicated. HP, ANSI, EM52 text handling and 132-column display mode are fully supported. As are European DOS and international keyboards.

Communications features include Kermit and Xmodem protocols, file overwrite protection, background file transfer, RAM-resident operation, and 2-way trace mode.

Window-based setup allows for multiple system configurations, remappable keyboards, and smart softkeys making SmarTerm 2392 exceptionally easy to use. On-line help makes it easy to master.

Contact your dealer or call us at 608-273-6000 for more reasons why your choice for HP terminal emulation should be SmarTerm. Period.







How can you connect hardware and software systems as diverse as Hewlett-Packard and DEC minis, IBM and Macintosh PCs, Novell, Ungermann-Bass, and Bridge's 3Com- and IBMcompatible LANs? With the Reflection Series software solution.

Reflection supports the widest variety of minicomputers, personal computers, LANs, and communication protocols of any single vendor.

Sophisticated features like command language, file transfer, background processing, and the PLUS backup option, give you the power you need to achieve your unique connectivity objectives.

RSVP and Dispatch address special needs of host-connected PCs. They take you one step further in automating your Reflection office.

Call us today to join over 100,000 satisfied Reflection users.

1-800-872-2829

**ENTER 143 ON READER CARD** 

**Reflection 2 Plus** VT220 and Tektronix 4010 graphics. Reflection 3 Plus HP 2623A, HP 2392A and VT102. **Reflection 7 Plus** HP 2627A color graphics, HP 2392A and VT102. Reflection for the Macintosh HP 2392A emulation. DISPATCH New independence from HPDesk. Links your PC with host-connected printers.

HP 2392A and VT102 emulation.

**Reflection 1 Plus** 



Walker Richer & Quinn, Inc.

2825 Eastlake Ave. E., Seattle, WA 98102 (206) 324-0350